

ellucian.

Banner Advancement Object:Access Reporting Guide

Release 8.7
December 2013



Banner®, Colleague®, PowerCampus™, and Luminis® are trademarks of Ellucian Company L.P. or its affiliates and are registered in the U.S. and other countries. Ellucian®, Ellucian Advance™, Ellucian Degree Works™, Ellucian Course Signals™, Ellucian SmartCall™, and Ellucian Recruiter™ are trademarks of Ellucian Company L.P. or its affiliates. Other names may be trademarks of their respective owners.

©1996-2013 Ellucian Company L.P. and its affiliates.

Contains confidential and proprietary information of Ellucian and its subsidiaries. Use of these materials is limited to Ellucian licensees, and is subject to the terms and conditions of one or more written license agreements between Ellucian and the licensee in question.

In preparing and providing this publication, Ellucian is not rendering legal, accounting, or other similar professional services. Ellucian makes no claims that an institution's use of this publication or the software for which it is provided will guarantee compliance with applicable federal or state laws, rules, or regulations. Each organization should seek legal, accounting and other similar professional services from competent providers of the organization's own choosing.

Prepared by: Ellucian
4375 Fair Lakes Court
Fairfax, Virginia 22033
United States of America

Revision History

| Publication Date | Summary |
|-------------------------|--|
| December 2013 | New version that supports Banner Advancement 8.7 software. |

Banner Advancement 8.7

Object:Access Reporting Guide

Contents

| | | |
|------------------|--|------------|
| Chapter 1 | Overview | 1-1 |
| | Banner Object:Access Architecture | 1-1 |
| | Object:Access Terms | 1-1 |
| | View | 1-1 |
| | Attribute | 1-1 |
| | Function | 1-2 |
| | Key Attribute | 1-2 |
| | Mandatory/Recommended Condition | 1-2 |
| | Repeating Groups | 1-3 |
| | Indicators | 1-4 |
| | Information Indicators | 1-4 |
| | Additional Entries Flag | 1-5 |
| | Addresses | 1-6 |
| | Telephone Numbers | 1-6 |
| | PIDM | 1-6 |
| | Manual Layout | 1-6 |
| | View Layout | 1-7 |
| | View Name | 1-7 |
| | Prefix | 1-7 |
| | Attribute List | 1-8 |
| | Reference Numbers | 1-8 |
| | How to Create a Report | 1-9 |
| Chapter 2 | Advancement Object:Access Views | 2-1 |
| | Key Attributes | 2-2 |
| | Recommended/Mandatory Conditions | 2-2 |
| | Attributes | 2-3 |

| | |
|--|-------|
| Key Attributes | 2-15 |
| Recommended/Mandatory Conditions | 2-16 |
| Attributes. | 2-16 |
| Key Attributes | 2-31 |
| Recommended/Mandatory Conditions | 2-32 |
| Attributes. | 2-32 |
| Key Attributes | 2-46 |
| Recommended/Mandatory Conditions | 2-47 |
| Attributes. | 2-47 |
| Key Attributes | 2-61 |
| Recommended/Mandatory Conditions | 2-61 |
| Attributes. | 2-62 |
| Key Attributes | 2-85 |
| Recommended/Mandatory Conditions | 2-85 |
| Attributes. | 2-86 |
| Key Attributes | 2-102 |
| Recommended/Mandatory Conditions | 2-102 |
| Attributes. | 2-103 |
| Key Attributes | 2-112 |
| Recommended/Mandatory Conditions | 2-112 |
| Attributes. | 2-113 |
| Key Attributes | 2-122 |
| Recommended/Mandatory Conditions | 2-123 |
| Attributes. | 2-123 |
| Key Attributes | 2-131 |
| Recommended/Mandatory Conditions | 2-132 |
| Attributes. | 2-132 |
| Key Attributes | 2-140 |
| Recommended/Mandatory Conditions | 2-140 |
| Attributes. | 2-141 |

1 Overview

Banner Object:Access Architecture

Each Banner system contains a wealth of information stored within a myriad of database tables. Banner Object:Access is a technical architecture that makes it easier for you to access that information. The result is increased ability to create ad hoc reports easily and quickly.

The Banner Object:Access architecture uses logical views to bring together the essential fields for a specific area of reporting. These views give you the ability to tailor reports to your specific needs using the reporting tool of your choice. Without Banner Object:Access, which combines the information for you, you would need an extensive knowledge of Structured Query Language (SQL) to combine information from several tables into one report. Object:Access Reporting Guide Object:Access Reporting Guide

Object:Access Terms

Understanding some general terms increases your ability to use Object:Access views.

View

A view, or logical view, is a grouping of information. It is called a “logical” view because information in the view is grouped in a logical order, putting related information in the same section of the view. For instance, in the Object:Access people-related views all of the name information is grouped together at the beginning of the view, followed by personal, biographic, and demographic information.

Most information in a view comes from fields within the Banner database tables. Some information is calculated based on database fields or retrieved using an Oracle function. A single view can include up to 255 pieces of information, called attributes.

Attribute

An attribute is one piece of information within a view. Many of the attributes in the Object:Access views come directly from a field in the Banner database. Other attributes are derived from Banner fields either through calculations or the logic defined in a function.

Function

A function is a small piece of code that uses some specified logic to get information from the Banner database that is not stored as a single field. For example, “Age” is not stored as a field in Banner. Using a function that subtracts birthdate from today’s date and then determines whether the birth month has passed, we can provide age as an attribute in many Object:Access views.

Ultimately, the use of functions in the Object:Access views expands the Banner database. You can get calculated information by selecting a single attribute rather than having to set up the calculation in your report.

Key Attribute

Certain attributes within each view are called “key attributes.” The key attributes determine the level of information returned by the view.

This concept is illustrated in the following sample Banner Human Resources report. In the sample, the key attributes differentiate whether a view returns one row of information for each person per position or simply one row for each person. In this report there is one row of information for each position that a person applied for, not just one row per person. This is because the key attributes of the view used to create the report are the **Applicant’s PIDM** and the **Position Applied For**.

Position Applicant List

| Name | Position | Position Title | Degree |
|--------------|----------|--------------------|--------|
| Sam Abrams | DIR001 | Director, HR | MS |
| | DIR002 | Director, Payroll | MS |
| Kevin Dillon | DIR001 | Director, HR | MBA |
| Sara Harper | DIR004 | Director, Benefits | MS |
| Clare Jones | DIR001 | Director, HR | MBA |
| | DIR002 | Director, Payroll | MBA |
| | DIR004 | Director, Benefits | MBA |

Notice that multiple rows are returned when a person has applied for more than one position.

Mandatory/Recommended Condition

Some views contain mandatory or recommended conditions. To obtain information at the level identified by the key attributes, you must supply these conditions when you create your report. (Refer to [“Key Attribute” on page 1-2](#) for more information about this.) In many of the Banner Student views, you need to provide a term to obtain the results described in the view. The following sample reports compare the results that occur when a term *is not* provided and when a term *is* provided.

Sample Report 1

List of Students by State

| Name | State | Phone | Term | |
|-----------------|-------|--------------|--------|---|
| Tim Parker | PA | 555-243-9765 | 200701 | The mandatory condition TERM_CODE_KEY was not supplied, so there is a row for every term in the database. |
| Tim Parker | PA | 555-243-9765 | 200703 | |
| Tim Parker | PA | 555-243-9765 | 200801 | |
| Allison Parshaw | OR | 555-624-8339 | 200801 | |
| Omar Patil | IL | 555-978-4122 | 200703 | |
| Omar Patil | IL | 555-978-4122 | 200801 | |

Sample Report 2

List of Students by State

| Name | State | Phone | Term | |
|-----------------|-------|--------------|--------|---|
| Tim Parker | PA | 555-243-9765 | 200801 | The mandatory condition TERM_CODE_KEY = 200801 was supplied, so only the rows in that term were returned. |
| Allison Parshaw | OR | 555-624-8339 | 200801 | |
| Omar Patil | IL | 555-978-4122 | 200801 | |

In some cases the first sample report may be what you want. If so, do not supply the mandatory condition for the view. Basically, you need to supply the mandatory conditions to ensure the view meets the specified reporting need.

Note

In some cases, performance may be an issue if a mandatory condition is not supplied. ■

Repeating Groups

Several areas of Banner allow multiple values to be stored in a record. Some examples of fields that can have more than one value are address, donor category, and test code. To allow retrieval of more than one value for a field, Banner Object:Access flattens some fields. This means that where a Banner table may store five values of a particular code in one field, Object:Access has five attributes, one for each value. These attributes are called a repeating group.

The following example shows how Tim Parker's four test codes are stored in the database and how they are reported using Banner Object:Access.

| Name | Test Code (SORTEST_TESC_CODE) | |
|------------|-----------------------------------|--|
| Tim Parker | SATV | } _____ In the database, multiple values for a field are stored in the same field in the Banner table. |
| Tim Parker | SATM | |
| Tim Parker | ACT | |
| Tim Parker | GRE | |

| Name | Test Codes (TEST_CODE1 TEST_CODE2 TEST_CODE3 TEST_CODE4) | | | | |
|------------|--|------|-----|-----|---|
| Tim Parker | SATV | SATM | ACT | GRE | _____ In the O:A views, multiple values are flattened out, allowing for detail reports with one row per person. |

Due to the limit of 255 attributes per view, Banner fields are carefully selected for inclusion in each view. The size limitation affects repeating groups the most.

For example, suppose you store ten different addresses for one person in the Address Repeating Table (SPRADDR). Most Object:Access views retrieve eleven fields of address information from this table. Each field is considered a different attribute in the view. If we allow space to retrieve these eleven attributes for all ten addresses, we will use 110 of the 255 attributes allowed. You can see how the number of attributes can quickly add up.

 **Tip**

Each repeating group has a limit on the number of values returned. ■

Therefore, sensible limits are set within each view for retrieving information for a repeating group. For example, most Object:Access people-related views let you retrieve information on two addresses per person. This uses only 22 attributes instead of the 110 used in the scenario above. Addresses are just one example of a repeating group.

With the capability to retrieve multiple code values (repeating groups), comes the need to identify which values you want to retrieve. You do this through the Crosswalk/Concept Validation Form (GTVSDAX), which you must set up to meet your institution’s reporting needs. Refer to the *GTVSDAX Handbook* for a complete description of GTVSDAX and how to properly set it up.

Indicators

Two special kinds of indicators increase the usefulness of the Object:Access views: information indicators and additional entries flags.”

Information Indicators

Several Banner Object:Access views contain indicators that are not stored in the Banner database tables. These indicators identify information that is not readily available in a

Banner field, such as whether or not a student has applied for admission, paid a deposit, or enrolled at the institution. Banner Object:Access uses PL/SQL functions to define these indicators with the Banner default definition. Information indicators are located at the beginning of each view immediately following the key attributes.

Example

In Banner Advancement the Constituent Identification view includes a **Donor Indicator** that contains a *Y* if the person/ID has a record on the Giving History by Campaign Repeating Table (APRCHIS). Similarly, some views in Banner Student and Banner Financial Aid include a **Complete Admissions Application Indicator** that contains a *Y* if the SARADAP_APST_CODE = complete.

Additional Entries Flag

Additional entries flags are used in conjunction with repeating groups. Because repeating groups limit the amount of information returned, some people might have more information than the view allows. An additional entries flag indicator identifies when a record exceeds the limit of the repeating group. The indicator contains a *Y* when a code has more values in the Banner database than fit in the attributes allotted in the view. The indicator contains an *N* when there is no overflow condition.

The criteria used to return information to the view from the database is the same criteria used to determine whether to set an additional entries flag to *Y*.

Example

Suppose that a constituent has four children in Banner Advancement. The views retrieve information about the three oldest children based on their birthdates. The **Additional Children Flag** (ADD_CHILDREN_FLAG) would have a *Y* in it because the constituent has more than three children.

For codes specified via GTVSDAX, the additional entries flag is only set to *Y* when there are multiple codes in the database for the particular selection criteria specified on GTVSDAX.

Examples

The Advancement Mail Code concept retrieves information related to four mail codes. Suppose that *BUS*, *ART*, *RES*, and *CPS* are the four values specified on GTVSDAX.

- A person who has *one* code for each of these values plus three codes with other values would not have a *Y* in the Additional Mail Codes attribute because they do not have additional codes of those specified on GTVSDAX.
- A person who has no *BUS* or *ART* codes, two *RES* codes, and one *CPS* code would have a *Y* in the Additional Mail Code attribute because there are more *RES* code values than fit in the view.

Addresses

People with inactive addresses as well as people with active addresses may need to be included for some reports. You can choose the desired address status: active, inactive, or both.

Telephone Numbers

Telephone numbers stored as *unlisted* are not returned using the Object:Access views. Asterisks (**) replace the actual numbers in any telephone number attributes that are unlisted (when `SPRTELE_UNLIST_IND = Y`),

PIDM

PIDM is a key attribute in many Banner Object:Access views. The following list highlights aspects of a PIDM that will help you better understand the concept.

- PIDM stands for Personal Identification Master.
- A PIDM is an identification number that Banner assigns to various entities, such as a person or company.
- The PIDM is an internal number that users do not see.
- The PIDM is unique to each entity; therefore two different entities, such as people or companies, cannot have the same PIDM.
- The PIDM for a particular entity is the same across all products and modules.
- Because a PIDM can be related to a person/entity and the PIDM is consistent across the Banner system, it is often the only thing that a person/entity has in common throughout the many tables in the database.
- Because a PIDM is unique and because it is often the one piece of information that is the same among tables, a PIDM is used to join tables. Joining tables is what enables you to access data from many different areas in the Banner database. Table joins are an important aspect of the Object:Access architecture.

Manual Layout

The topics in this section describe the layout of this manual and offer tips on how to use the manual to get the most from it.

View Layout

The information for each view is laid out in the same format throughout this manual. The organization of information provides easy identification of specific pieces of information within each view. The view information includes the following information:

- View name
- Reporting need the view meets
- How you might use the view
- Key attributes
- Mandatory conditions required to ensure the view returns the correct information
- Description of the information returned by the view
- List of attributes included in the view

View Name

Each Object:Access view is named based on the information included in it and its intended purpose. When you are using the views via your reporting tool, you may see an abbreviated view name. The abbreviations keep a friendly readable structure.

Prefix

A two-letter prefix is included with each name. The first letter of the prefix is always “A” so that all view names sort to the beginning of the selection list when accessed through a reporting tool. That way you can easily find the views in the list. The second letter of the prefix identifies the system or module associated with the view:

| Object:Access View Prefix | Banner System or Module |
|--------------------------------------|--------------------------------|
| AA | Advancement |
| AF | Finance |
| AG | General |
| AP | Human Resources |
| AR | Financial Aid |
| AS | Student |
| AT | Accounts Receivable |

For example, Admissions Applicant is a view in Banner Student. This view includes information that you can use to make reports related to admissions applicants and the admissions process. The abbreviated name that appears for this view when you use a reporting tool is AS_ADMISSIONS_APPLICANT.

Attribute List

Each view described in this manual includes a list of all attributes included in the view. These lists are road maps for you as you use the Object:Access views. Each list coincides with the attribute list that appears when you set up a report using a reporting tool. You can use the list to determine which attributes you want to include in your report.

The attribute lists are set up in a table format and include the following information:

- Reference number of attribute
- Attribute name in Banner Object:Access
- Attribute description
- Primary Banner form where the attribute appears
- Banner database field that is the source of the attribute or the function used to obtain the attribute

The following illustration shows a sample entry from an attribute list.

| | | | |
|-------|---------------------------------|----------|-------------------|
| S5.35 | Address Type 1 ADDRESS_TYPE1 | SPAI DEN | SPRADDR_ATYP_CODE |
|-------|---------------------------------|----------|-------------------|

The diagram shows a table with four columns. Labels with arrows point to specific parts of the table:

- Reference Number in Data Model:** Points to the value 'S5.35' in the first column.
- Attribute Description:** Points to the text 'Address Type 1' and 'ADDRESS_TYPE1' in the second column.
- Primary Banner Form where attribute appears:** Points to the text 'SPAI DEN' in the third column.
- Attribute Name:** Points to the text 'ADDRESS_TYPE1' in the second column.
- Banner Database Field (or Function Name):** Points to the text 'SPRADDR_ATYP_CODE' in the fourth column.

Reference Numbers

Each attribute has a reference number, which helps you easily identify each attribute in a view list. The reference number is in the first column of each attribute list (see preceding illustration for an example.) Reference numbers are assigned using a three-level numbering convention. S3.17 is a typical attribute reference number. Each level of numbering identifies an aspect of the attribute—the system, view, and attribute.

| Level 1 | | Level 2 | | Level 3 | |
|--|---------------------|--|---------|---|--------------|
| Primary system in which the view is used | | Number of the view within its primary system | | Number of the attribute within the view | |
| A | Advancement | 1 | View #1 | 1 | Attribute #1 |
| F | Finance | 2 | View #2 | 2 | Attribute #2 |
| G | General | X | View #X | X | Attribute #X |
| P | Human Resources | | | | |
| R | Financial Aid | | | | |
| S | Student | | | | |
| T | Accounts Receivable | | | | |

Example

Reference number S3.17 refers to the following:

| | |
|----|--|
| S | Banner Student |
| 3 | View 3 (Admissions Applicant) |
| 17 | Attribute 17 (Admission Applicant Last Name) |

How to Create a Report

How you actually create a report using the Banner Object:Access views depends largely on the reporting tool that you use to make your reports. Refer to the documentation delivered with your reporting tool for specific instructions on accessing the Banner Object:Access views and creating reports.

Though the tool you use to create reports with the Object:Access views can vary, the following steps remain fairly consistent no matter what the tool.

Tip

Be sure to supplement these steps with the instructions delivered with the reporting tool you use. ■

1. Analyze the report requirements.

Determine what information you want to include in the report. This information helps you choose which view you need to use to build the report. Refer to the attribute list with each view to help you make this determination.

2. Construct the query.

This includes all aspects of specifying the information you want to include on your report. Depending on the tool you use, you may do some or all of the following:

- Select the attributes to include in the report.
- Create additional attributes by manipulating existing attributes.
- Specify sorting conditions and other criteria.
- Specify the conditions of the query (key attributes and mandatory conditions).

3. Lay out the report.

Create the look of the report, following the directions of your reporting tool.

4. Run the query.

This is also considered *running the report* and varies by reporting tool.

2 Advancement Object:Access Views



This chapter describes the following logical views created for use in Banner Advancement.

- [“Constituent Identification” on page 2-2](#)
- [“Constituent Additional Information” on page 2-15](#)
- [“Constituent/Organization Shared” on page 2-31](#)
- [“Prospect” on page 2-46](#)
- [“Giving” on page 2-61](#)
- [“Organization” on page 2-85](#)
- [“Campaign Giving by ID” on page 2-102](#)
- [“Designation Giving by ID” on page 2-112](#)
- [“Gift Detail” on page 2-122](#)
- [“Pledge Detail” on page 2-131](#)
- [“Gift Memo Detail” on page 2-140](#)

View 1: Constituent Identification

AA_CONSTITUENT_IDENTIFICATION

If you are using FOCUS, the view name is APVCNIO.

The Constituent Identification view lets you access the most used biographical, demographic, and other related information about constituents. This view gives you one location to access the core Banner fields related to constituents including name, personal data, donor categories, addresses, primary phone number, additional phone numbers, and spouse information. These are also the core fields for prospects.



Tip

Use this view by itself or join it to the [“Constituent Additional Information”](#), [“Constituent/Organization Shared”](#), or [“Prospect”](#) views. ■

This view accesses the following main database tables.

- APBCONS Constituent Base Table
- APRCSPS Constituent Spouse Table
- SPBPERS Basic Person Base Table
- SPRADDR Address Repeating Table
- SPRIDEN Person Identification/Name Repeating Table
- SPRTELE Telephone Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) for a complete description of PIDM. ■

The key attribute of this view is

- Personal ID Master PIDM_KEY

Because the PIDM is an internal ID unique to each constituent, the view returns one row of information for each constituent.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view; however, you may find it useful to specify criteria for some or all of the following attributes. Specifying these criteria selects the population for a report and may reduce the time it takes to run the report.

- Preferred Class PREF_CLAS

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|---|
| A1.9 | Constituent First Name FIRST_NAME | APAIKEN | SPRIDEN_FIRST_NAME |
| A1.10 | Constituent Middle Name MIDDLE_NAME | APAIKEN | SPRIDEN_MI |
| A1.11 | Constituent Middle Initial MIDDLE_INITIAL | APAIKEN | SUBSTR (SPRIDEN_MI , 1 , 1) Returns first letter of middle name |
| A1.12 | Constituent Name Prefix NAME_PREFIX | APAPERS | SPBPERS_NAME_PREFIX |
| A1.13 | Constituent Name Suffix NAME_SUFFIX | APAPERS | SPBPERS_NAME_SUFFIX |
| A1.14 | Constituent Nickname NICK_NAME | APANAME | APBCONS_NICKNAME |
| A1.15 | Constituent Combined Mail Name COMBINED_MAIL_NAME | APANAME | APBCONS_CM_NAME |
| A1.16 | Constituent Birth/Maiden Name BIRTH_MAIDEN_NAME | APANAME | APBCONS_MAIDEN_LAST_NAME |
| A1.17 | Constituent Preferred Address Name PREF_ADDRESS_NAME | APANAME | APBCONS_ADDR_NAME |
| A1.18 | Constituent Preferred Address Type PREF_ADDRESS_TYPE | APANAME | APBCONS_ATYP_CODE_PREF |
| A1.19 | Birthdate BIRTH_DATE | APAPERS | SPBPERS_BIRTH_DATE |
| A1.20 | Age AGE | Function | F_CALCULATE_AGE Saturn owns this function. If the person is deceased, calculated age is the age at time of death. |

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|-------------------------------|
| A1.21 | Gender GENDER | APAPERS | SPBPERS_SEX |
| A1.22 | Marital Status Code MRTL_CODE | APAIDEN | SPBPERS_MRTL_CODE |
| A1.23 | Marital Status Description MRTL_DESC | APAIDEN | STVMRTL_DESC |
| A1.24 | Citizenship Code CITZ_CODE | APAPERS | SPBPERS_CITZ_CODE |
| A1.25 | Citizenship Description CITZ_DESC | APAPERS | STVCITZ_DESC |
| A1.26 | Legacy Code LGCY_CODE | APAPERS | SPBPERS_LGCY_CODE |
| A1.27 | Legacy Description LGCY_DESC | APAPERS | STVLGCY_DESC |
| A1.28 | Deceased Indicator DECEASED_IND | APAPERS | SPBPERS_DEAD_IND |
| A1.29 | Date of Death DECEASED_DATE | APAPERS | SPBPERS_DEAD_DATE |
| A1.30 | Confidentiality Indicator CONFIDENTIALITY_FLAG | APAPERS | SPBPERS_CONFID_IND |
| A1.31 | Preferred College PREF_COLL | APACONS | APBCONS_COLL_CODE_PREF |
| A1.32 | Preferred Class PREF_CLASS | APACONS | APBCONS_PREF_CLAS |
| A1.33 | Income Code INCM_CODE | APANAME | APBCONS_INCM_CODE |

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|---|-------------|-------------------------------|
| A1.34 | Income Description INCM_DESC | APANAME | ATVINCM_DESC |
| Get the four most preferred Donor Category Codes using the ATVDONR_RPT_SEQ_IND field which sorts Donor Category Codes by preference. | | | |
| A1.35 | Preferred Donor Category Code PREF_DONR_CODE | APACONS | ATVDONR_CODE |
| A1.36 | Preferred Donor Category Description PREF_DONR_DESC | APACONS | ATVDONR_DESC |
| A1.37 | Pref. Donor Category Alumni Indicator PREF_ALUM_IND | ATVDONR | ATVDONR_ALUM_IND |
| A1.38 | Other Donor Category Code 1 OTHER_DONR_CODE_1 | APACONS | ATVDONR_CODE |
| A1.39 | Other Donor Category 1 Description OTHER_DONR_DESC_1 | APACONS | ATVDONR_DESC |
| A1.40 | Other Donor Category Alumni Indicator 1 OTHER_ALUM_IND_1 | ATVDONR | ATVDONR_ALUM_IND |
| A1.41 | Other Donor Category Code 2 OTHER_DONR_CODE_2 | APACONS | ATVDONR_CODE |
| A1.42 | Other Donor Category 2 Description OTHER_DONR_DESC_2 | APACONS | ATVDONR_DESC |
| A1.43 | Other Donor Category Alumni Indicator 2 OTHER_ALUM_IND_2 | ATVDONR | ATVDONR_ALUM_IND |
| A1.44 | Other Donor Category Code 3 OTHER_DONR_CODE_3 | APACONS | ATVDONR_CODE |
| A1.45 | Other Donor Category 3 Description OTHER_DONR_DESC_3 | APACONS | ATVDONR_DESC |

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|---|-------------|--|
| A1.46 | Other Donor Category Alumni Indicator 3 OTHER_ALUM_IND_3 | ATVDONR | ATVDONR_ALUM_IND |
| A1.47 | Additional Donor Categories Flag ADD_DONOR_CAT_FLAG | Function | F_CHECK_FOR_MORE If there are more than four donor categories, put a Y in this field. |
| <p>Select two addresses. First get the Preferred Address information using the APACONS_ATYP_CODE_PREF indicator from APBCONS. Then select one other address and related information using the hierarchy defined for the Address Type (Advancement) concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMADDR and Internal Group = ADDRESS.</p> <p>Be sure that you refer to the correct Address Type concept, because there is more than one.</p> | | | |
| A1.48 | Preferred Address Type Code PREF_ATYP_CODE | APACONS | SPRADDR_ATYP_CODE |
| A1.49 | Preferred Address Type Description PREF_ATYP_DESC | APACONS | STVATYP_DESC |
| A1.50 | Preferred House Number PREF_HOUSE_NUMBER | APAIDEN | SPRADDR_HOUSE_NUMBER |
| A1.51 | Preferred Street Name Line 1 PREF_STREET_LINE1 | APAIDEN | SPRADDR_STREET_LINE1 |
| A1.52 | Preferred Street Name Line 2 PREF_STREET_LINE2 | APAIDEN | SPRADDR_STREET_LINE2 |
| A1.53 | Preferred Street Name Line 3 PREF_STREET_LINE3 | APAIDEN | SPRADDR_STREET_LINE3 |
| A1.54 | Preferred Street Name Line 4 PREF_STREET_LINE4 | APAIDEN | SPRADDR_STREET_LINE4 |

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|---|-------------|-------------------------------|
| A1.55 | Preferred City PREF_CITY | APAIDEN | SPRADDR_CITY |
| A1.56 | Preferred State PREF_STAT_CODE | APAIDEN | SPRADDR_STAT_CODE |
| A1.57 | Preferred Zip Code PREF_ZIP | APAIDEN | SPRADDR_ZIP |
| A1.58 | Preferred County Code PREF_CNTY_CODE | APAIDEN | SPRADDR_CNTY_CODE |
| A1.59 | Preferred County Description PREF_CNTY_DESC | APAIDEN | STVCNTY_DESC |
| A1.60 | Preferred Nation Code PREF_NATN_CODE | APAIDEN | SPRADDR_NATN_CODE |
| A1.61 | Preferred Nation Description PREF_NATN_DESC | APAIDEN | STVNATN_NATION |
| <p>Select the Geographic Region and related information using the hierarchy defined for the Geographic Region concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMGEOD</i> and Internal Group = <i>GEOR REGION</i>.</p> | | | |
| A1.62 | Preferred Geographic Region Code PREF_GEOR_CODE | SOAIGEO | SOVGEOR_GEOR_CODE |
| A1.63 | Preferred Geographic Region Description PREF_GEOR_DESC | SOAIGEO | STVGEOR_DESC |
| A1.64 | Preferred Delivery Point PREF_DELIVERY_POINT | APAIDEN | SPRADDR_DELIVERY_POINT |
| A1.65 | Preferred Correction Digit PREF_CORRECTION_DIGIT | APAIDEN | SPRADDR_CORRECTION_DIGIT |

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|---|--|-------------|--|
| A1.66 | Preferred Carrier Route PREF_CARRIER_ROUTE | APAIDEN | SPRADDR_CARRIER_ROUTE |
| A1.67 | Preferred Address Start Date PREF_ADDR_START_DATE | APAIDEN | SPRADDR_FROM_DATE |
| A1.68 | Preferred Address End Date PREF_ADDR_END_DATE | APAIDEN | SPRADDR_TO_DATE |
| A1.69 | Preferred Address Status Indicator PREF_ADDR_STATUS_IND | APAIDEN | SPRADDR_STATUS_IND |
| If the phone number is unlisted (SPRTELE_UNLIST_IND = Y), asterisks (**) are returned in place of the actual phone numbers. | | | |
| A1.70 | Preferred Phone Country Code PREF_CTRY_CODE_PHONE | APAIDEN | SPRTELE_CTRY_CODE_PHONE |
| A1.71 | Preferred Phone Number PREF_PHONE_NUMBER | APAIDEN | SPRTELE_PHONE_NUMBER Need to get SEQNO, ATYP_CODE, and PRIMARY_IND to get primary phone number. |
| A1.72 | Preferred Phone Area Code PREF_PHONE_AREA_CODE | APAIDEN | SPRTELE_PHONE_AREA |
| A1.73 | Preferred Phone Extension PREF_PHONE_EXT | APAIDEN | SPRTELE_PHONE_EXT |
| A1.74 | Other Address Type Code OTHER_ATYP_CODE | APAIDEN | SPRADDR_ATYP_CODE |
| A1.75 | Other Address Type Description OTHER_ATYP_DESC | APAIDEN | STVATYP_DESC |
| A1.76 | Other House Number OTHER_HOUSE_NUMBER | APAIDEN | SPRADDR_HOUSE_NUMBER |
| A1.77 | Other Street Name Line 1 OTHER_STREET_LINE1 | APAIDEN | SPRADDR_STREET_LINE1 |

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|---|-------------|-------------------------------|
| A1.78 | Other Street Name Line 2 OTHER_STREET_LINE2 | APAIDEN | SPRADDR_STREET_LINE2 |
| A1.79 | Other Street Name Line 3 OTHER_STREET_LINE3 | APAIDEN | SPRADDR_STREET_LINE3 |
| A1.80 | Other Street Name Line 4 OTHER_STREET_LINE4 | APAIDEN | SPRADDR_STREET_LINE4 |
| A1.81 | Other City OTHER_CITY | APAIDEN | SPRADDR_CITY |
| A1.82 | Other State OTHER_STAT_CODE | APAIDEN | SPRADDR_STAT_CODE |
| A1.83 | Other Zip Code OTHER_ZIP | APAIDEN | SPRADDR_ZIP |
| A1.84 | Other County Code OTHER_CNTY_CODE | APAIDEN | SPRADDR_CNTY_CODE |
| A1.85 | Other County Description OTHER_CNTY_DESC | APAIDEN | STVCNTY_DESC |
| A1.86 | Other Nation Code OTHER_NATN_CODE | APAIDEN | SPRADDR_NATN_CODE |
| A1.87 | Other Nation Description OTHER_NATN_DESC | APAIDEN | STVNATN_NATION |
| <p>Select the Geographic Region and related information using the hierarchy defined for the Geographic Region concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMGEOD</i> and Internal Group = <i>GEOR REGION</i>.</p> | | | |
| A1.88 | Other Geographic Region Code OTHER_GEOR_CODE | SOAIGEO | SOVGEOR_GEOR_CODE |

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|---|---|-------------|--|
| A1.89 | Other Geographic Region Description OTHER_GEOR_DESC | SOAIGEO | STVGEOR_DESC |
| A1.90 | Other Delivery Point OTHER_DELIVERY_POINT | APAIDEN | SPRADDR_DELIVERY_POINT |
| A1.91 | Other Correction Digit OTHER_CORRECTION_DIGIT | APAIDEN | SPRADDR_CORRECTION_DIGIT |
| A1.92 | Other Carrier Route OTHER_CARRIER_ROUTE | APAIDEN | SPRADDR_CARRIER_ROUTE |
| A1.93 | Other Address Start Date OTHER_ADDR_START_DATE | APAIDEN | SPRADDR_FROM_DATE |
| A1.94 | Other Address End Date OTHER_ADDR_END_DATE | APAIDEN | SPRADDR_TO_DATE |
| A1.95 | Other Address Status Indicator OTHER_ADDR_STATUS_IND | APAIDEN | SPRADDR_STATUS_IND |
| If the phone number is unlisted (SPRTELE_UNLIST_IND = Y), asterisks (**) are returned in place of the actual phone numbers. | | | |
| A1.96 | Other Phone Country Code OTHER_CTRY_CODE_PHONE | APAIDEN | SPRTELE_CTRY_CODE_PHONE |
| A1.97 | Other Phone Number OTHER_PHONE_NUMBER | APAIDEN | SPRTELE_PHONE_NUMBER Need to get SEQNO, ATYP_CODE, and PRIMARY_IND to get primary phone number. |
| A1.98 | Other Phone Area Code OTHER_PHONE_AREA_CODE | APAIDEN | SPRTELE_PHONE_AREA |
| A1.99 | Other Phone Extension OTHER_PHONE_EXT | APAIDEN | SPRTELE_PHONE_EXT |

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|-------------------------------|
| | <p>Select three additional Phone Numbers using the hierarchy defined for the Telephone Code (Additional) concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMPHONE and Internal Group = TELEPHONE.</p> | | |
| A1.100 | Additional Phone Code 1 TELE_CODE_1 | APAIDEN | SPRTELE_TELE_CODE |
| A1.101 | Additional Phone 1 Description TELE_DESC_1 | APAIDEN | STVTELE_DESC |
| A1.102 | Additional Phone Number 1 PHONE_NUMBER_1 | APAIDEN | SPRTELE_PHONE_NUMBER |
| A1.103 | Additional Phone Area Code 1 PHONE_AREA_CODE_1 | APAIDEN | SPRTELE_PHONE_AREA |
| A1.104 | Additional Phone Extension 1 PHONE_EXT_1 | APAIDEN | SPRTELE_PHONE_EXT |
| A1.105 | Additional Phone Code 2 TELE_CODE_2 | APAIDEN | SPRTELE_TELE_CODE |
| A1.106 | Additional Phone 2 Description TELE_DESC_2 | APAIDEN | STVTELE_DESC |
| A1.107 | Additional Phone Number 2 PHONE_NUMBER_2 | APAIDEN | SPRTELE_PHONE_NUMBER |
| A1.108 | Additional Phone Area Code 2 PHONE_AREA_CODE_2 | APAIDEN | SPRTELE_PHONE_AREA |
| A1.109 | Additional Phone Extension 2 PHONE_EXT_2 | APAIDEN | SPRTELE_PHONE_EXT |
| A1.110 | Additional Phone Code 3 TELE_CODE_3 | APAIDEN | SPRTELE_TELE_CODE |

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|--|-------------|--|
| A1.111 | Additional Phone 3 Description TELE_DESC_3 | APAIDEN | STVTELE_DESC |
| A1.112 | Additional Phone Number 3 PHONE_NUMBER_3 | APAIDEN | SPRTELE_PHONE_NUMBER |
| A1.113 | Additional Phone Area Code 3 PHONE_AREA_CODE_3 | APAIDEN | SPRTELE_PHONE_AREA |
| A1.114 | Additional Phone Extension 3 PHONE_EXT_3 | APAIDEN | SPRTELE_PHONE_EXT |
| A1.115 | More Phone Numbers Flag ADD_PHONE_FLAG | Function | F_CHECK_FOR_MORE If there are more than three additional phone numbers, put a <i>Y</i> in this field. |
| <p>Select the spouse using the most recent From Date.</p> <p>The table source of some spouse attributes depends on if the spouse has a <i>PIDM</i>. Multi-source attributes are denoted using a slash (/). The table name to the left of the slash indicates the source if the spouse <i>does not have a PIDM</i> or it may indicate a <i>Null</i> value. The table name to the right of the slash indicates the source if the spouse <i>has a PIDM</i>. In most cases, the field name is the same except for the table prefix.</p> | | | |
| A1.116 | Spouse Personal ID Master SPOUSE_PIDM | APACONS | null/APRCSPS_SPS_PIDM |
| A1.117 | Spouse Last Name SPOUSE_LAST_NAME | APACONS | APRCSPS/SPRIDEN_LAST_NAME |
| A1.118 | Spouse First Name SPOUSE_FIRST_NAME | APACONS | APRCSPS/ SPRIDEN_FIRST_NAME |
| A1.119 | Spouse Birth/Maiden Name SPOUSE_BIRTH_MAIDEN_NAME | APACONS | APRCSPS_MAIDEN_NAME/ APBCONS_MAIDEN_LAST_NAME |
| A1.120 | Spouse Name Prefix SPOUSE_NAME_PREFIX | APACONS | APRCSPS/ SPBPERS_NAME_PREFIX |

Table 1: Constituent Identification View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|---|
| A1.121 | Spouse Name Suffix SPOUSE_NAME_SUFFIX | APACONS | APRCSPS/ SPBPERS_NAME_SUFFIX |
| A1.122 | Spouse Status SPOUSE_IND | APACONS | APRCSPS_MARS_IND |
| A1.123 | Spouse Deceased Indicator SPOUSE_DECEASED_IND | APACONS | APRCSPS/SPBPERS_DEAD_IND |
| A1.124 | Spouse Date of Death SPOUSE_DECEASED_DATE | APACONS | APRCSPS/SPBPERS_DEAD_DATE |
| A1.125 | Spouse Preferred College SPOUSE_PREF_COLL | APACONS | Null/ APBCONS_COLL_CODE_PREF |
| A1.126 | Spouse Preferred Class Year SPOUSE_CLASS_YEAR | APACONS | Null/APBCONS_PREF_CLAS |
| A1.127 | Spouse Lost Alumnus Indicator SPOUSE_LOST_ALUMNUS_IND | Function | null/F_LOST_AL_IND If spouse has no active addresses, (the TO_DATE passed on all addresses, or all addresses on SPRADDR have an I (Inactive) status), put a Y in this field. |
| A1.128 | Spouse Primary Donor Category Code SPOUSE_PREF_DONR_CODE | APACONS | null/ATVDONR_CODE |
| A1.129 | Spouse Primary Donor Category Desc. SPOUSE_PREF_DONR_DESC | APACONS | null/ATVDONR_DESC |
| A1.130 | Spouse ID SPOUSE_ID | APACONS | null/SPRIDEN_ID |
| A1.131 | Spouse Surname Prefix SPOUSE_SURNAME_PREFIX | APACONS | APRCSPS/ SPBPERS_NAME_PREFIX |

View 2: Constituent Additional Information

AA_CONSTITUENT_ADDITIONAL_INFO

If you are using FOCUS, the view name is APVCNA0.

The Constituent Additional Information view contains the constituent-related information that is not shared with organizations or included in the Constituent Identification view. The Constituent Additional Information view includes the degree, job, and children information about constituents, the PIDM so that you can join it to other views.



Tip

Join this view to the [“Constituent Identification”](#) view to include name and address information. ■

This view accesses the following main database tables.

- AOBORGN Organization Base Table
- APBCONS Constituent Base Table
- APRADEG Academic Degree Repeating Table
- APRAMAJ Academic Major Repeating Table
- APRCHLD Children Repeating Table
- APREHIS Employment History Repeating Table
- SGBSTDN Student Base Table
- SGRCLSR Student Classification Table
- SORHSCH Person Related High School Base Table
- SPRIDEN Person Identification/Name Repeating Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) for a complete description of PIDM. ■

The key attribute of this view is

- Personal ID Master PIDM_KEY

Because the PIDM is an internal ID unique to each constituent, the view returns one row of information for each constituent.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view. In most cases, you join this view to the Constituent or the Constituent/Organization Shared views. Refer to the recommended conditions for those views.

Attributes

The following list specifies the attributes included in the Constituent Additional Information view. The list also indicates the primary Banner form and the database field or function that is the source for each attribute.

Table 2: Constituent Additional Information View Attributes

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|---|--|-------------|--|
| A2.1 | Personal ID Master Key PIDM_KEY | APAIIDEN | APBCONS_PIDM |
| Select three Institution Degrees using the most recent Degree Dates and validating the institution against AUBINST_SBGI_CODE on the form AGACTRL. | | | |
| A2.2 | Institution Degree Code 1 INST_DEGR_DEGC_CODE_1 | APAADEG | APRADEG_DEGC_CODE |
| A2.3 | Institution Degree 1 Description INST_DEGR_DEGC_DESC_1 | APAADEG | STVDEGC_DESC |
| A2.4 | College of Institution Degree 1 INST_DEGR_COLL_CODE_1 | APAADEG | APRADEG_COLL_CODE |
| A2.5 | College of Institution Degree 1 Desc. INST_DEGR_COLL_DESC_1 | APAADEG | STV_COLL_DESC |
| A2.6 | Institution Degree Date 1 INST_DEGR_DATE_1 | APAADEG | APRADEG_DATE |
| A2.7 | Institution Degree Year 1 INST_DEGR_YEAR_1 | APAADEG | Calculate as: to_char (APRADEG_DATE, 'YYYY') |
| A2.8 | Institution Degree Level Code 1 INST_DEGR_DLEV_CODE_1 | APAADEG | STVDEGC_DLEV_CODE |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|--|
| A2.9 | Institution Degree Level 1 Description INST_DEGR_DLEV_DESC_1 | APAADEG | STVDLEV_DESC |
| A2.10 | Major 1 of Institution Degree 1 INST_DEGR_MAJR1_CODE_1 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.11 | Major 1 of Institution Degree 1 Desc. INST_DEGR_MAJR1_DESC_1 | APAADEG | STVMAJR_DESC |
| A2.12 | Major 2 of Institution Degree 1 INST_DEGR_MAJR2_CODE_1 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.13 | Major 2 of Institution Degree 2 Desc. INST_DEGR_MAJR2_DESC_1 | APAADEG | STVMAJR_DESC |
| A2.14 | Honor Code of Institution Degree 1 INST_DEGR_HONR_CODE_1 | APAADEG | APRADEG_HONR_CODE |
| A2.15 | Honor Code of Institution Degree 1 Desc. INST_DEGR_HONR_DESC_1 | APAADEG | STVHONR_DESC |
| A2.16 | Institution Degree Code 2 INST_DEGR_DEGC_CODE_2 | APAADEG | APRADEG_DEGC_CODE |
| A2.17 | Institution Degree 2 Description INST_DEGR_DEGC_DESC_2 | APAADEG | STVDEGC_DESC |
| A2.18 | College of Institution Degree 2 INST_DEGR_COLL_CODE_2 | APAADEG | APRADEG_COLL_CODE |
| A2.19 | College of Institution Degree 2 Desc. INST_DEGR_COLL_DESC_2 | APAADEG | STV_COLL_DESC |
| A2.20 | Institution Degree Date 2 INST_DEGR_DATE_2 | APAADEG | APRADEG_DATE |
| A2.21 | Institution Degree Year 2 INST_DEGR_YEAR_2 | APAADEG | Calculate as: to_char (APRADEG_DATE , 'YYYY') |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|-------------------------------|
| A2.22 | Institution Degree Level Code 2 INST_DEGR_DLEV_CODE_2 | APAADEG | STVDEGC_dLEV_CODE |
| A2.23 | Institution Degree Level 2 Description INST_DEGR_DLEV_DESC_2 | APAADEG | STVDLEV_DESC |
| A2.24 | Major 1 of Institution Degree 2 INST_DEGR_MAJR1_CODE_2 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.25 | Major 1 of Institution Degree 2 Desc. INST_DEGR_MAJR1_DESC_2 | APAADEG | STVMAJR_DESC |
| A2.26 | Major 2 of Institution Degree 2 INST_DEGR_MAJR2_CODE_2 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.27 | Major 2 of Institution Degree 2 Desc. INST_DEGR_MAJR2_DESC_2 | APAADEG | STVMAJR_DESC |
| A2.28 | Honor Code of Institution Degree 2 INST_DEGR_HONR_CODE_2 | APAADEG | APRADEG_HONR_CODE |
| A2.29 | Honor Code of Institution Degree 2 Desc. INST_DEGR_HONR_DESC_2 | APAADEG | STVHONR_DESC |
| A2.30 | Institution Degree Code 3 INST_DEGR_DEGC_CODE_3 | APAADEG | APRADEG_DEGC_CODE |
| A2.31 | Institution Degree 3 Description INST_DEGR_DEGC_DESC_3 | APAADEG | STVDEGC_DESC |
| A2.32 | College of Institution Degree 3 INST_DEGR_COLL_CODE_3 | APAADEG | APRADEG_COLL_CODE |
| A2.33 | College of Institution Degree 3 Desc. INST_DEGR_COLL_DESC_3 | APAADEG | STV_COLL_DESC |
| A2.34 | Institution Degree Date 3 INST_DEGR_DATE_3 | APAADEG | APRADEG_DATE |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|--|
| A2.35 | Institution Degree Year 3 INST_DEGR_YEAR_3 | APAADEG | Calculate as: to_char(APRADEG_DATE, 'YYYY') |
| A2.36 | Institution Degree Level Code 3 INST_DEGR_DLEV_CODE_3 | APAADEG | STVDEGC_DLEV_CODE |
| A2.37 | Institution Degree Level 3 Description INST_DEGR_DLEV_DESC_3 | APAADEG | STVDLEV_DESC |
| A2.38 | Major 1 of Institution Degree 3 INST_DEGR_MAJR1_CODE_3 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.39 | Major 1 of Institution Degree 3 Desc. INST_DEGR_MAJR1_DESC_3 | APAADEG | STVMAJR_DESC |
| A2.40 | Major 2 of Institution Degree 3 INST_DEGR_MAJR2_CODE_3 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.41 | Major 2 of Institution Degree 3 Desc. INST_DEGR_MAJR2_DESC_3 | APAADEG | STVMAJR_DESC |
| A2.42 | Honor Code of Institution Degree 3 INST_DEGR_HONR_CODE_3 | APAADEG | APRADEG_HONR_CODE |
| A2.43 | Honor Code of Institution Degree 3 Desc. INST_DEGR_HONR_DESC_3 | APAADEG | STVHONR_DESC |
| A2.44 | Additional Institution Degrees Flag ADD_INST_DEGR_FLAG | Function | F_CHECK_FOR_MORE If there are more than three institution degrees, put a Y in this field. |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|--|
| | Select three Degrees received from Other Institutions using the most recent Degree Dates and validating that institution against AUBINST_SBGI_CODE on the form AGACTRL. | | |
| A2.45 | Other Degree Code 1 OTHER_DEGR_DEGC_CODE_1 | APAADEG | APRADEG_DEGC_CODE |
| A2.46 | Other Degree 1 Description OTHER_DEGR_DEGC_DESC_1 | APAADEG | STVDEGC_DESC |
| A2.47 | College of Other Degree 1 OTHER_DEGR_COLL_CODE_1 | APAADEG | APRADEG_COLL_CODE |
| A2.48 | College of Other Degree 1 Desc. OTHER_DEGR_COLL_DESC_1 | APAADEG | STV_COLL_DESC |
| A2.49 | Other Degree Date 1 OTHER_DEGR_DATE_1 | APAADEG | APRADEG_DATE |
| A2.50 | Other Degree Year 1 OTHER_DEGR_YEAR_1 | APAADEG | Calculate as: to_char (APRADEG_DATE, 'YYYY') |
| A2.51 | Other Degree Level Code 1 OTHER_DEGR_DLEV_CODE_1 | APAADEG | STVDEGC_dLEV_CODE |
| A2.52 | Other Degree Level 1 Description OTHER_DEGR_DLEV_DESC_1 | APAADEG | STVDLEV_DESC |
| A2.53 | Institution Code of Other Degree 1 OTHER_DEGR_SBGI_CODE_1 | APAADEG | APRADEG_SBGI_CODE |
| A2.54 | Institution Code Desc. of Other Degree 1 OTHER_DEGR_SBGI_DESC_1 | APAADEG | STVSBGI_DESC |
| A2.55 | Major 1 of Other Degree 1 OTHER_DEGR_MAJR1_CODE_1 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.56 | Major 1 of Other Degree 1 Desc. OTHER_DEGR_MAJR1_DESC_1 | APAADEG | STVMAJR_DESC |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|--|
| A2.57 | Major 2 of Other Degree 1 OTHER_DEGR_MAJR2_CODE_1 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.58 | Major 2 of Other Degree 1 Desc. OTHER_DEGR_MAJR2_DESC_1 | APAADEG | STVMAJR_DESC |
| A2.59 | Honor Code of Other Degree 1 OTHER_DEGR_HONR_CODE_1 | APAADEG | APRADEG_HONR_CODE |
| A2.60 | Honor Code of Other Degree 1 Desc. OTHER_DEGR_HONR_DESC_1 | APAADEG | STVHONR_DESC |
| A2.61 | Other Degree Code 2 OTHER_DEGR_DEGC_CODE_2 | APAADEG | APRADEG_DEGC_CODE |
| A2.62 | Other Degree 2 Description OTHER_DEGR_DEGC_DESC_2 | APAADEG | STVDEGC_DESC |
| A2.63 | College of Other Degree 2 OTHER_DEGR_COLL_CODE_2 | APAADEG | APRADEG_COLL_CODE |
| A2.64 | College of Other Degree 2 Desc. OTHER_DEGR_COLL_DESC_2 | APAADEG | STV_COLL_DESC |
| A2.65 | Other Degree Date 2 OTHER_DEGR_DATE_2 | APAADEG | APRADEG_DATE |
| A2.66 | Other Degree Year 2 OTHER_DEGR_YEAR_2 | APAADEG | Calculate as: to_char (APRADEG_DATE, 'YYYY') |
| A2.67 | Other Degree Level Code 2 OTHER_DEGR_DLEV_CODE_2 | APAADEG | STVDEGC_DLEV_CODE |
| A2.68 | Other Degree Level 2 Description OTHER_DEGR_DLEV_DESC_2 | APAADEG | STVDLEV_DESC |
| A2.69 | Institution Code of Other Degree 2 OTHER_DEGR_SBGI_CODE_2 | APAADEG | APRADEG_SBGI_CODE |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|--|
| A2.70 | Institution Code Desc. of Other Degree 2 OTHER_DEGR_SBGI_DESC_2 | APAADEG | STVSBGI_DESC |
| A2.71 | Major 1 of Other Degree 2 OTHER_DEGR_MAJR1_CODE_2 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.72 | Major 1 of Other Degree 2 Desc. OTHER_DEGR_MAJR1_DESC_2 | APAADEG | STVMAJR_DESC |
| A2.73 | Major 2 of Other Degree 2 OTHER_DEGR_MAJR2_CODE_2 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.74 | Major 2 of Other Degree 2 Desc. OTHER_DEGR_MAJR2_DESC_2 | APAADEG | STVMAJR_DESC |
| A2.75 | Honor Code of Other Degree 2 OTHER_DEGR_HONR_CODE_2 | APAADEG | APRADEG_HONR_CODE |
| A2.76 | Honor Code of Other Degree 2 Desc. OTHER_DEGR_HONR_DESC_2 | APAADEG | STVHONR_DESC |
| A2.77 | Other Degree Code 3 OTHER_DEGR_DEGC_CODE_3 | APAADEG | APRADEG_DEGC_CODE |
| A2.78 | Other Degree 3 Description OTHER_DEGR_DEGC_DESC_3 | APAADEG | STVDEGC_DESC |
| A2.79 | College of Other Degree 3 OTHER_DEGR_COLL_CODE_3 | APAADEG | APRADEG_COLL_CODE |
| A2.80 | College of Other Degree 3 Desc. OTHER_DEGR_COLL_DESC_3 | APAADEG | STV_COLL_DESC |
| A2.81 | Other Degree Date 3 OTHER_DEGR_DATE_3 | APAADEG | APRADEG_DATE |
| A2.82 | Other Degree Year 3 OTHER_DEGR_YEAR_3 | APAADEG | Calculate as: to_char (APRADEG_DATE, 'YYYY') |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|--|
| A2.83 | Other Degree Level Code 3 OTHER_DEGR_DLEV_CODE_3 | APAADEG | STVDEGC_DLEV_CODE |
| A2.84 | Other Degree Level 3 Description OTHER_DEGR_DLEV_DESC_3 | APAADEG | STVDLEV_DESC |
| A2.85 | Institution Code of Other Degree 3 OTHER_DEGR_SBGI_CODE_3 | APAADEG | APRADEG_SBGI_CODE |
| A2.86 | Institution Code Desc. of Other Degree 3 OTHER_DEGR_SBGI_DESC_3 | APAADEG | STVSBGI_DESC |
| A2.87 | Major 1 of Other Degree 3 OTHER_DEGR_MAJR1_CODE_3 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.88 | Major 1 of Other Degree 3 Desc. OTHER_DEGR_MAJR1_DESC_3 | APAADEG | STVMAJR_DESC |
| A2.89 | Major 2 of Other Degree 3 OTHER_DEGR_MAJR2_CODE_3 | APAADEG | APRAMAJ_MAJR_CODE |
| A2.90 | Major 2 of Other Degree 3 Desc. OTHER_DEGR_MAJR2_DESC_3 | APAADEG | STVMAJR_DESC |
| A2.91 | Honor Code of Other Degree 3 OTHER_DEGR_HONR_CODE_3 | APAADEG | APRADEG_HONR_CODE |
| A2.92 | Honor Code of Other Degree 3 Desc. OTHER_DEGR_HONR_DESC_3 | APAADEG | STVHONR_DESC |
| A2.93 | Additional Other Institution Degrees Flag ADD_OTHER_DEGR_FLAG | Function | F_CHECK_FOR_MORE If there are more than three other institution degrees, put a Y in this field. |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|---|
| | <p>Company information is based on the current employer from APREHIS. If there is more than one current employer, the view determines the employer with the most recent “from” date and sets the indicator to denote multiple current employers.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMJOB and Internal Group = JOB INFO.</p> <p>Note: The table source of some company attributes depends on whether the company has a PIDM. Multi-source attributes are denoted using a slash (/). The table name to the left of the slash indicates the source if the company <i>does not have a PIDM</i> or it may indicate a <i>Null</i> value. The table name to the right of the slash indicates the source if the company <i>has a PIDM</i>. In most cases the attribute name is the same except for the table prefix.</p> | | |
| A2.94 | Company Name COMPANY_NAME | APAEHIS | APREHIS_EMPR_NAME/ SPRIDEN_LAST_NAME |
| A2.95 | Company ID COMPANY_ID | APAEHIS | null/SPRIDEN_ID |
| A2.96 | Company Personal ID Master COMPANY_PIDM | APAEHIS | null/APREHIS_EMPR_PIDM |
| A2.97 | Employee Position EMPLOYEE_POSITION | APAEHIS | APREHIS_EMPL_POSITION |
| A2.98 | Employee Status Code EMPS_CODE | APAEHIS | APREHIS_EMPS_CODE |
| A2.99 | Employee Status Description EMPS_DESC | APAEHIS | ATVEMPS_DESC |
| A2.100 | Date Started Job JOB_START_DATE | APAEHIS | APREHIS_FROM_DATE |
| A2.101 | Date Ended Job JOB_END_DATE | APAEHIS | APREHIS_TO_DATE |
| A2.102 | Job Category Code JOBC_CODE | APAEHIS | APREHIS_JOBC_CODE |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|------------------------|--|
| A2.103 | Job Category Description JOB_CDESC | APAEHIS | ATVJOB_CDESC |
| A2.104 | Job Category Active Indicator EMPLOYMENT_ACTIVE_IND | APAEHIS | ATVEMPS_ACTIVE_IND |
| A2.105 | Occupation Code DOTT_CODE | APAEHIS | APBCONS_DOTT_CODE |
| A2.106 | Occupation Description DOTT_DESC | APAEHIS | ATVDOTT_DESC |
| A2.107 | Industry Code SICC_CODE | APAEHIS | APREHIS/ AOBORG_N_SICC_CODE |
| A2.108 | Industry Description SICC_DESC | APAEHIS | ATVSICC_DESC |
| A2.109 | Matching Gift Company Flag COMPANY_MATCH_GIFT_FLAG | APAEHIS | null/'Y' or 'N' |
| A2.110 | Matching Gift Percentage MATCH_GIFT_PERCENTAGE | Function (AOAORG_N) | F_JOB_INFO null/AOBORG_N_MATCH_PCT |
| A2.111 | Additional Employer Flag ADD_EMPLOYMENT_FLAG | Function | F_JOB_INFO If there is more than one employer, put a Y in this field. |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|---|
| | Select information about three children by the three earliest Birth Dates, that is, the three oldest children. | | |
| | Note: The table source of some child attributes depends on if the child has a PIDM. Multi-source attributes are denoted using a slash (/). The table name to the left of the slash indicates the source if the child <i>does not have a PIDM</i> or it may indicate a <i>Null</i> value. The table name to the right of the slash indicates the source if the child <i>has a PIDM</i> . In most cases, the attribute name is the same except for the table prefix. | | |
| A2.112 | Child Personal ID Master 1 CHILD_PIDM_1 | APACHLD | null/APRCHLD_chld_PIDM |
| A2.113 | Child Last Name 1 CHILD_LAST_NAME_1 | APACHLD | APRCHLD/ SPRIDEN_LAST_NAME |
| A2.114 | Child First Name 1 CHILD_FIRST_NAME_1 | APACHLD | APRCHLD/ SPRIDEN_FIRST_NAME |
| A2.115 | Child Middle Name 1 CHILD_MIDDLE_NAME_1 | APACHLD | APRCHLD/SPRIDEN_MI |
| A2.116 | Child ID 1 CHILD_ID_1 | APACHLD | APRCHLD/SPRIDEN_ID |
| A2.117 | Child Birthdate 1 CHILD_BIRTH_DATE_1 | APACHLD | APRCHLD/ SPBPERS_BIRTH_DATE |
| A2.118 | Child Age 1 CHILD_AGE_1 | Function | F_CALCULATE_AGE Note: Saturn owns this function. If the person is deceased, calculated age is the age at time of death. |
| | If the child is a student or an alumnus of the institution, you can obtain the following attributes. Otherwise, a “Null” value is returned. | | |
| A2.119 | Child High School CEEB Code 1 CHILD_HS_SBGI_CODE_1 | SOAHSCH | null/SORHSCH_SBGI_CODE |
| A2.120 | Child High School Name 1 CHILD_HS_SBGI_DESC_1 | SOAHSCH | null/STVSBGI_DESC |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-----------------------|--|
| A2.121 | Child College Code 1 CHILD_COLL_CODE_1 | SGASTDN | null/ SGBSTDN_COLL_CODE_1 |
| A2.122 | Child College Description 1 CHILD_COLL_DESC_1 | SGASTDN | null/STV_COLL_DESC |
| A2.123 | Child Class Code 1 CHILD_CLAS_CODE_1 | SGACLSR | null/SGRCLSR_CLAS_CODE |
| A2.124 | Child Class Description 1 CHILD_CLAS_DESC_1 | SGACLSR | null/STVCLAS_DESC |
| A2.125 | Child Alumni Indicator 1 CHILD_ALUMNUS_IND_1 | APACONS | null/ATVDONR_ALUM_IND |
| A2.126 | Child Donor Indicator 1 CHILD_DONOR_IND_1 | Function (APRCHIS) | F_DONOR_IND null/If there is a record in APRCHIS, put a Y in this field. |
| A2.127 | Child Personal ID Master 2 CHILD_PIDM_2 | APACHLD | null/APRCHLD_chld_PIDM |
| A2.128 | Child Last Name 2 CHILD_LAST_NAME_2 | APACHLD | APRCHLD/ SPRIDEN_LAST_NAME |
| A2.129 | Child First Name 2 CHILD_FIRST_NAME_2 | APACHLD | APRCHLD/ SPRIDEN_FIRST_NAME |
| A2.130 | Child Middle Name 2 CHILD_MIDDLE_NAME_2 | APACHLD | APRCHLD/SPRIDEN_MI |
| A2.131 | Child ID 2 CHILD_ID_2 | APACHLD | null/SPRIDEN_ID |
| A2.132 | Child Birthdate 2 CHILD_BIRTH_DATE_2 | APACHLD | APRCHLD/ SPBPERS_BIRTH_DATE |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|---|-----------------------|---|
| A2.133 | Child Age 2 CHILD_AGE_2 | Function | F_CALCULATE_AGE Note: Saturn owns this function. If the person is deceased, calculated age is the age at time of death. |
| If the child is a student or an alumnus of the institution, you can obtain the following attributes. Otherwise, a <i>Null</i> value is returned. | | | |
| A2.134 | Child High School CEEB Code 2 CHILD_HS_SBGI_CODE_2 | SOAHSCH | null/SORHSCH_SBGI_CODE |
| A2.135 | Child High School Name 2 CHILD_HS_SBGI_DESC_2 | SOAHSCH | null/STVSBGI_DESC |
| A2.136 | Child College Code 2 CHILD_COLL_CODE_2 | SGASTDN | null/ SGBSTDN_COLL_CODE_1 |
| A2.137 | Child College Description 2 CHILD_COLL_DESC_2 | SGASTDN | null/STV_COLL_DESC |
| A2.138 | Child Class Code 2 CHILD_CLAS_CODE_2 | SGACLSR | null/SGRCLSR_CLAS_CODE |
| A2.139 | Child Class Description 2 CHILD_CLAS_DESC_2 | SGACLSR | null/STVCLAS_DESC |
| A2.140 | Child Alumni Indicator 2 CHILD_ALUMNUS_IND_2 | APACONS | null/ATVDONR_ALUM_IND |
| A2.141 | Child Donor Indicator 2 CHILD_DONOR_IND_2 | Function (APACHIS) | F_DONOR_IND null/If there is a record in APRCHIS, put a Y in this field. |
| A2.142 | Child Personal ID Master 3 CHILD_PIDM_3 | APACHLD | null/APRCHLD_chld_PIDM |
| A2.143 | Child Last Name 3 CHILD_LAST_NAME_3 | APACHLD | APRCHLD/ SPRIDEN_LAST_NAME |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|--|-------------|---|
| A2.144 | Child First Name 3 CHILD_FIRST_NAME_3 | APACHLD | APRCHLD/ SPRIDEN_FIRST_NAME |
| A2.145 | Child Middle Name 3 CHILD_MIDDLE_NAME_3 | APACHLD | APRCHLD/SPRIDEN_MI |
| A2.146 | Child ID 3 CHILD_ID_3 | APACHLD | null/SPRIDEN_ID |
| A2.147 | Child Birthdate 3 CHILD_BIRTH_DATE_3 | APACHLD | APRCHLD/ SPBPERS_BIRTH_DATE |
| A2.148 | Child Age 3 CHILD_AGE_3 | Function | F_CALCULATE_AGE Note: Saturn owns this function. If the person is deceased, calculated age is the age at time of death. |
| If the child is a student or an alumnus of the institution, you can obtain the following attributes. Otherwise, a <i>Null</i> value is returned. | | | |
| A2.149 | Child High School CEEB Code 3 CHILD_HS_SBG_CODE_3 | SOAHSCH | null/SORHSCH_SBG_CODE |
| A2.150 | Child High School Name 3 CHILD_HS_SBG_DESC_3 | SOAHSCH | null/STVSBG_DESC |
| A2.151 | Child College Code 3 CHILD_COLL_CODE_3 | SGASTDN | null/ SGBSTDN_COLL_CODE_1 |
| A2.152 | Child College Description 3 CHILD_COLL_DESC_3 | SGASTDN | null/STV_COLL_DESC |
| A2.153 | Child Class Code 3 CHILD_CLAS_CODE_3 | SGACLSR | null/SGRCLSR_CLAS_CODE |
| A2.154 | Child Class Description 3 CHILD_CLAS_DESC_3 | SGACLSR | null/STVCLAS_DESC |
| A2.155 | Child Alumni Indicator 3 CHILD_ALUMNUS_IND_3 | APACONS | null/ATVDONR_ALUM_IND |

Table 2: Constituent Additional Information View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-----------------------|---|
| A2.156 | Child Donor Indicator 3 CHILD_DONOR_IND_3 | Function (APACHIS) | F_DONOR_IND null/If there is a record in APRCHIS, put a Y in this field. |
| A2.157 | Additional Children Flag ADD_CHILDREN_FLAG | Function | F_CHECK_FOR_MORE If there are more than three children, put a Y in this field. |
| A2.158 | Child Surname Prefix 1 SURNAME_PREFIX_1 | APACHLD | SPRIDEN_SURNAME_PREFIX |
| A2.159 | Child Surname Prefix 2 SURNAME_PREFIX_2 | APACHLD | SPRIDEN_SURNAME_PREFIX |
| A2.160 | Child Surname Prefix 3 SURNAME_PREFIX_3 | APACHLD | SPRIDEN_SURNAME_PREFIX |

View 3: Constituent/Organization Shared

AA_CONSTITUENT_ORGANIZ_SHARED

If you are using FOCUS, the view name is APVSHR0.

This view contains information that is related to both constituents and organizations, including special purposes, variable purposes, mail codes, exclusion codes, activity codes, cross references, and external sources.



Tip

Join this view to the [“Constituent Identification”](#) view to include name and address information.

Join this view to the [“Organization”](#) and/or the [“Constituent Additional Information”](#) views to obtain the information included in them. ■

This view accesses the following main database tables.

- AMREXRT Prospect External Ratings Table
- APRACTY Activity Repeating Table
- APRACYR Activity Year Repeating Table
- APREXCL Exclusion Code Repeating Table
- APRMAIL Mail Code Repeating Table
- APRPROS Special Purpose Repeating Table
- APRVIPC Advancement Vip Code Repeating Table
- APRXREF Cross Reference Repeating Table
- APVENTY Base Advancement Entity Table
- SPRIDEN Person Identification/Name Repeating Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) for a complete description of PIDM. ■

The key attribute of this view is

- Personal ID Master PIDM_KEY

Because the PIDM is an internal ID unique to each ID, the view returns one row of information for each ID.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view; however, you may find it useful to specify criteria for some or all of the following attributes. Specifying these criteria selects the population for a report and may reduce the time it takes to run the report.

- Mail Codes 1-4
 - MAIL_CODE_1
 - MAIL_CODE_2
 - MAIL_CODE_3
 - MAIL_CODE4
- Exclusion Codes 1-3
 - EXCLUSION_CODE_1
 - EXCLUSION_CODE_2
 - EXCLUSION_CODE_3
- Cross Reference Codes 1-5
 - XREF_CODE_1
 - XREF_CODE_2
 - XREF_CODE_3
 - XREF_CODE_4
 - XREF_CODE_5
- External Source Codes 1-3
 - EXRS_CODE_1
 - EXRS_CODE_2
 - EXRS_CODE_3

Depending on how the activity concepts are set up on the Crosswalk/Concept Validation Form (GTVSDAX), you may want to specify criteria for the code related to the activity concept used by GTVSDAX.

- Activity Category Code
 - ACCG_CODE_1
- Activity Type
 - ACTP_CODE_1
- Activity Code
 - ACTC_CODE_1

Attributes

The following list specifies the attributes included in this view. The list also indicates the primary form and the database field or function that is the source for each attribute.

Table 3: Constituent/Organization Shared View Attributes

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|------------------------------------|-----------|-------------------------------|
| A3.1 | Personal ID Master Key PIDM_KEY | APAIDEN | APVENTY_PIDM |
| A3.2 | Entity Indicator ENTITY_IND | APAIDEN | SPRIDEN_ENTITY_IND |

Table 3: Constituent/Organization Shared View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|-------------------------------|
| | <p>Select five Special Purposes using the logic defined for the Special Purpose Type concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMPRTP and Internal Group = SPECIAL PURPOSE.</p> | | |
| A3.3 | Special Purpose Type 1 PRTP_CODE_1 | APASPUR | APRPROS_PRTP_CODE |
| A3.4 | Special Purpose Type Description 1 PRTP_DESC_1 | APASPUR | ATVPRTP_DESC |
| A3.5 | Special Purpose Code 1 PRCD_CODE_1 | APASPUR | APRPROS_PRCODE_CODE |
| A3.6 | Special Purpose Code Description 1 PRCD_DESC_1 | APASPUR | ATVPRCD_DESC |
| A3.7 | Special Purpose Type 2 PRTP_CODE_2 | APASPUR | APRPROS_PRTP_CODE |
| A3.8 | Special Purpose Type Description 2 PRTP_DESC_2 | APASPUR | ATVPRTP_DESC |
| A3.9 | Special Purpose Code 2 PRCD_CODE_2 | APASPUR | APRPROS_PRCODE_CODE |
| A3.10 | Special Purpose Code Description 2 PRCD_DESC_2 | APASPUR | ATVPRCD_DESC |
| A3.11 | Special Purpose Type 3 PRTP_CODE_3 | APASPUR | APRPROS_PRTP_CODE |
| A3.12 | Special Purpose Type Description 3 PRTP_DESC_3 | APASPUR | ATVPRTP_DESC |
| A3.13 | Special Purpose Code 3 PRCD_CODE_3 | APASPUR | APRPROS_PRCODE_CODE |

Table 3: Constituent/Organization Shared View Attributes *(cont)*

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A3.14 | Special Purpose Code Description 3 PRCD_DESC_3 | APASPUR | ATVPRCD_DESC |
| A3.15 | Special Purpose Type 4 PRTP_CODE_4 | APASPUR | APRPROS_PRTP_CODE |
| A3.16 | Special Purpose Type Description 4 PRTP_DESC_4 | APASPUR | ATVPRTP_DESC |
| A3.17 | Special Purpose Code 4 PRCD_CODE_4 | APASPUR | APRPROS_PRCD_CODE |
| A3.18 | Special Purpose Code Description 4 PRCD_DESC_4 | APASPUR | ATVPRCD_DESC |
| A3.19 | Special Purpose Type 5 PRTP_CODE_5 | APASPUR | APRPROS_PRTP_CODE |
| A3.20 | Special Purpose Type Description 5 PRTP_DESC_5 | APASPUR | ATVPRTP_DESC |
| A3.21 | Special Purpose Code 5 PRCD_CODE_5 | APASPUR | APRPROS_PRCD_CODE |
| A3.22 | Special Purpose Code Description 5 PRCD_DESC_5 | APASPUR | ATVPRCD_DESC |
| A3.23 | Additional Special Purposes Flag ADD_SPECIAL_PURPOSE_FLAG | Function | F_CHECK_FOR_MORE If are more than five special purpose codes, put a Y in this field. |

Table 3: Constituent/Organization Shared View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| | <p>Select three variable purposes using the logic defined for the Variable Purpose Code concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMVIPC and Internal Group = VARIABLE PURPOSE.</p> | | |
| A3.24 | Variable Purpose Code 1 VIPCODE_1 | APASPUR | APRVIPCODE_CODE |
| A3.25 | Variable Purpose Description 1 VIPDESC_1 | APASPUR | ATVVIPDESC |
| A3.26 | Variable Purpose Code 2 VIPCODE_2 | APASPUR | APRVIPCODE_CODE |
| A3.27 | Variable Purpose Description 2 VIPDESC_2 | APASPUR | ATVVIPDESC |
| A3.28 | Variable Purpose Code 3 VIPCODE_3 | APASPUR | APRVIPCODE_CODE |
| A3.29 | Variable Purpose Description 3 VIPDESC_3 | APASPUR | ATVVIPDESC |
| A3.30 | Additional Variable Purposes Flag ADD_VARIABLE_PURPOSE_FLAG | Function | F_CHECK_FOR_MORE If are more than three variable purpose codes, put a Y in this field. |
| | <p>Select four mail codes and related information using the logic defined for the Mail Code (Advancement) concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMMAIL and Internal Group = MAIL CODE.</p> | | |
| A3.31 | Mail Code 1 MAILCODE_1 | APAMAIL | APRMAIL_MAIL_CODE |
| A3.32 | Mail Code Description 1 MAILDESC_1 | APAMAIL | GTVMAIL_DESC |

Table 3: Constituent/Organization Shared View Attributes *(cont)*

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|-------------------------------|
| A3.33 | Mail Date 1 MAIL_DATE_1 | APAMAIL | APRMAIL_DATE |
| A3.34 | Mail Code Address Type 1 MAIL_ADDRESS_TYPE_1 | APAMAIL | APRMAIL_ATYP_CODE |
| A3.35 | Mail Code 2 MAIL_CODE_2 | APAMAIL | APRMAIL_MAIL_CODE |
| A3.36 | Mail Code Description 2 MAIL_DESC_2 | APAMAIL | GTVMAIL_DESC |
| A3.37 | Mail Date 2 MAIL_DATE_2 | APAMAIL | APRMAIL_DATE |
| A3.38 | Mail Code Address Type 2 MAIL_ADDRESS_TYPE_2 | APAMAIL | APRMAIL_ATYP_CODE |
| A3.39 | Mail Code 3 MAIL_CODE_3 | APAMAIL | APRMAIL_MAIL_CODE |
| A3.40 | Mail Code Description 3 MAIL_DESC_3 | APAMAIL | GTVMAIL_DESC |
| A3.41 | Mail Date 3 MAIL_DATE_3 | APAMAIL | APRMAIL_DATE |
| A3.42 | Mail Code Address Type 3 MAIL_ADDRESS_TYPE_3 | APAMAIL | APRMAIL_ATYP_CODE |
| A3.43 | Mail Code 4 MAIL_CODE_4 | APAMAIL | APRMAIL_MAIL_CODE |
| A3.44 | Mail Code Description 4 MAIL_DESC_4 | APAMAIL | GTVMAIL_DESC |
| A3.45 | Mail Date 4 MAIL_DATE_4 | APAMAIL | APRMAIL_DATE |

Table 3: Constituent/Organization Shared View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|---|-----------|--|
| A3.46 | Mail Code Address Type 4 MAIL_ADDRESS_TYPE_4 | APAMAIL | APRMAIL_ATYP_CODE |
| A3.47 | Additional Mail Codes Flag ADD_MAIL_FLAG | Function | F_CHECK_FOR_MORE If there are more than four mail codes, put a Y in this field. |
| <p>Select three exclusions using the logic defined for the Exclusion Code (Const/Org) concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMEXCL and Internal Group = EXCLUSION.</p> <p>Note: Be sure that you refer to the correct Exclusion Code concept because there is more than one.</p> | | | |
| A3.48 | Exclusion Code 1 EXCL_CODE_1 | APAMAIL | APREXCL_EXCL_CODE |
| A3.49 | Exclusion Code Description 1 EXCL_DESC_1 | APAMAIL | ATVEXCL_DESC |
| A3.50 | Exclusion Date 1 EXCLUSION_DATE_1 | APAMAIL | APREXCL_DATE |
| A3.51 | Exclusion Code 2 EXCL_CODE_2 | APAMAIL | APREXCL_EXCL_CODE |
| A3.52 | Exclusion Code Description 2 EXCL_DESC_2 | APAMAIL | ATVEXCL_DESC |
| A3.53 | Exclusion Date 2 EXCLUSION_DATE_2 | APAMAIL | APREXCL_DATE |
| A3.54 | Exclusion Code 3 EXCL_CODE_3 | APAMAIL | APREXCL_EXCL_CODE |
| A3.55 | Exclusion Code Description 3 EXCL_DESC_3 | APAMAIL | ATVEXCL_DESC |

Table 3: Constituent/Organization Shared View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|---|-----------|---|
| A3.56 | Exclusion Date 3 EXCLUSION_DATE_3 | APAMAIL | APREXCL_DATE |
| A3.57 | Additional Exclusion Codes Flag ADD_EXCLUSION_FLAG | Function | F_CHECK_FOR_MORE If there are more than three exclusion codes, put a <i>Y</i> in this field. |
| <p>Select three Activities using the logic defined for the Activity Category Code concept, the Activity Type concept, or the Activity Code concept on GTVSDAX.</p> <p>To see a full explanation of how these concepts work together, refer to the <i>GTVSDAX Handbook</i>. To see which values are set up in the GTVSDAX logic, go to the GTVSDAX form and query as follows:</p> <ul style="list-style-type: none"> • Activity Category Code, query on Internal Code = <i>ALUMACCG</i> and Internal Group = <i>ACTIVITY CATEGORY</i> • Activity Type, query on Internal Code = <i>ALUMACTP</i> and Internal Group = <i>ACTIVITY TYPE</i> • Activity Code, query on Internal Code = <i>ALUMACTC</i> and Internal Group = <i>ACTIVITY</i> | | | |
| A3.58 | Activity Category Code 1 ACCG_CODE_1 | APAACTY | STVACTC_ACCG_CODE |
| A3.59 | Activity Category Description 1 ACCG_DESC_1 | APAACTY | STVACCG_DESC |
| A3.60 | Activity Type 1 ACTP_CODE_1 | APAACTY | STVACTC_ACTP_CODE |
| A3.61 | Activity Type Description 1 ACTP_DESC_1 | APAACTY | STVACTP_DESC |
| A3.62 | Activity Code 1 ACTC_CODE_1 | APAACTY | APRACTY_ACTC_CODE |
| A3.63 | Activity Code Description 1 ACTC_DESC_1 | APAACTY | STVACTC_DESC |

Table 3: Constituent/Organization Shared View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|--------------------|-------------------------------|
| A3.64 | Most Recent Year Participated in Activity 1 MOST_RECENT_ACTIVITY_YEAR_1 | APAACTY | APRACYR_YEAR |
| A3.65 | Total Years Participated in Activity 1 TOTAL_ACTIVITY_YEARS_1 | Function (APAACTY) | F_YEARS_ACTIVITY |
| A3.66 | Activity Category Code 2 ACCG_CODE_2 | APAACTY | STVACTC_ACCG_CODE |
| A3.67 | Activity Category Description 2 ACCG_DESC_2 | APAACTY | STVACCG_DESC |
| A3.68 | Activity Type 2 ACTP_CODE_2 | APAACTY | STVACTC_ACTP_CODE |
| A3.69 | Activity Type Description 2 ACTP_DESC_2 | APAACTY | STVACTP_DESC |
| A3.70 | Activity Code 2 ACTC_CODE_2 | APAACTY | APRACTY_ACTC_CODE |
| A3.71 | Activity Code Description 2 ACTC_DESC_2 | APAACTY | STVACTC_DESC |
| A3.72 | Most Recent Year Participated in Activity 2 MOST_RECENT_ACTIVITY_YEAR_2 | APAACTY | APRACYR_YEAR |
| A3.73 | Total Years Participated in Activity 2 TOTAL_ACTIVITY_YEARS_2 | Function (APAACTY) | F_YEARS_ACTIVITY |
| A3.74 | Activity Category Code 3 ACCG_CODE_3 | APAACTY | STVACTC_ACCG_CODE |
| A3.75 | Activity Category Description 3 ACCG_DESC_3 | APAACTY | STVACCG_DESC |
| A3.76 | Activity Type 3 ACTP_CODE_3 | APAACTY | STVACTC_ACTP_CODE |

Table 3: Constituent/Organization Shared View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|--|--------------------|---|
| A3.77 | Activity Type Description 3 ACTP_DESC_3 | APAACTY | STVACTP_DESC |
| A3.78 | Activity Code 3 ACTC_CODE_3 | APAACTY | APRACTY_ACTC_CODE |
| A3.79 | Activity Code Description 3 ACTC_DESC_3 | APAACTY | STVACTC_DESC |
| A3.80 | Most Recent Year Participated in Activity 3 MOST_RECENT_ACTIVITY_YEAR_3 | APAACTY | APRACYR_YEAR |
| A3.81 | Total Years Participated in Activity 3 TOTAL_ACTIVITY_YEARS_3 | Function (APAACTY) | F_YEARS_ACTIVITY |
| A3.82 | Additional Activities Flag ADD_ACTIVITY_FLAG | Function | F_ACTIVITY_CODE_INFO If there are more than three activities, put a Y in this field. |
| <p>Select five Cross Reference codes using the logic defined for the Cross Reference Code concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX and query on Internal Code = <i>ALUMXREF</i> and Internal Group = <i>CROSS REFERENCE</i>.</p> | | | |
| A3.83 | Cross Reference Code 1 XREF_CODE_1 | APAXREF | APRXREF_XREF_CODE |
| A3.84 | Cross Reference Description 1 XREF_DESC_1 | APAXREF | ATVXREF_DESC |
| A3.85 | Cross Reference Personal ID Master 1 CROSS_REFERENCE_PIDM_1 | APAXREF | APRXREF_XREF_PIDM |
| A3.86 | Cross Reference Surname Prefix 1 CROS_REF_SNAME_PRFX_1 | APAXREF | SPRIDEN_SURNAME_PREFIX |

Table 3: Constituent/Organization Shared View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A3.87 | Cross Reference Last Name 1 CROSS_REFERENCE_LAST_NAME_1 | APAXREF | SPRIDEN_LAST_NAME Note: Get name and ID information from SPRIDEN based on the Cross Reference PIDM. |
| A3.88 | Cross Reference First Name 1 CROSS_REFERENCE_FIRST_NAME_1 | APAXREF | SPRIDEN_FIRST_NAME |
| A3.89 | Cross Reference Middle Name 1 CROSS_REFERENCE_MIDDLE_NAME_1 | APAXREF | SPRIDEN_MI |
| A3.90 | Cross Reference ID 1 CROSS_REFERENCE_ID_NUMBER_1 | APAXREF | SPRIDEN_ID |
| A3.91 | Cross Reference Code 2 XREF_CODE_2 | APAXREF | APRXREF_XREF_CODE |
| A3.92 | Cross Reference Description 2 XREF_DESC_2 | APAXREF | ATVXREF_DESC |
| A3.93 | Cross Reference Personal ID Master 2 CROSS_REFERENCE_PIDM_2 | APAXREF | APRXREF_XREF_PIDM |
| A3.94 | Cross Reference Surname Prefix 2 CROS_REF_SNAME_PRFX_2 | APAXREF | SPRIDEN_SURNAME_PREFIX |
| A3.95 | Cross Reference Last Name 2 CROSS_REFERENCE_LAST_NAME_2 | APAXREF | SPRIDEN_LAST_NAME Note: Get name and ID information from SPRIDEN based on the Cross Reference PIDM. |
| A3.96 | Cross Reference First Name 2 CROSS_REFERENCE_FIRST_NAME_2 | APAXREF | SPRIDEN_FIRST_NAME |

Table 3: Constituent/Organization Shared View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A3.97 | Cross Reference Middle Name 2 CROSS_REFERENCE_MIDDLE_NAME_2 | APAXREF | SPRIDEN_MI |
| A3.98 | Cross Reference ID 2 CROSS_REFERENCE_ID_NUMBER_2 | APAXREF | SPRIDEN_ID |
| A3.99 | Cross Reference Code 3 XREF_CODE_3 | APAXREF | APRXREF_XREF_CODE |
| A3.100 | Cross Reference Description 3 XREF_DESC_3 | APAXREF | ATVXREF_DESC |
| A3.101 | Cross Reference Personal ID Master 3 CROSS_REFERENCE_PIDM_3 | APAXREF | APRXREF_XREF_PIDM |
| A3.102 | Cross Reference Surname Prefix 3 CROS_REF_SNAME_PRFX_3 | APAXREF | SPRIDEN_SURNAME_PREFIX |
| A3.103 | Cross Reference Last Name 3 CROSS_REFERENCE_LAST_NAME_3 | APAXREF | SPRIDEN_LAST_NAME Note: Get name and ID information from SPRIDEN based on the Cross Reference PIDM. |
| A3.104 | Cross Reference First Name 3 CROSS_REFERENCE_FIRST_NAME_3 | APAXREF | SPRIDEN_FIRST_NAME |
| A3.105 | Cross Reference Middle Name 3 CROSS_REFERENCE_MIDDLE_NAME_3 | APAXREF | SPRIDEN_MI |
| A3.106 | Cross Reference ID 3 CROSS_REFERENCE_ID_NUMBER_3 | APAXREF | SPRIDEN_ID |
| A3.107 | Cross Reference Code 4 XREF_CODE_4 | APAXREF | APRXREF_XREF_CODE |

Table 3: Constituent/Organization Shared View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A3.108 | Cross Reference Description 4 XREF_DESC_4 | APAXREF | ATVXREF_DESC |
| A3.109 | Cross Reference Personal ID Master 4 CROSS_REFERENCE_PIDM_4 | APAXREF | APRXREF_XREF_PIDM |
| A3.110 | Cross Reference Surname Prefix 4 CROS_REF_SNAME_PRFX4 | APAXREF | SPRIDEN_SURNAME_PREFIX |
| A3.111 | Cross Reference Last Name 4 CROSS_REFERENCE_LAST_NAME_4 | APAXREF | SPRIDEN_LAST_NAME Note: Get name and ID information from SPRIDEN based on the Cross Reference PIDM. |
| A3.112 | Cross Reference First Name 4 CROSS_REFERENCE_FIRST_NAME_4 | APAXREF | SPRIDEN_FIRST_NAME |
| A3.113 | Cross Reference Middle Name 4 CROSS_REFERENCE_MIDDLE_NAME_4 | APAXREF | SPRIDEN_MI |
| A3.114 | Cross Reference ID 4 CROSS_REFERENCE_ID_NUMBER_4 | APAXREF | SPRIDEN_ID |
| A3.115 | Cross Reference Code 5 XREF_CODE_5 | APAXREF | APRXREF_XREF_CODE |
| A3.116 | Cross Reference Description 5 XREF_DESC_5 | APAXREF | ATVXREF_DESC |
| A3.117 | Cross Reference Personal ID Master 5 CROSS_REFERENCE_PIDM_5 | APAXREF | APRXREF_XREF_PIDM |
| A3.118 | Cross Reference Surname Prefix 5 CROS_REF_SNAME_PRFX_5 | APAXREF | SPRIDEN_SURNAME_PREFIX |

Table 3: Constituent/Organization Shared View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|--|-----------|---|
| A3.119 | Cross Reference Last Name 5 CROSS_REFERENCE_LAST_NAME_5 | APAXREF | SPRIDEN_LAST_NAME Note: Get name and ID information from SPRIDEN based on the Cross Reference PIDM. |
| A3.120 | Cross Reference First Name 5 CROSS_REFERENCE_FIRST_NAME_5 | APAXREF | SPRIDEN_FIRST_NAME |
| A3.121 | Cross Reference Middle Name 5 CROSS_REFERENCE_MIDDLE_NAME_5 | APAXREF | SPRIDEN_MI |
| A3.122 | Cross Reference ID 5 CROSS_REFERENCE_ID_NUMBER_5 | APAXREF | SPRIDEN_ID |
| A3.123 | Additional Cross References Flag ADD_CROSS_REFERENCE_FLAG | Function | F_CHECK_FOR_MORE If there are more than five course references, put a <i>Y</i> in this field. |
| <p>Select three External Sources using the logic defined for the External Source Code concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX and query on Internal Code = <i>ALUMEXRS</i> and Internal Group = <i>EXTERNAL SOURCE</i>.</p> | | | |
| A3.124 | External Source Code 1 EXRS_CODE_1 | APAEXRS | AMREXRT_EXRS_CODE |
| A3.125 | External Source Description 1 EXRS_DESC_1 | APAEXRS | ATVEXRS_DESC |
| A3.126 | External Score 1 EXTERNAL_SCORE_1 | APAEXRS | AMREXRT_EXT_SCORE |
| A3.127 | External Value 1 EXTERNAL_VALUE_1 | APAEXRS | AMREXRT_EXT_VALUE |

Table 3: Constituent/Organization Shared View Attributes *(cont)*

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A3.128 | External Level 1 EXTERNAL_LEVEL_1 | APAEXRS | AMREXRT_EXT_LEVEL |
| A3.129 | External Source Code 2 EXRS_CODE_2 | APAEXRS | AMREXRT_EXRS_CODE |
| A3.130 | External Source Description 2 EXRS_DESC_2 | APAEXRS | ATVEXRS_DESC |
| A3.131 | External Score 2 EXTERNAL_SCORE_2 | APAEXRS | AMREXRT_EXT_SCORE |
| A3.132 | External Value 2 EXTERNAL_VALUE_2 | APAEXRS | AMREXRT_EXT_VALUE |
| A3.133 | External Level 2 EXTERNAL_LEVEL_2 | APAEXRS | AMREXRT_EXT_LEVEL |
| A3.134 | External Source Code 3 EXRS_CODE_3 | APAEXRS | AMREXRT_EXRS_CODE |
| A3.135 | External Source Description 3 EXRS_DESC_3 | APAEXRS | ATVEXRS_DESC |
| A3.136 | External Score 3 EXTERNAL_SCORE_3 | APAEXRS | AMREXRT_EXT_SCORE |
| A3.137 | External Value 3 EXTERNAL_VALUE_3 | APAEXRS | AMREXRT_EXT_VALUE |
| A3.138 | External Level 3 EXTERNAL_LEVEL_3 | APAEXRS | AMREXRT_EXT_LEVEL |
| A3.139 | Additional External Sources Flag ADD_EXTERNAL_SOURCE_FLAG | Function | F_CHECK_FOR_MORE If there are more than three external sources, put a Y in this field. |

View 4: Prospect

AA_PROSPECT

If you are using FOCUS, the view name is AMVPRS0.

This view contains all prospect related information not included in the Constituent Identification view, including external sources, references, status code, ratings, staff assignments, project codes, and contacts. Because all prospects are also constituents, the basic information in the Constituent Identification view can be used to supplement this view.



Tip

Join this view to the [“Constituent Identification”](#) and/or the [“Constituent Additional Information”](#) views for a complete picture of prospects. ■

This view accesses the following main database tables.

- AMRCONT Prospect Contact Table
- AMREXRT Prospect External Ratings Table
- AMRINFO Prospect Information Table
- AMRPRIN Prospect Project/Interest Table
- AMRPRRT Prospect Rating Table
- AMRSTAF Prospect Staff Assignment Table
- GURIDEN User Identification Table
- SPRIDEN Person Identification/Name Repeating Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) for a complete description of PIDM. ■

The key attribute of this view is

- Personal ID Master PIDM_KEY

Because the PIDM is an internal ID unique to each prospect, the view returns one row of information for each prospect.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view; however, you may find it useful to specify criteria for some or all of the following attributes. Specifying these criteria selects the population for a report and may reduce the time it takes to run the report.

- Rating Codes 1-4
 - RATE_CODE_1
 - RATE_CODE_2
 - RATE_CODE_3
 - RATE_CODE4

- Staff Assignments 1-5
 - PRIMARY_STAFF_ASSIGN_STFT_CODE
 - OTHER_STAFF_ASSIGN_STFT_CODE_1
 - OTHER_STAFF_ASSIGN_STFT_CODE_2
 - OTHER_STAFF_ASSIGN_STFT_CODE_3
 - OTHER_STAFF_ASSIGN_STFT_CODE_4

- Project Codes 1-5
 - PROJ_CODE_1
 - PROJ_CODE_2
 - PROJ_CODE_3
 - PROJ_CODE_4
 - PROJ_CODE_5

Attributes

The following list specifies the attributes included in the Prospect view, indicating the primary form and the database field or function that is the source for each attribute.

Table 4: Prospect View Attributes

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|-------------------------------|
| A4.1 | Prospect Personal ID Master Key PIDM_KEY | AMAINFO | AMRINFO_PIDM |
| A4.2 | Entity Indicator ENTITY_IND | APAIDEN | SPRIDEN_ENTITY_IND |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|-------------------------------|
| | <p>Select three External Sources using the logic defined for the External Source Code concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMEXRS and Internal Group = EXTERNAL SOURCE.</p> | | |
| A4.3 | External Source Code 1 EXRS_CODE_1 | AMAINFO | AMREXRT_EXRS_CODE |
| A4.4 | External Source Description 1 EXRS_DESC_1 | AMAINFO | ATVEXRS_DESC |
| A4.5 | External Score 1 EXTERNAL_SCORE_1 | AMAINFO | AMREXRT_EXT_SCORE |
| A4.6 | External Value 1 EXTERNAL_VALUE_1 | AMAINFO | AMREXRT_EXT_VALUE |
| A4.7 | External Level 1 EXTERNAL_LEVEL_1 | AMAINFO | AMREXRT_EXT_LEVEL |
| A4.8 | External Source Code 2 EXRS_CODE_2 | AMAINFO | AMREXRT_EXRS_CODE |
| A4.9 | External Source Description 2 EXRS_DESC_2 | AMAINFO | ATVEXRS_DESC |
| A4.10 | External Score 2 EXTERNAL_SCORE_2 | AMAINFO | AMREXRT_EXT_SCORE |
| A4.11 | External Value 2 EXTERNAL_VALUE_2 | AMAINFO | AMREXRT_EXT_VALUE |
| A4.12 | External Level 2 EXTERNAL_LEVEL_2 | AMAINFO | AMREXRT_EXT_LEVEL |
| A4.13 | External Source Code 3 EXRS_CODE_3 | AMAINFO | AMREXRT_EXRS_CODE |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|---|
| A4.14 | External Source Description 3 EXRS_DESC_3 | AMAINFO | ATVEXRS_DESC |
| A4.15 | External Score 3 EXTERNAL_SCORE_3 | AMAINFO | AMREXRT_EXT_SCORE |
| A4.16 | External Value 3 EXTERNAL_VALUE_3 | AMAINFO | AMREXRT_EXT_VALUE |
| A4.17 | External Level 3 EXTERNAL_LEVEL_3 | AMAINFO | AMREXRT_EXT_LEVEL |
| A4.18 | Additional External Sources Flag ADD_EXTERNAL_SOURCE_FLAG | Function | F_CHECK_FOR_MORE If there are more than three external sources, put a Y in this field. |
| A4.19 | Reference Code REFR_CODE | AMAINFO | AMRINFO_REFR_CODE |
| A4.20 | Reference Code Description REFR_DESC | AMAINFO | ATVREFR_DESC |
| A4.21 | Status Code PRST_CODE | AMAINFO | AMRINFO_STATUS |
| A4.22 | Status Code Description PRST_DESC | AMAINFO | ATVPRST_DESC |
| A4.23 | Target Ask Amount TARGET_ASK_AMT | AMAINFO | AMRINFO_PROSP_RATE |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|-------------------------------|
| | <p>Select five Ratings using the logic defined for the Rating Type concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMRTGT and Internal Group = RATING.</p> | | |
| A4.24 | Rating Type 1 RTGT_CODE_1 | AMAINFO | AMRPRRT_RTGT_CODE |
| A4.25 | Rating Type Description 1 RTGT_DESC_1 | AMAINFO | ATVRTGT_DESC |
| A4.26 | Rating Code 1 RATE_CODE_1 | AMAINFO | AMRPRRT_RATE_CODE |
| A4.27 | Rating Description 1 RATE_DESC_1 | AMAINFO | ATVRATE_DESC |
| A4.28 | Rate Screen Code 1 RSCR_CODE_1 | AMAINFO | AMRPRRT_RSCR_CODE |
| A4.29 | Rate Screen Description 1 RSCR_DESC_1 | AMAINFO | ATVRSCR_CODE |
| A4.30 | Rater Identification Code RATER_IDEN_CODE_1 | AMAINFO | AMRPRRT_IDEN_CODE |
| A4.31 | Rater Name RATER_IDEN_DESC_1 | AMAINFO | GURIDEN_DESC |
| A4.32 | Rating Type 2 RTGT_CODE_2 | AMAINFO | AMRPRRT_RTGT_CODE |
| A4.33 | Rating Type Description 2 RTGT_DESC_2 | AMAINFO | ATVRTGT_DESC |
| A4.34 | Rating Code 2 RATE_CODE_2 | AMAINFO | AMRPRRT_RATE_CODE |
| A4.35 | Rating Description 2 RATE_DESC_2 | AMAINFO | ATVRATE_DESC |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|-------------------------------|
| A4.36 | Rate Screen Code 2 RSCR_CODE_2 | AMAINFO | AMRPRRT_RSCR_CODE |
| A4.37 | Rate Screen Description 2 RSCR_DESC_2 | AMAINFO | ATVRSCR_CODE |
| A4.38 | Rater Identification Code 2 RATER_IDEN_CODE_2 | AMAINFO | AMRPRRT_IDEN_CODE |
| A4.39 | Rater Name 2 RATER_IDEN_DESC_2 | AMAINFO | GURIDEN_DESC |
| A4.40 | Rating Type 3 RTGT_CODE_3 | AMAINFO | AMRPRRT_RTGT_CODE |
| A4.41 | Rating Type Description 3 RTGT_DESC_3 | AMAINFO | ATVRTGT_DESC |
| A4.42 | Rating Code 3 RATE_CODE_3 | AMAINFO | AMRPRRT_RATE_CODE |
| A4.43 | Rating Description 3 RATE_DESC_3 | AMAINFO | ATVRATE_DESC |
| A4.44 | Rate Screen Code 3 RSCR_CODE_3 | AMAINFO | AMRPRRT_RSCR_CODE |
| A4.45 | Rate Screen Description 3 RSCR_DESC_3 | AMAINFO | ATVRSCR_CODE |
| A4.46 | Rater Identification Code 3 RATER_IDEN_CODE_3 | AMAINFO | AMRPRRT_IDEN_CODE |
| A4.47 | Rater Name 3 RATER_IDEN_DESC_3 | AMAINFO | GURIDEN_DESC |
| A4.48 | Rating Type 4 RTGT_CODE_4 | AMAINFO | AMRPRRT_RTGT_CODE |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|-------------------------------|
| A4.49 | Rating Type Description 4 RTGT_DESC_4 | AMAINFO | ATVRTGT_DESC |
| A4.50 | Rating Code 4 RATE_CODE_4 | AMAINFO | AMRPRRT_RATE_CODE |
| A4.51 | Rating Description 4 RATE_DESC_4 | AMAINFO | ATVRATE_DESC |
| A4.52 | Rate Screen Code 4 RSCR_CODE_4 | AMAINFO | AMRPRRT_RSCR_CODE |
| A4.53 | Rate Screen Description 4 RSCR_DESC_4 | AMAINFO | ATVRSCR_CODE |
| A4.54 | Rater Identification Code 4 RATER_IDEN_CODE_4 | AMAINFO | AMRPRRT_IDEN_CODE |
| A4.55 | Rater Name 4 RATER_IDEN_DESC_4 | AMAINFO | GURIDEN_DESC |
| A4.56 | Rating Type 5 RTGT_CODE_5 | AMAINFO | AMRPRRT_RTGT_CODE |
| A4.57 | Rating Type Description 5 RTGT_DESC_5 | AMAINFO | ATVRTGT_DESC |
| A4.58 | Rating Code 5 RATE_CODE_5 | AMAINFO | AMRPRRT_RATE_CODE |
| A4.59 | Rating Description 5 RATE_DESC_5 | AMAINFO | ATVRATE_DESC |
| A4.60 | Rate Screen Code 5 RSCR_CODE_5 | AMAINFO | AMRPRRT_RSCR_CODE |
| A4.61 | Rate Screen Description 5 RSCR_DESC_5 | AMAINFO | ATVRSCR_CODE |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|--|-------------|---|
| A4.62 | Rater Identification Code 5 RATER_IDEN_CODE_5 | AMAINFO | AMRPRRT_IDEN_CODE |
| A4.63 | Rater Name 5 RATER_IDEN_DESC_5 | AMAINFO | GURIDEN_DESC |
| A4.64 | Additional Ratings Flag ADD_RATING_FLAG | Function | F_CHECK_FOR_MORE If there are more than five ratings, put a Y in this field. |
| <p>Select five Staff Assignments. Get the Primary Assignment first based on the Primary Assignment Indicator, then select the other four assignments using the logic defined for the Staff Assignment Type concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMSTFT and Internal Group = STAFF ASSIGNMENT.</p> | | | |
| A4.65 | Primary Assignment Indicator PRIMARY_ASSIGN_IND | AMAINFO | AMRSTAF_PRIMARY_IND |
| A4.66 | Primary Staff Assignment Type PRIMARY_STAFF_ASSIGN_STFT_CODE | AMAINFO | AMRSTAF_STFT_CODE |
| A4.67 | Primary Staff Assignment Description PRIMARY_STAFF_ASSIGN_STFT_DESC | AMAINFO | ATVSTFT_DESC |
| A4.68 | Primary Staff Assignment Code PRIMARY_STAFF_ASSIGN_IDEN_CODE | AMAINFO | AMRSTAF_IDEN_CODE |
| A4.69 | Primary Staff Assignment Name PRIMARY_STAFF_ASSIGN_IDEN_DESC | AMAINFO | GURIDEN_DESC |
| A4.70 | Other Staff Assignment Type 1 OTHER_STAFF_ASSIGN_STFT_CODE_1 | AMAINFO | AMRSTAF_STFT_CODE |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|-------------------------------|
| A4.71 | Other Staff Assignment Description 1 OTHER_STAFF_ASSIGN_STFT_DESC_1 | AMAINFO | ATVSTFT_DESC |
| A4.72 | Other Staff Assignment Code 1 OTHER_STAFF_ASSIGN_IDEN_CODE_1 | AMAINFO | AMRSTAF_IDEN_CODE |
| A4.73 | Other Staff Assignment Name 1 OTHER_STAFF_ASSIGN_IDEN_DESC_1 | AMAINFO | GURIDEN_DESC |
| A4.74 | Other Staff Assignment Type 2 OTHER_STAFF_ASSIGN_STFT_CODE_2 | AMAINFO | AMRSTAF_STFT_CODE |
| A4.75 | Other Staff Assignment Description 2 OTHER_STAFF_ASSIGN_STFT_DESC_2 | AMAINFO | ATVSTFT_DESC |
| A4.76 | Other Staff Assignment Code 2 OTHER_STAFF_ASSIGN_IDEN_CODE_2 | AMAINFO | AMRSTAF_IDEN_CODE |
| A4.77 | Other Staff Assignment Name 2 OTHER_STAFF_ASSIGN_IDEN_DESC_2 | AMAINFO | GURIDEN_DESC |
| A4.78 | Other Staff Assignment Type 3 OTHER_STAFF_ASSIGN_STFT_CODE_3 | AMAINFO | AMRSTAF_STFT_CODE |
| A4.79 | Other Staff Assignment Description 3 OTHER_STAFF_ASSIGN_STFT_DESC_3 | AMAINFO | ATVSTFT_DESC |
| A4.80 | Other Staff Assignment Code 3 OTHER_STAFF_ASSIGN_IDEN_CODE_3 | AMAINFO | AMRSTAF_IDEN_CODE |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|--|-------------|---|
| A4.81 | Other Staff Assignment Name 3 OTHER_STAFF_ASSIGN_IDEN_DESC_3 | AMAINFO | GURIDEN_DESC |
| A4.82 | Other Staff Assignment Type 4 OTHER_STAFF_ASSIGN_STFT_CODE_4 | AMAINFO | AMRSTAF_STFT_CODE |
| A4.83 | Other Staff Assignment Description 4 OTHER_STAFF_ASSIGN_STFT_DESC_4 | AMAINFO | ATVSTFT_DESC |
| A4.84 | Other Staff Assignment Code 4 OTHER_STAFF_ASSIGN_IDEN_CODE_4 | AMAINFO | AMRSTAF_IDEN_CODE |
| A4.85 | Other Staff Assignment Name 4 OTHER_STAFF_ASSIGN_IDEN_DESC_4 | AMAINFO | GURIDEN_DESC |
| A4.86 | Additional Staff Assignments Flag ADD_STAFF_ASSIGN_FLAG | Function | F_CHECK_FOR_MORE If there are more than five staff assignments, put a Y in this field. |
| <p>Select five Project codes using the logic defined for the Project Code concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMPROJ</i> and Internal Group = <i>PROJECT</i>.</p> | | | |
| A4.87 | Assigned Project Code 1 PROJ_CODE_1 | AMAINFO | AMRPRIN_PROJ_CODE |
| A4.88 | Assigned Project Description 1 PROJ_DESC_1 | AMAINFO | ATVPROJ_DESC |
| A4.89 | Giving Vehicle 1 GIVH_CODE_1 | AMAINFO | AMRPRIN_GIVH_CODE |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|-------------------------------|
| A4.90 | Giving Vehicle Description 1 GIVH_DESC_1 | AMAINFO | ATVGIVH_DESC |
| A4.91 | Assigned Project Code 2 PROJ_CODE_2 | AMAINFO | AMRPRIN_PROJ_CODE |
| A4.92 | Assigned Project Description 2 PROJ_DESC_2 | AMAINFO | ATVPROJ_DESC |
| A4.93 | Giving Vehicle 2 GIVH_CODE_2 | AMAINFO | AMRPRIN_GIVH_CODE |
| A4.94 | Giving Vehicle Description 2 GIVH_DESC_2 | AMAINFO | ATVGIVH_DESC |
| A4.95 | Assigned Project Code 3 PROJ_CODE_3 | AMAINFO | AMRPRIN_PROJ_CODE |
| A4.96 | Assigned Project Description 3 PROJ_DESC_3 | AMAINFO | ATVPROJ_DESC |
| A4.97 | Giving Vehicle 3 GIVH_CODE_3 | AMAINFO | AMRPRIN_GIVH_CODE |
| A4.98 | Giving Vehicle Description 3 GIVH_DESC_3 | AMAINFO | ATVGIVH_DESC |
| A4.99 | Assigned Project Code 4 PROJ_CODE_4 | AMAINFO | AMRPRIN_PROJ_CODE |
| A4.100 | Assigned Project Description 4 PROJ_DESC_4 | AMAINFO | ATVPROJ_DESC |
| A4.101 | Giving Vehicle 4 GIVH_CODE_4 | AMAINFO | AMRPRIN_GIVH_CODE |
| A4.102 | Giving Vehicle Description 4 GIVH_DESC_4 | AMAINFO | ATVGIVH_DESC |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|---|-------------|---|
| A4.103 | Assigned Project Code 5 PROJ_CODE_5 | AMAINFO | AMRPRIN_PROJ_CODE |
| A4.104 | Assigned Project Description 5 PROJ_DESC_5 | AMAINFO | ATVPROJ_DESC |
| A4.105 | Giving Vehicle 5 GIVH_CODE_5 | AMAINFO | AMRPRIN_GIVH_CODE |
| A4.106 | Giving Vehicle Description 5 GIVH_DESC_5 | AMAINFO | ATVGIVH_DESC |
| A4.107 | Additional Project Codes Flag ADD_PROJECT_FLAG | Function | F_CHECK_FOR_MORE If there are more than five project codes, put a Y in this field. |
| Select the three most recent Contacts based on the AMRCONT_Contact_Date field. | | | |
| A4.108 | Contact/Originator Code 1 CONTACT_IDEN_CODE_1 | AMACONT | AMRCONT_IDEN_CODE |
| A4.109 | Contact/Originator Name 1 CONTACT_IDEN_DESC_1 | AMACONT | GURIDEN_DESC |
| A4.110 | Contact Date 1 CONTACT_DATE_1 | AMACONT | AMRCONT_CONTACT_DATE |
| A4.111 | Contact Text 1 CONTACT_TEXT_1 | AMACONT | AMRCONT_CONTACT |
| A4.112 | Move Code 1 CONTACT_MOVE_CODE_1 | AMACONT | AMRCONT_MOVE_CODE |
| A4.113 | Asking Amount 1 CONTACT_ASK_AMT_1 | AMACONT | AMRCONT_ASK_AMT |
| A4.114 | Next Action 1 NEXT_ACTION_1 | AMACONT | AMRCONT_TICKLER |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|-------------------------------|
| A4.115 | Next Action Date 1 NEXT_ACTION_DATE_1 | AMACONT | AMRCONT_TICK_DATE |
| A4.116 | Person Responsible for Next Action 1 IDEN_CODE_ASGN_1 | AMACONT | AMRCONT_IDEN_CODE_ASGN |
| A4.117 | Name of Person Responsible 1 IDEN_DESC_ASGN_1 | AMACONT | GURIDEN_DESC |
| A4.118 | Contact Project Code 1 CONTACT_PROJ_CODE_1 | AMACONT | AMRCONT_PROJ_CODE |
| A4.119 | Contact Project Description 1 CONTACT_PROJ_DESC_1 | AMACONT | ATVPROJ_DESC |
| A4.120 | Item Reference Number 1 ITEM_REFERER_NUMBER_1 | AMACONT | AMRCONT_ITEM_REFNO |
| A4.121 | Contact/Originator Code 2 CONTACT_IDEN_CODE_2 | AMACONT | AMRCONT_IDEN_CODE |
| A4.122 | Contact/Originator Name 2 CONTACT_IDEN_DESC_2 | AMACONT | GURIDEN_DESC |
| A4.123 | Contact Date 2 CONTACT_DATE_2 | AMACONT | AMRCONT_CONTACT_DATE |
| A4.124 | Contact Text 2 CONTACT_TEXT_2 | AMACONT | AMRCONT_CONTACT |
| A4.125 | Move Code 2 CONTACT_MOVE_CODE_2 | AMACONT | AMRCONT_MOVE_CODE |
| A4.126 | Asking Amount 2 CONTACT_ASK_AMT_2 | AMACONT | AMRCONT_ASK_AMT |
| A4.127 | Next Action 2 NEXT_ACTION_2 | AMACONT | AMRCONT_TICKLER |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|-------------------------------|
| A4.128 | Next Action Date 2 NEXT_ACTION_DATE_2 | AMACONT | AMRCONT_TICK_DATE |
| A4.129 | Person Responsible for Next Action 2 IDEN_CODE_ASGN_2 | AMACONT | AMRCONT_IDEN_CODE_ASGN |
| A4.130 | Name of Person Responsible 2 IDEN_DESC_ASGN_2 | AMACONT | GURIDEN_DESC |
| A4.131 | Contact Project Code 2 CONTACT_PROJ_CODE_2 | AMACONT | AMRCONT_PROJ_CODE |
| A4.132 | Contact Project Description 2 CONTACT_PROJ_DESC_2 | AMACONT | ATVPROJ_DESC |
| A4.133 | Item Reference Number 2 ITEM_REFERER_NUMBER_2 | AMACONT | AMRCONT_ITEM_REFNO |
| A4.134 | Contact/Originator Code 3 CONTACT_IDEN_CODE_3 | AMACONT | AMRCONT_IDEN_CODE |
| A4.135 | Contact/Originator Name 3 CONTACT_IDEN_DESC_3 | AMACONT | GURIDEN_DESC |
| A4.136 | Contact Date 3 CONTACT_DATE_3 | AMACONT | AMRCONT_CONTACT_DATE |
| A4.137 | Contact Text 3 CONTACT_TEXT_3 | AMACONT | AMRCONT_CONTACT |
| A4.138 | Move Code 3 CONTACT_MOVE_CODE_3 | AMACONT | AMRCONT_MOVE_CODE |
| A4.139 | Asking Amount 3 CONTACT_ASK_AMT_3 | AMACONT | AMRCONT_ASK_AMT |
| A4.140 | Next Action 3 NEXT_ACTION_3 | AMACONT | AMRCONT_TICKLER |

Table 4: Prospect View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|---|
| A4.141 | Next Action Date 3 NEXT_ACTION_DATE_3 | AMACONT | AMRCONT_TICK_DATE |
| A4.142 | Person Responsible for Next Action 3 IDEN_CODE_ASGN_3 | AMACONT | AMRCONT_IDEN_CODE_ASGN |
| A4.143 | Name of Person Responsible 3 IDEN_DESC_ASGN_3 | AMACONT | GURIDEN_DESC |
| A4.144 | Contact Project Code 3 CONTACT_PROJ_CODE_3 | AMACONT | AMRCONT_PROJ_CODE |
| A4.145 | Contact Project Description 3 CONTACT_PROJ_DESC_3 | AMACONT | ATVPROJ_DESC |
| A4.146 | Item Reference Number 3 ITEM_REFER_NUMBER_3 | AMACONT | AMRCONT_ITEM_REFNO |
| A4.147 | Additional Contacts Flag ADD_CONTACT_FLAG | Function | F_CHECK_FOR_MORE If there are more than three contacts, put a Y in this field. |

View 5: Giving

AA_GIVING

If you are using FOCUS, the view name is AGVGIV0.

The Giving view lets you report on a donor's giving summarized by fiscal year. This view includes pledge and gift information for the six most recent fiscal years, and pledge and gift lifetime totals. The view also includes information about a donor's spouse, donor categories, and gift societies.

This view accesses the following main database tables.

- AGRGMMO Detail Gift Memo Credit Table
- APBCONS Constituent Base Table
- APRCHIS Giving History by Campaign Repeating Table
- APRCSPS Constituent Spouse Table
- APRDCLB Gift Society Table
- APVENTY Base Advancement Entity Table
- SPBPERS Basic Person Base Table
- SPRIDEN Person Identification/Name Repeating Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) for a complete description of PIDM. ■

The key attribute of this view is

- Donor Personal ID Master PIDM_KEY

Because the PIDM is an internal ID unique to each donor, the view returns one row of information for each donor.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view, but you may find it useful to specify criteria for some or all of the following attributes. Specifying these criteria selects the population for a report and may reduce the time it takes to run the report.

- Preferred Donor Category Code DONOR_PREF_DONR_CODE

Attributes

The following list specifies the attributes included in the Giving view. The list also indicates the primary Banner form and the database field or function that is the source for each attribute.

Table 5: Giving View Attributes

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|--|
| A5.1 | Donor Personal ID Master Key PIDM_KEY | APAGHIS | APVENTY_PIDM |
| A5.2 | Donor Entity Indicator DONOR_ENTITY_IND | APAGHIS | SPRIDEN_ENTITY_IND |
| A5.3 | Donor ID DONOR_ID | APAGHIS | SPRIDEN_ID |
| A5.4 | Donor Social Security Number DONOR_SSN | APAPERS | SPBPERS_SSN |
| A5.5 | Donor Surname Prefix DONOR_SURNAME_PREFIX | APAGHIS | SPRIDEN_SURNAME_PREFIX |
| A5.6 | Donor Last Name DONOR_LAST_NAME | APAGHIS | SPRIDEN_LAST_NAME |
| A5.7 | Donor First Name DONOR_FIRST_NAME | APAGHIS | SPRIDEN_FIRST_NAME |
| A5.8 | Donor Middle Name DONOR_MIDDLE_NAME | APAGHIS | SPRIDEN_MI |
| A5.9 | Donor Middle Initial DONOR_MIDDLE_INITIAL | APAGHIS | SUBSTR (SPRIDEN_MI , 1 , 1) Returns first letter of middle name |
| A5.10 | Donor Name Prefix DONOR_NAME_PREFIX | APAPERS | SPBPERS_NAME_PREFIX |
| A5.11 | Donor Name Suffix DONOR_NAME_SUFFIX | APAPERS | SPBPERS_NAME_SUFFIX |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|--|-------------|-------------------------------|
| A5.12 | Donor Nickname DONOR_NICK_NAME | APAPERS | APBCONS_NICKNAME |
| A5.13 | Donor Combined Mail Name DONOR_COMBINED_MAIL_NAME | APANAME | APBCONS_CM_NAME |
| A5.14 | Donor Birth/Maiden Name DONOR_BIRTH_MAIDEN_NAME | APANAME | APBCONS_MAIDEN_LAST_NAME |
| A5.15 | Donor Preferred Address Name DONOR_PREF_ADDRESS_NAME | APANAME | APBCONS_ADDR_NAME |
| A5.16 | Donor Preferred Address Type DONOR_PREF_ADDRESS_TYPE | APANAME | APBCONS_ATYP_CODE_PREF |
| A5.17 | Deceased Indicator DONOR_DECEASED_IND | APAPERS | SPBPERS_DEAD_IND |
| A5.18 | Date of Death DONOR_DECEASED_DATE | APAPERS | SPBPERS_DEAD_DATE |
| A5.19 | Donor Preferred College DONOR_PREF_COLL | APACONS | APBCONS_COLL_CODE_PREF |
| A5.20 | Donor Preferred Class DONOR_PREF_CLASS | APACONS | APBCONS_PREF_CLAS |
| Get the four most preferred Donor Category Codes using the ATVDONR_RPT_SEQ_IND field which sorts Donor Categories by preference. | | | |
| A5.21 | Preferred Donor Category Code DONOR_PREF_DONR_CODE | APACONS | ATVDONR_CODE |
| A5.22 | Preferred Donor Category Description DONOR_PREF_DONR_DESC | APACONS | ATVDONR_DESC |
| A5.23 | Pref. Donor Category Alumni Indicator DONOR_PREF_ALUM_IND | ATVDONR | ATVDONR_ALUM_IND |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|--|
| A5.24 | Other Donor Category Code 1 DONOR_OTHER_DONR_CODE_1 | APACONS | ATVDONR_CODE |
| A5.25 | Other Donor Category 1 Description DONOR_OTHER_DONR_DESC_1 | APACONS | ATVDONR_DESC |
| A5.26 | Other Donor Category Alumni Indicator 1 DONOR_OTHER_ALUM_IND_1 | ATVDONR | ATVDONR_ALUM_IND |
| A5.27 | Other Donor Category Code 2 DONOR_OTHER_DONR_CODE_2 | APACONS | ATVDONR_CODE |
| A5.28 | Other Donor Category 2 Description DONOR_OTHER_DONR_DESC_2 | APACONS | ATVDONR_DESC |
| A5.29 | Other Donor Category Alumni Indicator 2 DONOR_OTHER_ALUM_IND_2 | ATVDONR | ATVDONR_ALUM_IND |
| A5.30 | Other Donor Category Code 3 DONOR_OTHER_DONR_CODE_3 | APACONS | ATVDONR_CODE |
| A5.31 | Other Donor Category 3 Description DONOR_OTHER_DONR_DESC_3 | APACONS | ATVDONR_DESC |
| A5.32 | Other Donor Category Alumni Indicator 3 DONOR_OTHER_ALUM_IND_3 | ATVDONR | ATVDONR_ALUM_IND |
| A5.33 | Additional Donor Categories Flag DONOR_ADD_DONOR_CAT_FLAG | Function | F_CHECK_FOR_MORE If there are more than four donor categories, put a Y in this field. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|---|--|-------------|--|
| Select the spouse using the most recent From Date. | | | |
| Note: The table source of some spouse attributes depends on if the spouse has a PIDM. Multi-source attributes are denoted using a slash (/). The table name to the left of the slash indicates the source if the spouse <i>does not have a PIDM</i> or it may indicate a <i>Null</i> value. The table name to the right of the slash indicates the source if the spouse <i>has a PIDM</i> . In most cases, the field name is the same except for the table prefix. | | | |
| A5.34 | Spouse Personal ID Master SPOUSE_PIDM | APACONS | null/APRCSPS_SPS_PIDM |
| A5.35 | Spouse Last Name SPOUSE_LAST_NAME | APACONS | APRCSPS/SPRIDEN_LAST_NAME |
| A5.36 | Spouse First Name SPOUSE_FIRST_NAME | APACONS | APRCSPS/ SPRIDEN_FIRST_NAME |
| A5.37 | Spouse Birth/Maiden Name SPOUSE_BIRTH_MAIDEN_NAME | APACONS | APRCSPS_MAIDEN_NAME/ APBCONS_MAIDEN_LAST_NAME |
| A5.38 | Spouse Name Prefix SPOUSE_NAME_PREFIX | APACONS | APRCSPS/ SPBPERS_NAME_PREFIX |
| A5.39 | Spouse Name Suffix SPOUSE_NAME_SUFFIX | APACONS | APRCSPS/ SPBPERS_NAME_SUFFIX |
| A5.40 | Spouse Status SPOUSE_IND | APACONS | APRCSPS_MARS_IND |
| A5.41 | Spouse Deceased Indicator SPOUSE_DECEASED_IND | APACONS | APRCSPS/SPBPERS_DEAD_IND |
| A5.42 | Spouse Date of Death SPOUSE_DECEASED_DATE | APACONS | APRCSPS/SPBPERS_DEAD_DATE |
| A5.43 | Spouse Preferred College SPOUSE_PREF_COLL | APACONS | null/ APBCONS_COLL_CODE_PREF |
| A5.44 | Spouse Preferred Class Year SPOUSE_CLASS_YEAR | APACONS | null/APBCONS_PREF_CLAS |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|--|--------------------|---|
| A5.45 | Spouse Lost Alumnus Indicator SPOUSE_LOST_ALUMNUS_IND | Function | null/F_LOST_AL_IND If spouse has no active addresses (the TO_DATE passed on all addresses or all addresses on SPRADDR have an I (Inactive) status), put a Y in this field. |
| A5.46 | Spouse Primary Donor Category Code SPOUSE_PREF_DONR_CODE | APACONS | null/ATVDONR_CODE |
| A5.47 | Spouse Primary Donor Category Desc. SPOUSE_PREF_DONR_DESC | APACONS | null/ATVDONR_DESC |
| A5.48 | Spouse ID SPOUSE_ID | APACONS | null/SPRIDEN_ID |
| A5.49 | Spouse Surname Prefix SPOUSE_SURNAME_PREFIX | APACONS APRCSPS | SPRIDEN_SURNAME_PREFIX |
| <p>Select the six most recent years of gift and pledge information based on the Fiscal Year Code. Information for the current fiscal year is returned in the attributes with a suffix of “1”. The previous year’s information is returned in the attributes with a suffix of “2”, and so on.</p> | | | |
| A5.50 | Fiscal Year Code 1 FISC_CODE_1 | APAFHIS | F_FISC_CODE Select ATVFISC_CODE where the system date is between the START_DATE and END_DATE for the fiscal year. |
| A5.51 | Number of Gifts this Year 1 NUMBER_GIFT_YEAR_1 | AGCGIFT | F_NUMBER_GIFT_YEAR Count(AGBGIFT_GIFT_NO) and Count(AGRGMLT_GIFT_NO) for the Fiscal Year. |
| A5.52 | Total Giving this Year 1 TOTAL_GIVING_YEAR_1 | APAGHIS | F_TOTAL_GIVING_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) + Sum(APRCHIS_AMT_GIFT) for the fiscal year for the PIDM. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|---|
| A5.53 | Highest Gift Amount this Year 1 HIGHEST_GIFT_YEAR_1 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR Get the highest amount of either Max(AGBGIFT_AMT_TOT) or Max(AGRGMLT_AMT_TOT) for the Fiscal Year. |
| A5.54 | Date of Highest Gift Amount this Year 1 DATE_HIGHEST_GIFT_YEAR_1 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR AGBGIFT/AGRGMLT_GIFT_DATE for the AGBGIFT/AGRGMLT_GIFT_NO Get the date associated with above gift amount. |
| A5.55 | Total Anticipated Matching Gifts for Payments 1 TOTAL_ANT_MATCH_GIFT_PAY_1 | AGCGIFT | F_TOTAL_AMT_MAT_GIFT_PAY Sum(AGBMGID_AMT) for the fiscal year of AGBMGID_EMPL_GIFT_NO where gift is a payment. |
| A5.56 | Total Realized Matching Gifts for Payments 1 TOTAL_RLZ_MATCH_GIFT_PAY_1 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one time payment. |
| A5.57 | Total Anticipated Matching Gifts for One Time Payments 1 TOTAL_ANT_MATCH_GIFT_ONE_TIM_1 | AGCGIFT | F_TOTAL_ANT_MAT_GIFT_ONE_PAY Sum(AGBMGID_AMT) for the fiscal year of AGGBMGID_EMPL_GIFT_NO where the gift is a one time payment. |
| A5.58 | Total Realized Matching Gifts for One Time Payments 1 TOTAL_RLZ_MATCH_GIFT_ONE_TIM_1 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_ONE_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one time payment. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|--|
| A5.59 | Non-Matching Gift Memo Total 1 TOTAL_NON_MATCH_GIFT_MEMO_1 | AGCGIFT | F_TOTAL_NON_MAT_GIFT_MEMO Sum(AGRGMMO_CREDIT) where Donor's PIDM is AGRGMMO_XREF_PIDM for each fiscal year of AGRGMMO_GIFT_NO and AGRGMMO_GIFT_NO is not a matching gift, that is, not in AGRMGIF_EMPR_GIFT_NO. |
| A5.60 | Number of Pledges this Year 1 NUMBER_PLEDGE_YEAR_1 | AGCPLDG | F_NUMBER_PLEDGE_YEAR Count(AGBPLDG_PLEDGE_NO and AGRPMLT_PLEDGE_NO) for the Fiscal Year. |
| A5.61 | Total Pledged Amount this Year 1 TOTAL_PLEDGE_AMT_YEAR_1 | APAFHIS | F_TOTAL_PLEDGE_AMOUNT_YEAR Sum(APRCHIS_AMT_PLEDGED) for the Fiscal Year. |
| A5.62 | Highest Pledge Amount this Year 1 HIGHEST_PLEDGE_AMT_YEAR_1 | AGCPLDG | F_HIGH_PLEDGE_AMOUNT_YEAR Get the highest amount of either Max(AGBPLDG_AMT_PLEDGED) or Max(AGRPMLT_AMT_PLEDGED) for the Fiscal Year. |
| A5.63 | Total Pledge Payments this Year 1 TOTAL_PLEDGE_PAY_YEAR_1 | AGCGIFT | F_TOTAL_PLEDGE_PAYMENT_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) for the Fiscal Year. |
| A5.64 | Fiscal Year Code 2 FISC_CODE_2 | APAFHIS | F_FISC_CODE Select ATVFISC_CODE where the system date is between the START_DATE and END_DATE for the fiscal year. |
| A5.65 | Number of Gifts this Year 2 NUMBER_GIFT_YEAR_2 | AGCGIFT | F_NUMBER_GIFT_YEAR Count(AGBGIFT_GIFT_NO) and Count(AGRGMLT_GIFT_NO) for the Fiscal Year. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|---|
| A5.66 | Total Giving this Year 2 TOTAL_GIVING_YEAR_2 | APAGHIS | F_TOTAL_GIVING_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) + Sum(APRCHIS_AMT_GIFT) for the fiscal year for the PIDM. |
| A5.67 | Highest Gift Amount this Year 2 HIGHEST_GIFT_YEAR_2 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR Get the highest amount of either Max(AGBGIFT_AMT_TOT) or Max(AGRGMLT_AMT_TOT) for the Fiscal Year. |
| A5.68 | Date of Highest Gift Amount this Year 2 DATE_HIGHEST_GIFT_YEAR_2 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR AGBGIFT/AGRGMLT_GIFT_DATE for the AGBGIFT/AGRGMLT_GIFT_NO Get the date associated with above gift amount. |
| A5.69 | Total Anticipated Matching Gifts for Payments 2 TOTAL_ANT_MATCH_GIFT_PAY_2 | AGCGIFT | F_TOTAL_AMT_MAT_GIFT_PAY Sum(AGBMGID_AMT) for the fiscal year of AGBMGID_EMPL_GIFT_NO where gift is a payment. |
| A5.70 | Total Realized Matching Gifts for Payments 2 TOTAL_RLZ_MATCH_GIFT_PAY_2 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one time payment. |
| A5.71 | Total Anticipated Matching Gifts for One Time Payments 2 TOTAL_ANT_MATCH_GIFT_ONE_TIM_2 | AGCGIFT | F_TOTAL_ANT_MAT_GIFT_ONE_PAY Sum(AGBMGID_AMT) for the fiscal year of AGGBMGID_EMPL_GIFT_NO where the gift is a one-time payment. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|--|
| A5.72 | Total Realized Matching Gifts for One Time Payments 2 TOTAL_RLZ_MATCH_GIFT_ONE_TIM_2 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_ONE_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one-time payment. |
| A5.73 | Non-Matching Gift Memo Total 2 TOTAL_NON_MATCH_GIFT_MEMO_2 | AGCGIFT | F_TOTAL_NON_MAT_GIFT_MEMO Sum(AGRGMMO_CREDIT) where Donor's PIDM is AGRGMMO_XREF_PIDM for each fiscal year of AGRGMMO_GIFT_NO and AGRGMMO_GIFT_NO is not a matching gift, that is, not in AGRMGIF_EMPR_GIFT_NO. |
| A5.74 | Number of Pledges this Year 2 NUMBER_PLEDGE_YEAR_2 | AGCPLDG | F_NUMBER_PLEDGE_YEAR Count(AGBPLDG_PLEDGE_NO and AGRPMLT_PLEDGE_NO) for the Fiscal Year. |
| A5.75 | Total Pledged Amount this Year 2 TOTAL_PLEDGE_AMT_YEAR_2 | APAFHIS | F_TOTAL_PLEDGE_AMOUNT_YEAR Sum(APRCHIS_AMT_PLEDGED) for the Fiscal Year. |
| A5.76 | Highest Pledge Amount this Year 2 HIGHEST_PLEDGE_AMT_YEAR_2 | AGCPLDG | F_HIGH_PLEDGE_AMOUNT_YEAR Get the highest amount of either Max(AGBPLDG_AMT_PLEDGED) or Max(AGRPMLT_AMT_PLEDGED) for the Fiscal Year. |
| A5.77 | Total Pledge Payments this Year 2 TOTAL_PLEDGE_PAY_YEAR_2 | AGCGIFT | F_TOTAL_PLEDGE_PAYMENT_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) for the Fiscal Year. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|---|
| A5.78 | Fiscal Year Code 3 FISC_CODE_3 | APAFHIS | F_FISC_CODE Select ATVFISC_CODE where the system date is between the START_DATE and END_DATE for the fiscal year. |
| A5.79 | Number of Gifts this Year 3 NUMBER_GIFT_YEAR_3 | AGCGIFT | F_NUMBER_GIFT_YEAR Count(AGBGIFT_GIFT_NO) and Count(AGRGMLT_GIFT_NO) for the Fiscal Year. |
| A5.80 | Total Giving this Year 3 TOTAL_GIVING_YEAR_3 | APAGHIS | F_TOTAL_GIVING_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) + Sum(APRCHIS_AMT_GIFT) for the fiscal year for the PIDM. |
| A5.81 | Highest Gift Amount this Year 3 HIGHEST_GIFT_YEAR_3 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR Get the highest amount of Max(AGBGIFT_AMT_TOT) or Max(AGRGMLT_AMT_TOT) for the Fiscal Year. |
| A5.82 | Date of Highest Gift Amount this Year 3 DATE_HIGHEST_GIFT_YEAR_3 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR AGBGIFT/AGRGMLT_GIFT_DATE for the AGBGIFT/ AGRGMLT_GIFT_NO Get the date associated with preceding gift amount. |
| A5.83 | Total Anticipated Matching Gifts for Payments 3 TOTAL_ANT_MATCH_GIFT_PAY_3 | AGCGIFT | F_TOTAL_AMT_MAT_GIFT_PAY Sum(AGBMGID_AMT) for the fiscal year of AGBMGID_EMPL_GIFT_NO where gift is a payment. |
| A5.84 | Total Realized Matching Gifts for Payments 3 TOTAL_RLZ_MATCH_GIFT_PAY_3 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one-time payment. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|--|
| A5.85 | Total Anticipated Matching Gifts for One Time Payments 3 TOTAL_ANT_MATCH_GIFT_ONE_TIM_3 | AGCGIFT | F_TOTAL_ANT_MAT_GIFT_ONE_PAY Sum(AGBMGID_AMT) for the fiscal year of AGGBMGID_EMPL_GIFT_NO where the gift is a one-time payment. |
| A5.86 | Total Realized Matching Gifts for One Time Payments 3 TOTAL_RLZ_MATCH_GIFT_ONE_TIM_3 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_ONE_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one-time payment. |
| A5.87 | Non-Matching Gift Memo Total 3 TOTAL_NON_MATCH_GIFT_MEMO_3 | AGCGIFT | F_TOTAL_NON_MAT_GIFT_MEMO Sum(AGRGMMO_CREDIT) where Donor's PIDM is AGRGMMO_XREF_PIDM for each fiscal year of AGRGMMO_GIFT_NO and AGRGMMO_GIFT_NO is not a matching gift, that is, not in AGRMGIF_EMPR_GIFT_NO. |
| A5.88 | Number of Pledges this Year 3 NUMBER_PLEDGE_YEAR_3 | AGCPLDG | F_NUMBER_PLEDGE_YEAR Count(AGBPLDG_PLEDGE_NO and AGRPMLT_PLEDGE_NO) for the Fiscal Year. |
| A5.89 | Total Pledged Amount this Year 3 TOTAL_PLEDGE_AMT_YEAR_3 | APAFHIS | F_TOTAL_PLEDGE_AMOUNT_YEAR Sum(APRCHIS_AMT_PLEDGED) for the Fiscal Year. |
| A5.90 | Highest Pledge Amount this Year 3 HIGHEST_PLEDGE_AMT_YEAR_3 | AGCPLDG | F_HIGH_PLEDGE_AMOUNT_YEAR Get the highest amount of Max(AGBPLDG_AMT_PLEDGED) or Max(AGRPMLT_AMT_PLEDGED) for the Fiscal Year. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|---|
| A5.91 | Total Pledge Payments this Year 3 TOTAL_PLEDGE_PAY_YEAR_3 | AGCGIFT | F_TOTAL_PLEDGE_PAYMENT_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) for the Fiscal Year. |
| A5.92 | Fiscal Year Code 4 FISC_CODE_4 | APAFHIS | F_FISC_CODE Select ATVFISC_CODE where the system date is between the START_DATE and END_DATE for the fiscal year. |
| A5.93 | Number of Gifts this Year 4 NUMBER_GIFT_YEAR_4 | AGCGIFT | F_NUMBER_GIFT_YEAR Count(AGBGIFT_GIFT_NO) and Count(AGRGMLT_GIFT_NO) for the Fiscal Year. |
| A5.94 | Total Giving this Year 4 TOTAL_GIVING_YEAR_4 | APAGHIS | F_TOTAL_GIVING_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) + Sum(APRCHIS_AMT_GIFT) for the fiscal year for the PIDM. |
| A5.95 | Highest Gift Amount this Year 4 HIGHEST_GIFT_YEAR_4 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR Get the highest amount of Max(AGBGIFT_AMT_TOT) or Max(AGRGMLT_AMT_TOT) for the Fiscal Year. |
| A5.96 | Date of Highest Gift Amount this Year 4 DATE_HIGHEST_GIFT_YEAR_4 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR AGBGIFT/AGRGMLT_GIFT_DATE for the AGBGIFT/AGRGMLT_GIFT_NO Get the date associated with above gift amount. |
| A5.97 | Total Anticipated Matching Gifts for Payments 4 TOTAL_ANT_MATCH_GIFT_PAY_4 | AGCGIFT | F_TOTAL_AMT_MAT_GIFT_PAY Sum(AGBMGID_AMT) for the fiscal year AGBMGID_EMPL_GIFT_NO where gift is a payment. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|---|
| A5.98 | Total Realized Matching Gifts for Payments 4 TOTAL_RLZ_MATCH_GIFT_PAY_4 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one-time payment. |
| A5.99 | Total Anticipated Matching Gifts for One Time Payments 4 TOTAL_ANT_MATCH_GIFT_ONE_TIM_4 | AGCGIFT | F_TOTAL_ANT_MAT_GIFT_ONE_PAY Sum(AGBMGID_AMT) for the fiscal year AGGBMGID_EMPL_GIFT_NO where the gift is a one-time payment. |
| A5.100 | Total Realized Matching Gifts for One Time Payments 4 TOTAL_RLZ_MATCH_GIFT_ONE_TIM_4 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_ONE_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one-time payment. |
| A5.101 | Non-Matching Gift Memo Total 4 TOTAL_NON_MATCH_GIFT_MEMO_4 | AGCGIFT | F_TOTAL_NON_MAT_GIFT_MEMO Sum(AGRGMMO_CREDIT) where Donor's PIDM is AGRGMMO_XREF_PIDM for each fiscal year of AGRGMMO_GIFT_NO and AGRGMMO_GIFT_NO is not a matching gift, i.e., not in AGRMGIF_EMPR_GIFT_NO. |
| A5.102 | Number of Pledges this Year 4 NUMBER_PLEDGE_YEAR_4 | AGCPLDG | F_NUMBER_PLEDGE_YEAR Count(AGBPLDG_PLEDGE_NO and AGRPMLT_PLEDGE_NO) for the Fiscal Year. |
| A5.103 | Total Pledged Amount this Year 4 TOTAL_PLEDGE_AMT_YEAR_4 | APAFHIS | F_TOTAL_PLEDGE_AMOUNT_YEAR Sum(APRCHIS_AMT_PLEDGED) for the Fiscal Year. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|---|
| A5.104 | Highest Pledge Amount this Year 4 HIGHEST_PLEDGE_AMT_YEAR_4 | AGCPLDG | F_HIGH_PLEDGE_AMOUNT_YEAR Get the highest amount of Max(AGBPLDG_AMT_PLEDGED) or Max(AGRPMLT_AMT_PLEDGED) for the Fiscal Year. |
| A5.105 | Total Pledge Payments this Year 4 TOTAL_PLEDGE_PAY_YEAR_4 | AGCGIFT | F_TOTAL_PLEDGE_PAYMENT_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) for the Fiscal Year. |
| A5.106 | Fiscal Year Code 5 FISC_CODE_5 | APAFHIS | F_FISC_CODE Select ATVFISC_CODE where the system date is between the START_DATE and END_DATE for the fiscal year. |
| A5.107 | Number of Gifts this Year 5 NUMBER_GIFT_YEAR_5 | AGCGIFT | F_NUMBER_GIFT_YEAR Count(AGBGIFT_GIFT_NO) and Count(AGRGMLT_GIFT_NO) for the Fiscal Year. |
| A5.108 | Total Giving this Year 5 TOTAL_GIVING_YEAR_5 | APAGHIS | F_TOTAL_GIVING_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) + Sum(APRCHIS_AMT_GIFT) for the fiscal year for the PIDM. |
| A5.109 | Highest Gift Amount this Year 5 HIGHEST_GIFT_YEAR_5 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR Get the highest amount of Max(AGBGIFT_AMT_TOT) or Max(AGRGMLT_AMT_TOT) for the Fiscal Year. |
| A5.110 | Date of Highest Gift Amount this Year 5 DATE_HIGHEST_GIFT_YEAR_5 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR AGBGIFT/AGRGMLT_GIFT_DATE for the AGBGIFT/AGRGMLT_GIFT_NO Get the date associated with above gift amount. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|---|
| A5.111 | Total Anticipated Matching Gifts for Payments 5 TOTAL_ANT_MATCH_GIFT_PAY_5 | AGCGIFT | F_TOTAL_AMT_MAT_GIFT_PAY Sum(AGBMGID_AMT) for the fiscal year of AGBMGID_EMPL_GIFT_NO where gift is a payment. |
| A5.112 | Total Realized Matching Gifts for Payments 5 TOTAL_RLZ_MATCH_GIFT_PAY_5 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one-time payment. |
| A5.113 | Total Anticipated Matching Gifts for One Time Payments 5 TOTAL_ANT_MATCH_GIFT_ONE_TIM_5 | AGCGIFT | F_TOTAL_ANT_MAT_GIFT_ONE_PAY Sum(AGBMGID_AMT) for the fiscal year of AGGBMGID_EMPL_GIFT_NO where the gift is a one-time payment. |
| A5.114 | Total Realized Matching Gifts for One Time Payments 5 TOTAL_RLZ_MATCH_GIFT_ONE_TIM_5 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_ONE_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one-time payment. |
| A5.115 | Non-Matching Gift Memo Total 5 TOTAL_NON_MATCH_GIFT_MEMO_5 | AGCGIFT | F_TOTAL_NON_MAT_GIFT_MEMO Sum(AGRGMMO_CREDIT) where Donor's PIDM is AGRGMMO_XREF_PIDM for each fiscal year of AGRGMMO_GIFT_NO and AGRGMMO_GIFT_NO is not a matching gift, i.e., not in AGRMGIF_EMPR_GIFT_NO. |
| A5.116 | Number of Pledges this Year 5 NUMBER_PLEDGE_YEAR_5 | AGCPLDG | F_NUMBER_PLEDGE_YEAR Count(AGBPLDG_PLEDGE_NO and AGRPMLT_PLEDGE_NO) for the Fiscal Year. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|---|
| A5.117 | Total Pledged Amount this Year 5 TOTAL_PLEDGE_AMT_YEAR_5 | APAFHIS | F_TOTAL_PLEDGE_AMOUNT_YEAR Sum(APRCHIS_AMT_PLEDGED) for the Fiscal Year. |
| A5.118 | Highest Pledge Amount this Year 5 HIGHEST_PLEDGE_AMT_YEAR_5 | AGCPLDG | F_HIGH_PLEDGE_AMOUNT_YEAR Get the highest amount of Max(AGBPLDG_AMT_PLEDGED) or Max(AGRPMLT_AMT_PLEDGED) for the Fiscal Year. |
| A5.119 | Total Pledge Payments this Year 5 TOTAL_PLEDGE_PAY_YEAR_5 | AGCGIFT | F_TOTAL_PLEDGE_PAYMENT_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) for the Fiscal Year. |
| A5.120 | Fiscal Year Code 6 FISC_CODE_6 | APAFHIS | F_FISC_CODE Select ATVFISC_CODE where the system date is between the START_DATE and END_DATE for the fiscal year. |
| A5.121 | Number of Gifts this Year 6 NUMBER_GIFT_YEAR_6 | AGCGIFT | F_NUMBER_GIFT_YEAR Count(AGBGIFT_GIFT_NO) and Count(AGRGMLT_GIFT_NO) for the Fiscal Year. |
| A5.122 | Total Giving this Year 6 TOTAL_GIVING_YEAR_6 | APAGHIS | F_TOTAL_GIVING_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) + Sum(APRCHIS_AMT_GIFT) for the fiscal year for the PIDM. |
| A5.123 | Highest Gift Amount this Year 6 HIGHEST_GIFT_YEAR_6 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR Get the highest amount of Max(AGBGIFT_AMT_TOT) or Max(AGRGMLT_AMT_TOT) for the Fiscal Year. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|--|
| A5.124 | Date of Highest Gift Amount this Year 6 DATE_HIGHEST_GIFT_YEAR_6 | AGCGIFT | F_HIGH_GIFT_AMOUNT_YEAR AGBGIFT/AGRGMLT_GIFT_DATE for the AGBGIFT/ AGRGMLT_GIFT_NO Get the date associated with above gift amount. |
| A5.125 | Total Anticipated Matching Gifts for Payments 6 TOTAL_ANT_MATCH_GIFT_PAY_6 | AGCGIFT | F_TOTAL_AMT_MAT_GIFT_PAY Sum(AGBMGID_AMT) for the fiscal year of AGBMGID_EMPL_GIFT_NO where gift is a payment. |
| A5.126 | Total Realized Matching Gifts for Payments 6 TOTAL_RLZ_MATCH_GIFT_PAY_6 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one-time payment. |
| A5.127 | Total Anticipated Matching Gifts for One Time Payments 6 TOTAL_ANT_MATCH_GIFT_ONE_TIM_6 | AGCGIFT | F_TOTAL_ANT_MAT_GIFT_ONE_PAY Sum(AGBMGID_AMT) for the fiscal year of AGGBMGID_EMPL_GIFT_NO where the gift is a one-time payment. |
| A5.128 | Total Realized Matching Gifts for One Time Payments 6 TOTAL_RLZ_MATCH_GIFT_ONE_TIM_6 | AGCGIFT | F_TOTAL_RLZ_MAT_GIFT_ONE_PAY Sum(AGVGMEM_CREDIT) for the fiscal year of AGRMGIF_EMPR_GIFT_NO where the gift is a one-time payment. |
| A5.129 | Non-Matching Gift Memo Total 6 TOTAL_NON_MATCH_GIFT_MEMO_6 | AGCGIFT | F_TOTAL_NON_MAT_GIFT_MEMO Sum(AGRGMMO_CREDIT) where Donor's PIDM is AGRGMMO_XREF_PIDM for each fiscal year of AGRGMMO_GIFT_NO and AGRGMMO_GIFT_NO is not a matching gift, that is, not in AGRMGIF_EMPR_GIFT_NO. |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|--|--|-------------|--|
| A5.130 | Number of Pledges this Year 6 NUMBER_PLEDGE_YEAR_6 | AGCPLDG | F_NUMBER_PLEDGE_YEAR Count(AGBPLDG_PLEDGE_NO and AGRPMLT_PLEDGE_NO) for the Fiscal Year. |
| A5.131 | Total Pledged Amount this Year 6 TOTAL_PLEDGE_AMT_YEAR_6 | APAFHIS | F_TOTAL_PLEDGE_AMOUNT_YEAR Sum(APRCHIS_AMT_PLEDGED) for the Fiscal Year. |
| A5.132 | Highest Pledge Amount this Year 6 HIGHEST_PLEDGE_AMT_YEAR_6 | AGCPLDG | F_HIGH_PLEDGE_AMOUNT_YEAR Get the highest amount of Max(AGBPLDG_AMT_PLEDGED) or Max(AGRPMLT_AMT_PLEDGED) for the Fiscal Year. |
| A5.133 | Total Pledge Payments this Year 6 TOTAL_PLEDGE_PAY_YEAR_6 | AGCGIFT | F_TOTAL_PLEDGE_PAYMENT_YEAR Sum(APRCHIS_AMT_PLEDGED_PAID) for the Fiscal Year. |
| <p>Select two Gift Society Types for each of the six fiscal years of information using the logic defined for the Gift Society Type concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMDCST</i> and Internal Group = <i>GIFT SOCIETY</i>.</p> <p>Note: If a donor did not pledge or give in any of the six pledge years, a record containing zeroes is returned.</p> | | | |
| A5.134 | Gift Society Type 1 Year 1 DCST_CODE_1_1 | APADCLB | ATVDCST_CODE |
| A5.135 | Gift Society Type Description 1 Year 1 DCST_DESC_1_1 | APADCLB | ATVDCST_DESC |
| A5.136 | Gift Society Code 1 Year 1 DCNP_CODE_1_1 | APADCLB | APRDCLB_DCNP_CODE |
| A5.137 | Gift Society Name 1 Year 1 DCNP_DESC_1_1 | APADCLB | ATVDCNP_DESC |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|-----------------|---|--------------------|--------------------------------------|
| A5.138 | Gift Society Type 2 Year 1 DCST_CODE_2_1 | APADCLB | ATVDCST_CODE |
| A5.139 | Gift Society Type Description 2 Year 1 DCST_DESC_2_1 | APADCLB | ATVDCST_DESC |
| A5.140 | Gift Society Code 2 Year 1 DCNP_CODE_2_1 | APADCLB | APRDCLB_DCNP_CODE |
| A5.141 | Gift Society Name 2 Year 1 DCNP_DESC_2_1 | APADCLB | ATVDCNP_DESC |
| A5.142 | Gift Society Type 1 Year 2 DCST_CODE_1_2 | APADCLB | ATVDCST_CODE |
| A5.143 | Gift Society Type Description 1 Year 2 DCST_DESC_1_2 | APADCLB | ATVDCST_DESC |
| A5.144 | Gift Society Code 1 Year 2 DCNP_CODE_1_2 | APADCLB | APRDCLB_DCNP_CODE |
| A5.145 | Gift Society Name 1 Year 2 DCNP_DESC_1_2 | APADCLB | ATVDCNP_DESC |
| A5.146 | Gift Society Type 2 Year 2 DCST_CODE_2_2 | APADCLB | ATVDCST_CODE |
| A5.147 | Gift Society Type Description 2 Year 2 DCST_DESC_2_2 | APADCLB | ATVDCST_DESC |
| A5.148 | Gift Society Code 2 Year 2 DCNP_CODE_2_2 | APADCLB | APRDCLB_DCNP_CODE |
| A5.149 | Gift Society Name 2 Year 2 DCNP_DESC_2_2 | APADCLB | ATVDCNP_DESC |
| A5.150 | Gift Society Type 1 Year 3 DCST_CODE_1_3 | APADCLB | ATVDCST_CODE |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|-----------------|---|--------------------|--------------------------------------|
| A5.151 | Gift Society Type Description 1 Year 3 DCST_DESC_1_3 | APADCLB | ATVDCST_DESC |
| A5.152 | Gift Society Code 1 Year 3 DCNP_CODE_1_3 | APADCLB | APRDCLB_DCNP_CODE |
| A5.153 | Gift Society Name 1 Year 3 DCNP_DESC_1_3 | APADCLB | ATVDCNP_DESC |
| A5.154 | Gift Society Type 2 Year 3 DCST_CODE_2_3 | APADCLB | ATVDCST_CODE |
| A5.155 | Gift Society Type Description 2 Year 3 DCST_DESC_2_3 | APADCLB | ATVDCST_DESC |
| A5.156 | Gift Society Code 2 Year 3 DCNP_CODE_2_3 | APADCLB | APRDCLB_DCNP_CODE |
| A5.157 | Gift Society Name 2 Year 3 DCNP_DESC_2_3 | APADCLB | ATVDCNP_DESC |
| A5.158 | Gift Society Type 1 Year 4 DCST_CODE_1_4 | APADCLB | ATVDCST_CODE |
| A5.159 | Gift Society Type Description 1 Year 4 DCST_DESC_1_4 | APADCLB | ATVDCST_DESC |
| A5.160 | Gift Society Code 1 Year 4 DCNP_CODE_1_4 | APADCLB | APRDCLB_DCNP_CODE |
| A5.161 | Gift Society Name 1 Year 4 DCNP_DESC_1_4 | APADCLB | ATVDCNP_DESC |
| A5.162 | Gift Society Type 2 Year 4 DCST_CODE_2_4 | APADCLB | ATVDCST_CODE |
| A5.163 | Gift Society Type Description 2 Year 4 DCST_DESC_2_4 | APADCLB | ATVDCST_DESC |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|-------------------------------|
| A5.164 | Gift Society Code 2 Year 4 DCNP_CODE_2_4 | APADCLB | APRDCLB_DCNP_CODE |
| A5.165 | Gift Society Name 2 Year 4 DCNP_DESC_2_4 | APADCLB | ATVDCNP_DESC |
| A5.166 | Gift Society Type 1 Year 5 DCST_CODE_1_5 | APADCLB | ATVDCST_CODE |
| A5.167 | Gift Society Type Description 1 Year 5 DCST_DESC_1_5 | APADCLB | ATVDCST_DESC |
| A5.168 | Gift Society Code 1 Year 5 DCNP_CODE_1_5 | APADCLB | APRDCLB_DCNP_CODE |
| A5.169 | Gift Society Name 1 Year 5 DCNP_DESC_1_5 | APADCLB | ATVDCNP_DESC |
| A5.170 | Gift Society Type 2 Year 5 DCST_CODE_2_5 | APADCLB | ATVDCST_CODE |
| A5.171 | Gift Society Type Description 2 Year 5 DCST_DESC_2_5 | APADCLB | ATVDCST_DESC |
| A5.172 | Gift Society Code 2 Year 5 DCNP_CODE_2_5 | APADCLB | APRDCLB_DCNP_CODE |
| A5.173 | Gift Society Name 2 Year 5 DCNP_DESC_2_5 | APADCLB | ATVDCNP_DESC |
| A5.174 | Gift Society Type 1 Year 6 DCST_CODE_1_6 | APADCLB | ATVDCST_CODE |
| A5.175 | Gift Society Type Description 1 Year 6 DCST_DESC_1_6 | APADCLB | ATVDCST_DESC |
| A5.176 | Gift Society Code 1 Year 6 DCNP_CODE_1_6 | APADCLB | APRDCLB_DCNP_CODE |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|---|-------------|---|
| A5.177 | Gift Society Name 1 Year 6 DCNP_DESC_1_6 | APADCLB | ATVDCNP_DESC |
| A5.178 | Gift Society Type 2 Year 6 DCST_CODE_2_6 | APADCLB | ATVDCST_CODE |
| A5.179 | Gift Society Type Description 2 Year 6 DCST_DESC_2_6 | APADCLB | ATVDCST_DESC |
| A5.180 | Gift Society Code 2 Year 6 DCNP_CODE_2_6 | APADCLB | APRDCLB_DCNP_CODE |
| A5.181 | Gift Society Name 2 Year 6 DCNP_DESC_2_6 | APADCLB | ATVDCNP_DESC |
| A5.182 | Lifetime Total Giving LIFE_TOTAL_GIVING | Function | F_LIFE_TOTAL_GIVING Sum(AGVFGIV_GIVING) |
| A5.183 | Most Recent Gift Date MOST_RECENT_GIFT_DATE | Function | F_MOST_RECENT_GIFT_DATE Max(AGVGCRD_GIFT_DATE) |
| A5.184 | Most Recent Gift Amount MOST_RECENT_GIFT_AMT | Function | F_MOST_RECENT_GIFT_AMOUNT AGVGCRD_GIFT_AMT associated with the Most Recent Gift Date |
| A5.185 | Lifetime Total Pledged Amount LIFE_TOTAL_PLEDGE_AMT | Function | F_LIFE_TOTAL_PLEDGE_AMOUNT Sum(APRCHIS_AMT_PLEDGED) |
| A5.186 | Most Recent Pledge Date MOST_RECENT_PLEDGE_DATE | Function | F_MOST_RECENT_PLEDGE_DATE Max(AGVPCRD_PLEDGE_DATE) |
| A5.187 | Most Recent Pledge Amount MOST_RECENT_PLEDGE_AMT | Function | F_MOST_RECENT_PLEDGE_AMOUNT AGVPCRD_AMOUNT associated with the Most Recent Pledge Date |

Table 5: Giving View Attributes (cont)

| Ref. No. | Attribute | Source Form | Source Field or Function Name |
|----------|--|-------------|--|
| A5.188 | Lifetime Total Pledge Payments LIFE_TOTAL_PLEDGE_PAY | Function | F_LIFE_TOTAL_PLEDGE_PAYME NT Sum(APRCHIS_AMT_PLEDGED_ PAID) |
| A5.189 | Lifetime Gift Society Type LIFE_DCST_CODE | APADCLB | ATVDCST_CODE |
| A5.190 | Lifetime Gift Society Type Description LIFE_DCST_DESC | APADCLB | ATVDCST_desc |
| A5.191 | Lifetime Gift Society Code LIFE_DCNP_CODE | APADCLB | APRDCLB_DCNP_CODE |
| A5.192 | Lifetime Gift Society Description LIFE_DCNP_DESC | APADCLB | ATVDCNP_desc |
| A5.193 | Lifetime Total Commitments LIFE_TOTAL_COMMITMENT | Function | F_LIFE_TOTAL_COMMITMENT Sum(APRCHIS_AMT_PLEDGED) + Sum(APRCHIS_AMT_GIFT) |

View 6: Organization

AA_ORGANIZATION

If you are using FOCUS, the view name is AOVORG0.

The Organization view lets you report the most used information about organizations. This view contains information about organizations not in the Constituent/Organization Shared view, including the organization's name, addresses, phone numbers, donor categories, contacts, funding, and matching gifts.



Tip

Use this view by itself or join it to the [“Constituent/Organization Shared”](#) view for a more complete picture of organizations. ■

This view accesses the following main database tables.

- AOBORGN Organization Base Table
- AORCONT Organization Contact Repeating Table
- AORFUND Organization Fund Table
- SPRADDR Address Repeating Table
- SPRIDEN Person Identification/Name Repeating Table
- SPRTELE Telephone Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) chapter for a complete description of PIDM. ■

The key attribute of this view is:

- Organization Personal ID MasterPIDM_KEY

Because the PIDM is an internal ID unique to each organization, the view returns one row of information for each organization.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view, but you may find it useful to specify criteria for some or all of the following attributes. Specifying these criteria selects the population for a report and may reduce the time it takes to run the report.

- Preferred Donor Category Code PREF_DONR_CODE

- Secondary Contact Type Codes 1-2 SEC_CONTACT_OCON_CODE_1
SEC_CONTACT_OCON_CODE_2
- Funding Interests Codes 1-3 FUND_CODE_1
FUND_CODE_2
FUND_CODE_3

Attributes

The following list specifies the attributes included in the Organization view. The list also indicates the primary form and the database field or function that is the source for each attribute.

Table 6: Organization View Attributes

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|---|
| A6.1 | Organization Personal ID Master Key PIDM_KEY | APAIDEN | AOBORGN_PIDM |
| A6.2 | Donor Indicator ORGN_DONOR_IND | Function | F_DONOR_IND If there is a record in APRCHIS, put a Y in this field. |
| A6.3 | Prospect Indicator ORGN_PROSPECT_IND | Function | F_PROSPECT_IND If there is a record in AMRINFO, put a Y in this field. |
| A6.4 | Organization ID ORGN_ID_NUMBER | APAIDEN | SPRIDEN_ID |
| A6.5 | Organization Name ORGN_NAME | APAIDEN | SPRIDEN_LAST_NAME |
| A6.6 | Organization Industry Code SICC_CODE | AOAORGN | AOBORGN_SICC_CODE |
| A6.7 | Organization Industry Description SICC_DESC | AOAORGN | ATVSICC_DESC |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|-------------------------------|
| | <p>Select two Addresses and related information using the hierarchy defined for the Address Type (Advancement) concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMADDR</i> and Internal Group = <i>ADDRESS</i>.</p> <p>Note: Be sure to refer to the correct Address Type concept, because there is more than one.</p> | | |
| A6.8 | Organization Address Type Code 1 ATYP_CODE_1 | APAIDEN | SPRADDR_ATYP_CODE |
| A6.9 | Organization Address Type Desc. 1 ATYP_DESC_1 | APAIDEN | ATVATYP_DESC |
| A6.10 | Organization Address 1 House Number HOUSE_NUMBER_1 | APAIDEN | SPRADDR_HOUSE_NUMBER |
| A6.11 | Organization Address 1 Street Line 1 STREET_LINE1_1 | APAIDEN | SPRADDR_STREET_LINE1 |
| A6.12 | Organization Address 1 Street Line 2 STREET_LINE2_1 | APAIDEN | SPRADDR_STREET_LINE2 |
| A6.13 | Organization Address 1 Street Line 3 STREET_LINE3_1 | APAIDEN | SPRADDR_STREET_LINE3 |
| A6.14 | Organization Address 1 Street Line 4 STREET_LINE4_1 | APAIDEN | SPRADDR_STREET_LINE4 |
| A6.15 | Organization City 1 CITY_1 | APAIDEN | SPRADDR_CITY |
| A6.16 | Organization State 1 STAT_CODE_1 | APAIDEN | SPRADDR_STAT_CODE |
| A6.17 | Organization Zip Code 1 ZIP_1 | APAIDEN | SPRADDR_ZIP |
| A6.18 | Organization County Code 1 CNTY_CODE_1 | APAIDEN | SPRADDR_CNTY_CODE |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|---|-----------|-------------------------------|
| A6.19 | Organization County Description 1 CNTY_DESC_1 | APAIDEN | STVCNTY_DESC |
| A6.20 | Organization Nation Code 1 NATN_CODE_1 | APAIDEN | SPRADDR_NATN_CODE |
| A6.21 | Organization Nation Description 1 NATN_DESC_1 | APAIDEN | STVNATN_NATION |
| <p>Select the Geographic Region and related information using the hierarchy defined for the Geographic Region concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMGEOD</i> and Internal Group = <i>GEOR REGION</i>.</p> | | | |
| A6.22 | Organization Geographic Region Code 1 GEOR_CODE_1 | SOAIGEO | SOVGEOR_GEO_CODE |
| A6.23 | Organization Geo. Region Desc. 1 GEOR_DESC_1 | SOAIGEO | STVGEOR_DESC |
| A6.24 | Organization Delivery Point 1 DELIVERY_POINT_1 | APAIDEN | SPRADDR_DELIVERY_POINT |
| A6.25 | Organization Correction Digit 1 CORRECTION_DIGIT_1 | APAIDEN | SPRADDR_CORRECTION_DIGIT |
| A6.26 | Organization Carrier Route 1 CARRIER_ROUTE_1 | APAIDEN | SPRADDR_CARRIER_ROUTE |
| A6.27 | Organization Address Start Date 1 ADDR_START_DATE_1 | APAIDEN | SPRADDR_FROM_DATE |
| A6.28 | Organization Address End Date 1 ADDR_END_DATE_1 | APAIDEN | SPRADDR_TO_DATE |
| A6.29 | Organization Add. Status Indicator 1 ADDR_STATUS_IND_1 | APAIDEN | SPRADDR_STATUS_IND |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|---|-----------|---|
| <p>Note: If the phone number is unlisted (SPRTELE_UNLIST_IND = Y), asterisks (**) are returned in place of the actual phone numbers.</p> | | | |
| A6.30 | Organization Primary Phone Number 1 ADDR_PHONE_NUMBER_1 | APAIDEN | SPRTELE_PHONE_NUMBER Note: Need to get SEQNO, ATYP_CODE, and PRIMARY_IND to get primary phone number. |
| A6.31 | Organization Primary Phone Area Code 1 ADDR_PHONE_AREA_CODE_1 | APAIDEN | SPRTELE_PHONE_AREA |
| A6.32 | Organization Primary Phone Extension 1 ADDR_PHONE_EXT_1 | APAIDEN | SPRTELE_PHONE_EXT |
| A6.33 | Organization Primary Phone Country Code 1 ADDR_CTRY_CODE_PHONE_1 | APAIDEN | SPRTELE_CTRY_CODE_PHONE |
| A6.34 | Organization Address Type Code 2 ATYP_CODE_2 | APAIDEN | SPRADDR_ATYP_CODE |
| A6.35 | Organization Address Type Desc. 2 ATYP_DESC_2 | APAIDEN | ATVATYP_DESC |
| A6.36 | Organization Address 2 House Number HOUSE_NUMBER_2 | APAIDEN | SPRADDR_HOUSE_NUMBER |
| A6.37 | Organization Address 2 Street Line 1 STREET_LINE1_2 | APAIDEN | SPRADDR_STREET_LINE1 |
| A6.38 | Organization Address 2 Street Line 2 STREET_LINE2_2 | APAIDEN | SPRADDR_STREET_LINE2 |
| A6.39 | Organization Address 2 Street Line 3 STREET_LINE3_2 | APAIDEN | SPRADDR_STREET_LINE3 |
| A6.40 | Organization Address 2 Street Line 4 STREET_LINE4_2 | APAIDEN | SPRADDR_STREET_LINE4 |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|---|-----------|-------------------------------|
| A6.41 | Organization City 2 CITY_2 | APAIDEN | SPRADDR_CITY |
| A6.42 | Organization State 2 STAT_CODE_2 | APAIDEN | SPRADDR_STAT_CODE |
| A6.43 | Organization Zip Code 2 ZIP_2 | APAIDEN | SPRADDR_ZIP |
| A6.44 | Organization County Code 2 CNTY_CODE_2 | APAIDEN | SPRADDR_CNTY_CODE |
| A6.45 | Organization County Description 2 CNTY_DESC_2 | APAIDEN | STVCNTY_DESC |
| A6.46 | Organization Nation Code 2 NATN_CODE_2 | APAIDEN | SPRADDR_NATN_CODE |
| A6.47 | Organization Nation Description 2 NATN_DESC_2 | APAIDEN | STVNATN_NATION |
| <p>Select the Geographic Region and related information using the hierarchy defined for the Geographic Region concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMGEOD</i> and Internal Group = <i>GEOR REGION</i>.</p> | | | |
| A6.48 | Organization Geographic Region Code 2 GEOR_CODE_2 | SOAIGEO | SOVGEOR_GEOR_CODE |
| A6.49 | Organization Geo. Region Desc. 2 GEOR_DESC_2 | SOAIGEO | STVGEOR_DESC |
| A6.50 | Organization Delivery Point 2 DELIVERY_POINT_2 | APAIDEN | SPRADDR_DELIVERY_POINT |
| A6.51 | Organization Correction Digit 2 CORRECTION_DIGIT_2 | APAIDEN | SPRADDR_CORRECTION_DIGIT |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|---|-----------|---|
| A6.52 | Organization Carrier Route 2 CARRIER_ROUTE_2 | APAIDEN | SPRADDR_CARRIER_ROUTE |
| A6.53 | Organization Address Start Date 2 ADDR_START_DATE_2 | APAIDEN | SPRADDR_FROM_DATE |
| A6.54 | Organization Address End Date 2 ADDR_END_DATE_2 | APAIDEN | SPRADDR_TO_DATE |
| A6.55 | Organization Add. Status Indicator 2 ADDR_STATUS_IND_2 | APAIDEN | SPRADDR_STATUS_IND |
| <p>Note: If the phone number is unlisted (SPRTELE_UNLIST_IND = Y), asterisks (**) are returned in place of the actual phone numbers.</p> | | | |
| A6.56 | Organization Primary Phone Number 2 ADDR_PHONE_NUMBER_2 | APAIDEN | SPRTELE_PHONE_NUMBER Note: Need to get SEQNO, ATYP_CODE, and PRIMARY_IND to get primary phone number. |
| A6.57 | Organization Primary Phone Area Code 2 ADDR_PHONE_AREA_CODE_2 | APAIDEN | SPRTELE_PHONE_AREA |
| A6.58 | Organization Primary Phone Extension 2 ADDR_PHONE_EXT_2 | APAIDEN | SPRTELE_PHONE_EXT |
| A6.59 | Organization Primary Phone Country Code 2 ADDR_CTRY_CODE_PHONE_2 | APAIDEN | SPRTELE_CTRY_CODE_PHONE |
| <p>Select three additional Phone Numbers using the hierarchy defined for the Telephone Code (Additional) concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = ALUMPHONE and Internal Group = TELEPHONE.</p> | | | |
| A6.60 | Other Phone Type Code 1 TELE_CODE_1 | APAIDEN | SPRTELE_TELE_CODE |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|-------------------------------|
| A6.61 | Other Phone Type Description 1 TELE_DESC_1 | APAIDEN | STVTELE_DESC |
| A6.62 | Other Phone Number 1 PHONE_NUMBER_1 | APAIDEN | SPRTELE_PHONE_NUMBER |
| A6.63 | Other Phone Area Code 1 PHONE_AREA_CODE_1 | APAIDEN | SPRTELE_PHONE_AREA |
| A6.64 | Other Phone Extension 1 PHONE_EXT_1 | APAIDEN | SPRTELE_PHONE_EXT |
| A6.65 | Other Phone Country Code 1 CTRY_CODE_PHONE_1 | APAIDEN | SPRTELE_CTRY_CODE_PHONE |
| A6.66 | Other Phone Type Code 2 TELE_CODE_2 | APAIDEN | SPRTELE_TELE_CODE |
| A6.67 | Other Phone Type Description 2 TELE_DESC_2 | APAIDEN | STVTELE_DESC |
| A6.68 | Other Phone Number 2 PHONE_NUMBER_2 | APAIDEN | SPRTELE_PHONE_NUMBER |
| A6.69 | Other Phone Area Code 2 PHONE_AREA_CODE_2 | APAIDEN | SPRTELE_PHONE_AREA |
| A6.70 | Other Phone Extension 2 PHONE_EXT_2 | APAIDEN | SPRTELE_PHONE_EXT |
| A6.71 | Other Phone Country Code 2 CTRY_CODE_PHONE_2 | APAIDEN | SPRTELE_CTRY_CODE_PHONE |
| A6.72 | Other Phone Type Code 3 TELE_CODE_3 | APAIDEN | SPRTELE_TELE_CODE |
| A6.73 | Other Phone Type Description 3 TELE_DESC_3 | APAIDEN | STVTELE_DESC |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|---|-----------|--|
| A6.74 | Other Phone Number 3 PHONE_NUMBER_3 | APAIDEN | SPRTELE_PHONE_NUMBER |
| A6.75 | Other Phone Area Code 3 PHONE_AREA_CODE_3 | APAIDEN | SPRTELE_PHONE_AREA |
| A6.76 | Other Phone Extension 3 PHONE_EXT_3 | APAIDEN | SPRTELE_PHONE_EXT |
| A6.77 | Other Phone Country Code 3 CTRY_CODE_PHONE_3 | APAIDEN | SPRTELE_CTRY_CODE_PHONE |
| A6.78 | Additional Phone Numbers Flag ADD_PHONE_FLAG | Function | F_CHECK_FOR_MORE If there are more than three additional phone numbers, put a <i>Y</i> in this field. |
| Get the four most preferred Donor Category Codes using the ATVDONR_RPT_SEQ_IND field which sorts Donor Categories by preference. | | | |
| A6.79 | Preferred Donor Category Code PREF_DONR_CODE | AOAORGN | ATVDONR_CODE |
| A6.80 | Preferred Donor Category Description PREF_DONR_DESC | AOAORGN | ATVDONR_DESC |
| A6.81 | Other Donor Category Code 1 OTHER_DONR_CODE_1 | AOAORGN | ATVDONR_CODE |
| A6.82 | Other Donor Category 1 Description OTHER_DONR_DESC_1 | AOAORGN | ATVDONR_DESC |
| A6.83 | Other Donor Category Code 2 OTHER_DONR_CODE_2 | AOAORGN | ATVDONR_CODE |
| A6.84 | Other Donor Category 2 Description OTHER_DONR_DESC_2 | AOAORGN | ATVDONR_DESC |
| A6.85 | Other Donor Category Code 3 OTHER_DONR_CODE_3 | AOAORGN | ATVDONR_CODE |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|--|
| A6.86 | Other Donor Category 3 Description OTHER_DONR_DESC_3 | AOAORGN | ATVDONR_DESC |
| A6.87 | Additional Donor Categories Flag ADD_DONOR_CAT_FLAG | Function | F_CHECK_FOR_MORE If there are more than four donor categories, put a Y in this field. |
| A6.88 | Primary Contact Surname Prefix PRM_CONTACT_SURNAME_PREFIX | AOAORGN | AOBORGN_SURNAME_PRFX_CONTACT |
| A6.89 | Primary Contact Last Name PRM_CONTACT_LAST_NAME | AOAORGN | AOBORGN_LAST_NAME_CONTACT |
| A6.90 | Primary Contact First Name PRM_CONTACT_FIRST_NAME | AOAORGN | AOBORGN_FIRST_NAME_CONTACT |
| A6.91 | Primary Contact Middle Name PRM_CONTACT_MIDDLE_NAME | AOAORGN | AOBORGN_MI_CONTACT |
| A6.92 | Primary Contact Prefix Name PRM_CONTACT_PREFIX_NAME | AOAORGN | AOBORGN_PREFIX_CONTACT |
| A6.93 | Primary Contact Address Type PRM_CONTACT_ATYP_CODE | AOAORGN | AOBORGN_ATYP_CODE |
| A6.94 | Primary Contact Address Type Description PRM_CONTACT_ATYP_DESC | AOAORGN | ATVATYP_DESC |
| A6.95 | Primary Contact House Number PRM_CONTACT_HOUSE_NUMBER | AOAORGN | SPRADDR_HOUSE_NUMBER |
| A6.96 | Primary Contact Street Line 1 PRM_CONTACT_STREET_LINE1 | AOAORGN | SPRADDR_STREET_LINE1 |
| A6.97 | Primary Contact Street Line 2 PRM_CONTACT_STREET_LINE2 | AOAORGN | SPRADDR_STREET_LINE2 |
| A6.98 | Primary Contact Street Line 3 PRM_CONTACT_STREET_LINE3 | AOAORGN | SPRADDR_STREET_LINE3 |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|--|
| A6.99 | Primary Contact Street Line 4 PRM_CONTACT_STREET_LINE4 | AOAORGN | SPRADDR_STREET_LINE4 |
| A6.100 | Primary Contact City PRM_CONTACT_CITY | AOAORGN | SPRADDR_CITY |
| A6.101 | Primary Contact State PRM_CONTACT_STAT_CODE | AOAORGN | SPRADDR_STAT_CODE |
| A6.102 | Primary Contact Zip Code PRM_CONTACT_ZIP | AOAORGN | SPRADDR_ZIP |
| A6.103 | Primary Contact County Code PRM_CONTACT_CNTY_CODE | AOAORGN | SPRADDR_CNTY_CODE |
| A6.104 | Primary Contact County Description PRM_CONTACT_CNTY_DESC | AOAORGN | SPRADDR_CNTY_DESC |
| A6.105 | Primary Contact Nation Code PRM_CONTACT_NATN_CODE | AOAORGN | SPRADDR_NATN_CODE |
| A6.106 | Primary Contact Nation Description PRM_CONTACT_NATN_DESC | AOAORGN | STVNATN_NATION |
| A6.107 | Primary Contact Primary Phone Number PRM_CONTACT_PHONE_NUMBER | AOAORGN | SPRTELE_PHONE_NUMBER Note: Need to get SEQNO , ATYP_CODE , and PRIMARY_IND to get primary phone number. |
| A6.108 | Primary Contact Prim. Phone Area Code PRM_CONTACT_PHONE_AREA_CODE | AOAORGN | SPRTELE_PHONE_AREA |
| A6.109 | Primary Contact Primary Phone Extension PRM_CONTACT_PHONE_EXT | AOAORGN | SPRTELE_PHONE_EXT |
| A6.110 | Primary Contact Primary Phone Country Code PRM_CONTACT_CTRY_CODE | AOAORGN | SPRTELE_CTRY_CODE_PHONE |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|------------------------------------|
| | <p>Select two Secondary Contacts and related information using the logic defined for the Secondary Contact Type concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMOCON</i> and Internal Group = <i>SECONDARY CONTACT</i>.</p> <p>Note: The table source of some secondary contact attributes depends on if the secondary contact has a PIDM. Multi-source attributes are denoted using a slash (/). The table name to the left of the slash indicates the source if the secondary contact <i>does not have a PIDM</i>. The table name to the right of the slash indicates the source if the secondary contact <i>has a PIDM</i>. In most cases the source field name is the same except for the table name prefix.</p> | | |
| A6.111 | Secondary Contact Type Code 1 SEC_CONTACT_OCON_CODE_1 | AOAORGN | AORCONT_OCON_CODE |
| A6.112 | Secondary Contact Type Description 1 SEC_CONTACT_OCON_DESC_1 | AOAORGN | ATVOCON_DESC |
| A6.113 | Secondary Contact Personal ID Master 1 SEC_CONTACT_PIDM_1 | AOAORGN | AORCONT_CONTACT_PIDM |
| A6.114 | Secondary Contact Surname Prefix 1 SEC_CONTACT_SURNAME_PRFX_1 | AOAORGN | AORCONT/ SPRIDEN_SURNAME_PREFIX |
| A6.115 | Secondary Contact Last Name 1 SEC_CONTACT_LAST_NAME_1 | AOAORGN | AORCONT/SPRIDEN_LAST_NAME |
| A6.116 | Secondary Contact First Name 1 SEC_CONTACT_FIRST_NAME_1 | AOAORGN | AORCONT/ SPRIDEN_FIRST_NAME |
| A6.117 | Secondary Contact Middle Name 1 SEC_CONTACT_MIDDLE_NAME_1 | AOAORGN | AORCONT/SPRIDEN_MI |
| A6.118 | Secondary Contact Address Type Code 1 SEC_CONTACT_ATYP_CODE_1 | AOAORGN | AORCONT/SPRIDEN_ATYP_CODE |
| A6.119 | Sec. Contact Address Type Description 1 SEC_CONTACT_ATYP_DESC_1 | AOAORGN | ATVATYP_DESC |
| A6.120 | Secondary Contact House Number 1 SEC_CONTACT_HOUSE_NUMBER_1 | AOAORGN | SPRADDR_HOUSE_NUMBER |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|-------------------------------|
| A6.121 | Secondary Contact 1 Street Line 1 SEC_CONTACT_STREET_LINE1_1 | AOAORGN | SPRADDR_STREET_LINE1 |
| A6.122 | Secondary Contact 1 Street Line 2 SEC_CONTACT_STREET_LINE2_1 | AOAORGN | SPRADDR_STREET_LINE2 |
| A6.123 | Secondary Contact 1 Street Line 3 SEC_CONTACT_STREET_LINE3_1 | AOAORGN | SPRADDR_STREET_LINE3 |
| A6.124 | Secondary Contact 1 Street Line 4 SEC_CONTACT_STREET_LINE4_1 | AOAORGN | SPRADDR_STREET_LINE4 |
| A6.125 | Secondary Contact City 1 SEC_CONTACT_CITY_1 | AOAORGN | SPRADDR_CITY |
| A6.126 | Secondary Contact State 1 SEC_CONTACT_STAT_CODE_1 | AOAORGN | SPRADDR_STAT_CODE |
| A6.127 | Secondary Contact Zip Code 1 SEC_CONTACT_ZIP_1 | AOAORGN | SPRADDR_ZIP |
| A6.128 | Secondary Contact County Code 1 SEC_CONTACT_CNTY_CODE_1 | AOAORGN | SPRADDR_CNTY_CODE |
| A6.129 | Secondary Contact County Description 1 SEC_CONTACT_CNTY_DESC_1 | AOAORGN | STVCNTY_DESC |
| A6.130 | Secondary Contact Nation Code 1 SEC_CONTACT_NATN_CODE_1 | AOAORGN | SPRADDR_NATN_CODE |
| A6.131 | Secondary Contact Nation Description 1 SEC_CONTACT_NATN_DESC_1 | AOAORGN | STVNATN_NATION |
| A6.132 | Secondary Contact Prim. Phone Num. 1 SEC_CONTACT_PHONE_NUMBER_1 | AOAORGN | SPRTELE_PHONE_NUMBER |

Note: Need to get SEQNO, ATYP_CODE, and PRIMARY_IND to get primary phone number.

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|------------------------------------|
| A6.133 | Secondary Contact Prim. Phone Area Code 1 SEC_CONTACT_PHONE_AREA_CODE_1 | AOAORGN | SPRTELE_PHONE_AREA |
| A6.134 | Secondary Contact Primary Phone Ext. 1 SEC_CONTACT_PHONE_EXT_1 | AOAORGN | SPRTELE_PHONE_EXT |
| A6.135 | Secondary Contact Primary Phone Country Code 1 SEC_CONTACT_CTRY_CODE_1 | AOAORGN | SPRTELE_CTRY_CODE_PHONE |
| A6.136 | Secondary Contact Type Code 2 SEC_CONTACT_OCON_CODE_2 | AOAORGN | AORCONT_OCON_CODE |
| A6.137 | Secondary Contact Type Description 2 SEC_CONTACT_OCON_DESC_2 | AOAORGN | ATVOCON_DESC |
| A6.138 | Secondary Contact Personal ID Master 2 SEC_CONTACT_PIDM_2 | AOAORGN | AORCONT_CONTACT_PIDM |
| A6.139 | Secondary Contact Surname Prefix 2 SEC_CONTACT_SURNAME_PRFX_2 | AOAORGN | AORCONT/ SPRIDEN_SURNAME_PREFIX |
| A6.140 | Secondary Contact Last Name 2 SEC_CONTACT_LAST_NAME_2 | AOAORGN | AORCONT/SPRIDEN_LAST_NAME |
| A6.141 | Secondary Contact First Name 2 SEC_CONTACT_FIRST_NAME_2 | AOAORGN | AORCONT/ SPRIDEN_FIRST_NAME |
| A6.142 | Secondary Contact Middle Name 2 SEC_CONTACT_MIDDLE_NAME_2 | AOAORGN | AORCONT/SPRIDEN_MI |
| A6.143 | Secondary Contact Address Type Code 2 SEC_CONTACT_ATYP_CODE_2 | AOAORGN | AORCONT/SPRIDEN_ATYP_CODE |
| A6.144 | Sec. Contact Address Type Description 2 SEC_CONTACT_ATYP_DESC_2 | AOAORGN | ATVATYP_DESC |
| A6.145 | Secondary Contact 2 House Number 2 SEC_CONTACT_HOUSE_NUMBER_2 | AOAORGN | SPRADDR_HOUSE_NUMBER |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A6.146 | Secondary Contact 2 Street Line 1 SEC_CONTACT_STREET_LINE1_2 | AOAORGN | SPRADDR_STREET_LINE1 |
| A6.147 | Secondary Contact 2 Street Line 2 SEC_CONTACT_STREET_LINE2_2 | AOAORGN | SPRADDR_STREET_LINE2 |
| A6.148 | Secondary Contact 2 Street Line 3 SEC_CONTACT_STREET_LINE3_2 | AOAORGN | SPRADDR_STREET_LINE3 |
| A6.149 | Secondary Contact 2 Street Line 4 SEC_CONTACT_STREET_LINE4_2 | AOAORGN | SPRADDR_STREET_LINE4 |
| A6.150 | Secondary Contact City 2 SEC_CONTACT_CITY_2 | AOAORGN | SPRADDR_CITY |
| A6.151 | Secondary Contact State 2 SEC_CONTACT_STAT_CODE_2 | AOAORGN | SPRADDR_STAT_CODE |
| A6.152 | Secondary Contact Zip Code 2 SEC_CONTACT_ZIP_2 | AOAORGN | SPRADDR_ZIP |
| A6.153 | Secondary Contact County Code 2 SEC_CONTACT_CNTY_CODE_2 | AOAORGN | SPRADDR_CNTY_CODE |
| A6.154 | Secondary Contact County Description 2 SEC_CONTACT_CNTY_DESC_2 | AOAORGN | STVCNTY_DESC |
| A6.155 | Secondary Contact Nation Code 2 SEC_CONTACT_NATN_CODE_2 | AOAORGN | SPRADDR_NATN_CODE |
| A6.156 | Secondary Contact Nation Description 2 SEC_CONTACT_NATN_DESC_2 | AOAORGN | STVNATN_NATION |
| A6.157 | Secondary Contact Prim. Phone Num. 2 SEC_CONTACT_PHONE_NUMBER_2 | AOAORGN | SPRTELE_PHONE_NUMBER Note: Need to get SEQNO, ATYP_CODE, and PRIMARY_IND to get primary phone number. |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|--|-----------|--|
| A6.158 | Secondary Contact Prim. Phone Area Code 2 SEC_CONTACT_PHONE_AREA_CODE_2 | AOAORGN | SPRTELE_PHONE_AREA |
| A6.159 | Secondary Contact Primary Phone Ext. 2 SEC_CONTACT_PHONE_EXT_2 | AOAORGN | SPRTELE_PHONE_EXT |
| A6.160 | Secondary Contact Primary Phone Country Code 2 SEC_CONTACT_CTRY_CODE_2 | AOAORGN | SPRTELE_CTRY_CODE_PHONE |
| <p>Select three Funding Interests and related information using the logic defined for the Funding Interest Code concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMFUND</i> and Internal Group = <i>FUNDING</i>.</p> | | | |
| A6.161 | Funding Interests Code 1 FUND_CODE_1 | AOAORGN | AORFUND_FUND_CODE |
| A6.162 | Funding Interests Description 1 FUND_DESC_1 | AOAORGN | ATVFUND_DESC |
| A6.163 | Funding Interests Code 2 FUND_CODE_2 | AOAORGN | AORFUND_FUND_CODE |
| A6.164 | Funding Interests Description 2 FUND_DESC_2 | AOAORGN | ATVFUND_DESC |
| A6.165 | Funding Interests Code 3 FUND_CODE_3 | AOAORGN | AORFUND_FUND_CODE |
| A6.166 | Funding Interests Description 3 FUND_DESC_3 | AOAORGN | ATVFUND_DESC |
| A6.167 | Additional Funding Codes Flag ADD_FUND_INTEREST_FLAG | Function | F_CHECK_FOR_MORE If there are more than three funding codes, put a Y in this field. |

Table 6: Organization View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|--|
| A6.168 | Matching Gift Comp. Personal ID Master MATCH_GIFT_COMP_PIDM | Function | F_MATCHING_GIFT_COMPANY_NAME SPRIDEN_PIDM of AOBORGN_MG_PIDM |
| A6.169 | Matching Gift Company ID MATCH_GIFT_COMP_ID | Function | F_MATCHING_GIFT_COMPANY_NAME SPRIDEN_ID of AOBORGN_MG_PIDM |
| A6.170 | Matching Gift Company Name MATCH_GIFT_COMP_NAME | Function | F_MATCHING_GIFT_COMPANY_NAME SPRIDEN_LAST_NAME of AOBORGN_MG_PIDM |
| A6.171 | Organization Matching Gift Percentage ORGN_MATCH_GIFT_PCT | AOAORGN | AOBORGN_MATCH_PCT |
| A6.172 | Multiple Ratios MULTIPLE_RATIOS | Function | F_MULTIPLE_RATIOS If a record exists in AORMRTO for AOBORGN_MG_PIDM, enter a Y in this attribute. |
| A6.173 | Minimum Gift Amount to Match MIN_GIFT_AMT_MATCH | AOAORGN | AOBORGN_MATCH_MINIMUM |
| A6.174 | Maximum Matching Gift Amount per Employee per Year MAX_MATCH_GIFT_EMP_YR | AOAORGN | AOBORGN_MATCH_ORG_EMPL_YR |

View 7: Campaign Giving by ID

AA_CAMPAIGN_GIVING_BY_ID

If you are using FOCUS, the view name is AFVCOMP0.

The Campaign Giving by ID view lets you report on an ID's campaign giving by fiscal year. This view includes information about the donor categories, exclusions, and campaign giving for donors and their spouses.

This view accesses the following main database tables.

- AFBCAMP Campaign Base Table
- APBCONS Constituent Base Table
- APRCHIS Giving History by Campaign Repeating Table
- APRCSPS Constituent Spouse Table
- APREXCL Exclusion Code Repeating Table
- SPBPERS Basic Person Base Table
- SPRIDEN Person Identification/Name Repeating Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) chapter for a complete description of PIDM.

The key attributes of this view are

- Donor Personal ID Master PIDM_KEY
- Campaign Fiscal Year FISC_CODE_KEY
- Campaign CAMPAIGN_KEY

Because the PIDM is an internal ID unique to each ID, the view returns one row of information for each ID for every Campaign/Fiscal Year combination.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view, but you may find it useful to specify criteria for some or all of the following attributes. Specifying these criteria selects the population for a report and may reduce the time it takes to run the report.

- Campaign Fiscal Year FISC_CODE_KEY

- Campaign CAMPAIGN_KEY
- Preferred Donor Category Code DONOR_PREF_DONR_CODE

Attributes

The following list specifies the attributes included in the Campaign Giving by ID view. The list indicates the primary form and the database field or function that is the source for each attribute.

Table 7: Campaign Giving by ID View Attributes

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------------------|--|
| A7.1 | Donor Personal ID Master Key PIDM_KEY | APAIDEN | APRCHIS_PIDM |
| A7.2 | Campaign Fiscal Year Code Key FISC_CODE_KEY | APACHIS | APRCHIS_FISC_CODE |
| A7.3 | Campaign Key CAMPAIGN_KEY | AFACAMP | APRCHIS_CAMPAIGN |
| A7.4 | Campaign Name CAMPAIGN_NAME | AFACAMP | AFBCAMP_NAME |
| A7.5 | Donor Entity Indicator DONOR_ENTITY_IND | APAIDEN | SPRIDEN_ENTITY_IND |
| A7.6 | Donor Lost Alumnus Indicator DONOR_LOST_ALUMNUS_IND | Function (APAIDEN) | F_LOST_AL_IND If alumnus has no active addresses, that is, the TO_DATE passed on all addresses, or all addresses on SPRADDR have an I (Inactive) status, put a Y in this field. |
| A7.7 | Donor ID DONOR_ID | APAIDEN | SPRIDEN_ID |
| A7.8 | Donor Social Security Number DONOR_SSN | APAPERS | SPBPERS_SSN |

Table 7: Campaign Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|--|
| A7.9 | Donor Surname Prefix DONOR_SURNAME_PREFIX | APAIDEN | SPRIDEN_SURNAME_PREFIX |
| A7.10 | Donor Last Name DONOR_LAST_NAME | APAIDEN | SPRIDEN_LAST_NAME |
| A7.11 | Donor First Name DONOR_FIRST_NAME | APAIDEN | SPRIDEN_FIRST_NAME |
| A7.12 | Donor Middle Name DONOR_MIDDLE_NAME | APAIDEN | SPRIDEN_MI |
| A7.13 | Donor Middle Initial DONOR_MIDDLE_INITIAL | APAIDEN | SUBSTR (SPRIDEN_MI , 1 , 1) Returns first letter of middle name |
| A7.14 | Donor Name Prefix DONOR_NAME_PREFIX | APAPERS | SPBPERS_NAME_PREFIX |
| A7.15 | Donor Name Suffix DONOR_NAME_SUFFIX | APAPERS | SPBPERS_NAME_SUFFIX |
| A7.16 | Donor Nickname DONOR_NICKNAME | APANAME | APBCONS_NICKNAME |
| A7.17 | Donor Combined Mail Name DONOR_COMBINED_MAIL_NAME | APANAME | APBCONS_CM_NAME |
| A7.18 | Donor Birth/Maiden Name DONOR_BIRTH_MAIDEN_NAME | APANAME | APBCONS_MAIDEN_LAST_NAME |
| A7.19 | Donor Preferred Address Name DONOR_PREF_ADDRESS_NAME | APANAME | APBCONS_ADDR_NAME |
| A7.20 | Donor Preferred Address Type DONOR_PREF_ADDRESS_TYPE | APANAME | APBCONS_ATYP_CODE_PREF |
| A7.21 | Donor Deceased Indicator DONOR_DECEASED_IND | APAPERS | SPBPERS_DEAD_IND |

Table 7: Campaign Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|---|-----------|-------------------------------|
| A7.22 | Donor Date of Death DONOR_DECEASED_DATE | APAPERS | SPBPERS_DEAD_DATE |
| A7.23 | Donor Preferred College DONOR_PREF_COLL | APACONS | APBCONS_COLL_CODE_PREF |
| A7.24 | Donor Preferred Class DONOR_PREF_CLASS | APACONS | APBCONS_PREF_CLAS |
| <p>Get the four most preferred Donor Category Codes using the ATVDONR_RPT_SEQ_IND field which sorts Donor Categories by preference.</p> <p>Note: The source form of some donor category attributes depends on whether the donor is a person or a company. Multi-source attributes are denoted using a slash (/). The form name to the left of the slash indicates the source if the donor is a person. The form name to the right of the slash indicates the source if the donor is a company.</p> | | | |
| A7.25 | Preferred Donor Category Code DONOR_PREF_DONR_CODE | AOAORGN | ATVDONR_CODE |
| A7.26 | Preferred Donor Category Description DONOR_PREF_DONR_DESC | AOAORGN | ATVDONR_DESC |
| A7.27 | Pref. Donor Category Alumni Indicator DONOR_PREF_ALUM_IND | ATVDONR | ATVDONR_ALUM_IND |
| A7.28 | Other Donor Category Code 1 DONOR_OTHER_DONR_CODE_1 | AOAORGN | ATVDONR_CODE |
| A7.29 | Other Donor Category 1 Description DONOR_OTHER_DONR_DESC_1 | AOAORGN | ATVDONR_DESC |
| A7.30 | Other Donor Category Alumni Indicator 1 DONOR_OTHER_ALUM_IND_1 | ATVDONR | ATVDONR_ALUM_IND |
| A7.31 | Other Donor Category Code 2 DONOR_OTHER_DONR_CODE_2 | AOAORGN | ATVDONR_CODE |
| A7.32 | Other Donor Category 2 Description DONOR_OTHER_DONR_DESC_2 | AOAORGN | ATVDONR_DESC |

Table 7: Campaign Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|--|
| A7.33 | Other Donor Category Alumni Indicator 2 DONOR_OTHER_ALUM_IND_2 | ATVDONR | ATVDONR_ALUM_IND |
| A7.34 | Other Donor Category Code 3 DONOR_OTHER_DONR_CODE_3 | AOAORGN | ATVDONR_CODE |
| A7.35 | Other Donor Category 3 Description DONOR_OTHER_DONR_DESC_3 | AOAORGN | ATVDONR_DESC |
| A7.36 | Other Donor Category Alumni Indicator 3 DONOR_OTHER_ALUM_IND_3 | ATVDONR | ATVDONR_ALUM_IND |
| A7.37 | Additional Donor Categories Flag DONOR_ADD_DONOR_CAT_FLAG | Function | F_CHECK_FOR_MORE If there are more than four donor categories, put a Y in this field. |
| A7.38 | Donor Campaign Giving DONOR_CAMPAIGN_GIVING | Function | F_CAMPAIGN_GIVING Sum(APRCHIS_AMT_PLEDGED_PAID) + Sum(APRCHIS_AMT_GIFT) |
| A7.39 | Donor Campaign Pledged DONOR_CAMPAIGN_PLEDGED | APACHIS | APRCHIS_AMT_PLEDGED |
| A7.40 | Donor Campaign Gifts DONOR_CAMPAIGN_GIFT | APACHIS | APRCHIS_AMT_GIFT |
| A7.41 | Donor Campaign Payments DONOR_CAMPAIGN_PAYMENT | APACHIS | APRCHIS_AMT_PLEDGED_PAID |
| A7.42 | Donor Campaign Matching Gifts DONOR_CAMPAIGN_MATCHING_GIFT | Function | F_CAMPAIGN_MATCHING_GIFT AGRMGIF_AMT_PAID for the campaign |
| A7.43 | Donor Campaign Memo Credit (Non-matching) DONOR_CAMPAIGN_MEMO_CREDIT | Function | F_CAMPAIGN_MEMO_CREDIT APRCHIS_AMT_MEMO – (AGRMGIF_AMT_PAID for the campaign) |

Table 7: Campaign Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|---|-----------|-------------------------------|
| A7.44 | Campaign Type Code CMTP_CODE | AFACAMP | AFBCAMP_CMTP_CODE |
| A7.45 | Campaign Type Description CMTP_DESC | AFACAMP | ATVCMTP_DESC |
| <p>Select three Exclusions for the donor using the logic defined for the Exclusion Code (Campaign) concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMEXCL</i> and Internal Group = <i>CAMP EXCLUSION</i>.</p> <p>Note: Be sure to refer to the correct Exclusion Code concept, because there is more than one.</p> | | | |
| A7.46 | Donor Exclusion Code 1 DONOR_EXCL_CODE_1 | APAMAIL | APREXCL_EXCL_CODE |
| A7.47 | Donor Exclusion Code Description 1 DONOR_EXCL_DESC_1 | APAMAIL | ATVEXCL_DESC |
| A7.48 | Donor Exclusion Date 1 DONOR_EXCLUSION_DATE_1 | APAMAIL | APREXCL_DATE |
| A7.49 | Donor Exclusion Code 2 DONOR_EXCL_CODE_2 | APAMAIL | APREXCL_EXCL_CODE |
| A7.50 | Donor Exclusion Code Description 2 DONOR_EXCL_DESC_2 | APAMAIL | ATVEXCL_DESC |
| A7.51 | Donor Exclusion Date 2 DONOR_EXCLUSION_DATE_2 | APAMAIL | APREXCL_DATE |
| A7.52 | Donor Exclusion Code 3 DONOR_EXCL_CODE_3 | APAMAIL | APREXCL_EXCL_CODE |
| A7.53 | Donor Exclusion Code Description 3 DONOR_EXCL_DESC_3 | APAMAIL | ATVEXCL_DESC |
| A7.54 | Donor Exclusion Date 3 DONOR_EXCLUSION_DATE_3 | APAMAIL | APREXCL_DATE |

Table 7: Campaign Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|---|-----------|---|
| A7.55 | Additional Donor Exclusion Codes Flag DONOR_ADD_EXCLUSION_FLAG | Function | F_CHECK_FOR_MORE If there are more than three exclusion codes, put a <i>Y</i> in this field. |
| Select the spouse using the most recent From Date. | | | |
| Note: The table source of some spouse attributes depends on whether the spouse has a PIDM. Multi-source attributes are denoted using a slash (/). The table name to the left of the slash indicates the source if the spouse <i>does not have a PIDM</i> or it may indicate a <i>Null</i> value. The table name to the right of the slash indicates the source if the spouse <i>has a PIDM</i> . In most cases, the field name is the same except for the table prefix. | | | |
| A7.56 | Spouse Personal ID Master SPOUSE_PIDM | APACONS | null/APRCSPS_SPS_PIDM |
| A7.57 | Spouse Surname Prefix SPOUSE_SURNAME_PREFIX | APACONS | APRCSPS/ SPRIDEN_SURNAME_PREFIX |
| A7.58 | Spouse Last Name SPOUSE_LAST_NAME | APACONS | APRCSPS/SPRIDEN_LAST_NAME |
| A7.59 | Spouse First Name SPOUSE_FIRST_NAME | APACONS | APRCSPS/ SPRIDEN_FIRST_NAME |
| A7.60 | Spouse Birth/Maiden Name SPOUSE_BIRTH_MAIDEN_NAME | APACONS | APRCSPS_MAIDEN_NAME/ APBCONS_MAIDEN_last_NAME |
| A7.61 | Spouse Name Prefix SPOUSE_NAME_PREFIX | APACONS | APRCSPS/ SPBPERS_NAME_PREFIX |
| A7.62 | Spouse Name Suffix SPOUSE_NAME_SUFFIX | APACONS | APRCSPS/ SPBPERS_NAME_SUFFIX |
| A7.63 | Spouse Status SPOUSE_IND | APACONS | APRCSPS_MARS_IND |
| A7.64 | Spouse Deceased Indicator SPOUSE_DECEASED_IND | APACONS | APRCSPS/SPBPERS_DEAD_IND |

Table 7: Campaign Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A7.65 | Spouse Date of Death SPOUSE_DECEASED_DATE | APACONS | APRCSPS/SPBPERS_DEAD_DATE |
| A7.66 | Spouse Preferred College SPOUSE_PREF_COLL | APANAME | null/ APBCONS_COLL_CODE_PREF |
| A7.67 | Spouse Preferred Class Year SPOUSE_CLASS_YEAR | APANAME | null/APBCONS_PREF_CLAS |
| A7.68 | Spouse Lost Alumnus Indicator SPOUSE_LOST_ALUMNUS_IND | Function | null/F_LOST_AL_IND If spouse has no active addresses, that is, the TO_DATE passed on all addresses or all addresses on SPRADDR have an I (Inactive) status, put a Y in this field. |
| A7.69 | Spouse Primary Donor Category Code SPOUSE_PREF_DONR_CODE | APACONS | null/ATVDONR_CODE |
| A7.70 | Spouse Primary Donor Category Desc. SPOUSE_PREF_DONR_DESC | APACONS | null/ATVDONR_DESC |
| A7.71 | Spouse ID SPOUSE_ID | APACONS | null/SPRIDEN_ID |
| A7.72 | Spouse Campaign Giving SPOUSE_CAMPAIGN_GIVING | Function | f_campaign_giving Sum(APRCHIS_AMT_PLEDGED_PAID) + Sum(APRCHIS_AMT_GIFT) |
| A7.73 | Spouse Campaign Pledged SPOUSE_CAMPAIGN_PLEDGED | APACHIS | APRCHIS_AMT_PLEDGED |
| A7.74 | Spouse Campaign Gifts SPOUSE_CAMPAIGN_GIFT | APACHIS | APRCHIS_AMT_GIFT |
| A7.75 | Spouse Campaign Payments SPOUSE_CAMPAIGN_PAYMENT | APACHIS | APRCHIS_AMT_PLEDGED_PAID |

Table 7: Campaign Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|---|-----------|--|
| A7.76 | Spouse Campaign Matching Gifts SPOUSE_CAMPAIGN_MATCHING_GIFT | Function | F_CAMPAIGN_MATCHING_GIFT AGRMGIF_AMT_PAID for the campaign |
| A7.77 | Spouse Campaign Memo Credit (Non-matching) SPOUSE_CAMPAIGN_MEMO_CREDIT | Function | F_CAMPAIGN_MEMO_CREDIT APRCHIS_AMT_MEMO – (AGRMGIF_AMT_PAID for the campaign) |
| <p>Select three Exclusions for the spouse using the logic defined for the Exclusion Code (Campaign) concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMEXCL</i> and Internal Group = <i>CAMP EXCLUSION</i>.</p> <p>Note: Be sure to refer to the correct Exclusion Code concept, because there is more than one.</p> | | | |
| A7.78 | Spouse Exclusion Code 1 SPOUSE_EXCL_CODE_1 | APAMAIL | APREXCL_EXCL_CODE |
| A7.79 | Spouse Exclusion Code Description 1 SPOUSE_EXCL_DESC_1 | APAMAIL | ATVEXCL_DESC |
| A7.80 | Spouse Exclusion Date 1 SPOUSE_EXCLUSION_DATE_1 | APAMAIL | APREXCL_DATE |
| A7.81 | Spouse Exclusion Code 2 SPOUSE_EXCL_CODE_2 | APAMAIL | APREXCL_EXCL_CODE |
| A7.82 | Spouse Exclusion Code Description 2 SPOUSE_EXCL_DESC_2 | APAMAIL | ATVEXCL_DESC |
| A7.83 | Spouse Donor Exclusion Date 2 SPOUSE_EXCLUSION_DATE_2 | APAMAIL | APREXCL_DATE |
| A7.84 | Spouse Exclusion Code 3 SPOUSE_EXCL_CODE_3 | APAMAIL | APREXCL_EXCL_CODE |

Table 7: Campaign Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A7.85 | Spouse Exclusion Code Description 3 SPOUSE_EXCL_DESC_3 | APAMAIL | ATVEXCL_DESC |
| A7.86 | Spouse Exclusion Date 3 SPOUSE_EXCLUSION_DATE_3 | APAMAIL | APREXCL_DATE |
| A7.87 | Additional Donor Exclusion Codes Flag SPOUSE_ADD_EXCLUSION_FLAG | Function | F_CHECK_FOR_MORE If there are more than three exclusion codes, put a <i>Y</i> in this field. |

View 8: Designation Giving by ID

AA_DESIGNATION_GIVING_BY_ID

If you are using FOCUS, the view name is ADVDSG0.

The Designation Giving by ID view lets you report on an ID's designation giving by fiscal year. This view includes information about the donor categories, exclusions, and designation giving for donors and their spouses.

This view accesses the following main database tables.

- ADBDESG Designation Base Table
- APBCONS Constituent Base Table
- APRCSPS Constituent Spouse Table
- APRDHIS Giving History by Designation Repeating Table
- APREXCL Exclusion Code Repeating Table
- SPBPERS Basic Person Base Table
- SPRIDEN Person Identification/Name Repeating Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) for a complete description of PIDM. ■

The key attributes of this view are:

- Donor Personal ID Master PIDM_KEY
- Designation Fiscal Year FISC_CODE_KEY
- Designation DESIGNATION_KEY

Because the PIDM is an internal ID unique to each ID, the view returns one row of information for each ID for every Designation/Fiscal Year combination.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view, but you may find it useful to specify criteria for some or all of the following attributes. Specifying these criteria selects the population for a report and may reduce the time it takes to run the report.

- Designation Fiscal Year FISC_CODE_KEY

- Designation DESIGNATION_KEY
- Preferred Donor Category Code DONOR_PREF_DONR_CODE

Attributes

The following list specifies the attributes included in the Designation Giving by ID view. The list also indicates the primary form and the database field or function that is the source for each attribute.

Table 8: Designation Giving by ID View Attributes

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------------------|---|
| A8.1 | Donor Personal ID Master Key PIDM_KEY | APAIDEN | APRDHIS_PIDM |
| A8.2 | Designation Fiscal Year Key FISC_CODE_KEY | APADHIS | APRDHIS_FISC_CODE |
| A8.3 | Designation Key DESIGNATION_KEY | APADHIS | APRDHIS_DESG |
| A8.4 | Designation Description DESIGNATION_NAME | ADADESG | ADBDESG_NAME |
| A8.5 | Donor Entity Indicator DONOR_ENTITY_IND | APAIDEN | SPRIDEN_ENTITY_IND |
| A8.6 | Donor Lost Alumnus Indicator DONOR_LOST_ALUMNUS_IND | Function (APAIDEN) | F_LOST_AL_IND If alumnus has no active addresses, that is, the TO_DATE passed on all addresses or all addresses on SPRADDR have an I (Inactive) status, put a Y in this field. |
| A8.7 | Donor ID DONOR_ID | APAIDEN | SPRIDEN_ID |
| A8.8 | Donor Social Security Number DONOR_SSN | APAPERS | SPBPERS_SSN |

Table 8: Designation Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|--|
| A8.9 | Donor Surname Prefix DONOR_SURNAME_PREFIX | APAIDEN | SPRIDEN_SURNAME_PREFIX |
| A8.10 | Donor Last Name DONOR_LAST_NAME | APAIDEN | SPRIDEN_LAST_NAME |
| A8.11 | Donor First Name DONOR_FIRST_NAME | APAIDEN | SPRIDEN_FIRST_NAME |
| A8.12 | Donor Middle Name DONOR_MIDDLE_NAME | APAIDEN | SPRIDEN_MI |
| A8.13 | Donor Middle Initial DONOR_MIDDLE_INITIAL | APAIDEN | SUBSTR (SPRIDEN_MI , 1 , 1) Returns first letter of middle name |
| A8.14 | Donor Name Prefix DONOR_NAME_PREFIX | APAPERS | SPBPERS_NAME_PREFIX |
| A8.15 | Donor Name Suffix DONOR_NAME_SUFFIX | APAPERS | SPBPERS_NAME_SUFFIX |
| A8.16 | Donor Nickname DONOR_NICKNAME | APANAME | APBCONS_NICKNAME |
| A8.17 | Donor Combined Mail Name DONOR_COMBINED_MAIL_NAME | APANAME | APBCONS_CM_NAME |
| A8.18 | Donor Birth/Maiden Name DONOR_BIRTH_MAIDEN_NAME | APANAME | APBCONS_MAIDEN_LAST_NAME |
| A8.19 | Donor Preferred Address Name DONOR_PREF_ADDRESS_NAME | APANAME | APBCONS_ADDR_NAME |
| A8.20 | Donor Preferred Address Type DONOR_PREF_ADDRESS_TYPE | APANAME | APBCONS_ATYP_CODE_PREF |

Table 8: Designation Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|---|---------------------|-------------------------------|
| A8.21 | Donor Deceased Indicator DECEASED_IND | APAPERS | SPBPERS_DEAD_IND |
| A8.22 | Donor Date of Death DECEASED_DATE | APAPERS | SPBPERS_DEAD_DATE |
| A8.23 | Donor Preferred College DONOR_PREF_COLL | APACONS | APBCONS_COLL_CODE_PREF |
| A8.24 | Donor Preferred Class DONOR_PREF_CLASS | APACONS | APBCONS_PREF_CLAS |
| <p>Get the four most preferred Donor Category Codes using the ATVDONR_RPT_SEQ_IND field which sorts Donor Categories by preference.</p> <p>Note: The source form of some donor category attributes depends on whether the donor is a person or a company. Multi-source attributes are denoted using a slash (/). The form name to the left of the slash indicates the source if the donor is a person. The form name to the right of the slash indicates the source if the donor is a company.</p> | | | |
| A8.25 | Preferred Donor Category Code DONOR_PREF_DONR_CODE | APACONS/ AOAORGN | ATVDONR_CODE |
| A8.26 | Preferred Donor Category Description DONOR_PREF_DONR_DESC | APACONS/ AOAORGN | ATVDONR_DESC |
| A8.27 | Pref. Donor Category Alumni Indicator DONOR_PREF_ALUM_IND | ATVDONR | ATVDONR_ALUM_IND |
| A8.28 | Other Donor Category Code 1 DONOR_OTHER_DONR_CODE_1 | APACONS/ AOAORGN | ATVDONR_CODE |
| A8.29 | Other Donor Category 1 Description DONOR_OTHER_DONR_DESC_1 | APACONS/ AOAORGN | ATVDONR_DESC |
| A8.30 | Other Donor Category Alumni Indicator 1 DONOR_OTHER_ALUM_IND_1 | ATVDONR | ATVDONR_ALUM_IND |
| A8.31 | Other Donor Category Code 2 DONOR_OTHER_DONR_CODE_2 | APACONS/ AOAORGN | ATVDONR_CODE |

Table 8: Designation Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|---------------------|--|
| A8.32 | Other Donor Category 2 Description DONOR_OTHER_DONR_DESC_2 | APACONS/ AOAORGN | ATVDONR_DESC |
| A8.33 | Other Donor Category Alumni Indicator 2 DONOR_OTHER_ALUM_IND_2 | ATVDONR | ATVDONR_ALUM_IND |
| A8.34 | Other Donor Category Code 3 DONOR_OTHER_DONR_CODE_3 | APACONS/ AOAORGN | ATVDONR_CODE |
| A8.35 | Other Donor Category 3 Description DONOR_OTHER_DONR_DESC_3 | APACONS/ AOAORGN | ATVDONR_DESC |
| A8.36 | Other Donor Category Alumni Indicator 3 DONOR_OTHER_ALUM_IND_3 | ATVDONR | ATVDONR_ALUM_IND |
| A8.37 | Additional Donor Categories Flag DONOR_ADD_DONOR_CAT_FLAG | Function | F_CHECK_FOR_MORE If there are more than four donor categories, put a Y in this field. |
| A8.38 | Donor Designation Giving DONOR_DESG_GIVING | Function | F_DESIGNATION_GIVING Sum(APRDHIS_PLEDGED_PAID) + Sum(APRDHIS_AMT_GIFT) |
| A8.39 | Donor Designation Pledged DONOR_DESG_PLEDGED | APADHIS | APRDHIS_AMT_PLEDGED |
| A8.40 | Donor Designation Gifts DONOR_DESG_GIFT | APADHIS | APRDHIS_AMT_GIFT |
| A8.41 | Donor Designation Payments DONOR_DESG_PAYMENT | APADHIS | APRDHIS_AMT_PLEDGED_PAID |
| A8.42 | Donor Designation Matching Gifts DONOR_DESG_MATCHING_GIFT | Function | F_DESIGNATION_MATCHING_GIFT AGRMGIF_AMT_PAID for the designation |

Table 8: Designation Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|--|-----------|---|
| A8.43 | Donor Designation Memo Credit (Non-matching) DONOR_DESG_MEMO_CREDIT | Function | F_DESIGNATION_MEMO_CREDIT APRDHIS_AMT_MEMO – (AGRMGIF_AMT_PAID for the designation) |
| A8.44 | Designation College Code COLL_CODE | ADADESG | ADBDESG_COLL_CODE |
| A8.45 | College Description COLL_DESC | ADADESG | STV_COLL_DESC |
| A8.46 | Voluntary Support of Education Code CFAE_CODE | ADADESG | ADBDESG_CFAE_CODE |
| A8.47 | Voluntary Support of Education Description CFAE_DESC | ADADESG | ATVCFAE_DESC |
| A8.48 | Designation Type Code DSTP_CODE | ADADESG | ADBDESG_DSTP_CODE |
| A8.49 | Designation Type Description DSTP_DESC | ADADESG | ATVDSTP_DESC |
| <p>Select three Exclusions for the donor using the logic defined for the Exclusion Code (Designation) concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMEXCL</i> and Internal Group = <i>DESG EXCLUSION</i>.</p> <p>Note: Be sure to refer to the correct Exclusion Code concept, because there is more than one.</p> | | | |
| A8.50 | Donor Exclusion Code 1 DONOR_EXCL_CODE_1 | APAMAIL | APREXCL_EXCL_CODE |
| A8.51 | Donor Exclusion Code Description 1 DONOR_EXCL_DESC_1 | APAMAIL | ATVEXCL_DESC |
| A8.52 | Donor Exclusion Date 1 DONOR_EXCLUSION_DATE_1 | APAMAIL | APREXCL_DATE |

Table 8: Designation Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|---|-----------|---|
| A8.53 | Donor Exclusion Code 2 DONOR_EXCL_CODE_2 | APAMAIL | APREXCL_EXCL_CODE |
| A8.54 | Donor Exclusion Code Description 2 DONOR_EXCL_DESC_2 | APAMAIL | ATVEXCL_DESC |
| A8.55 | Donor Exclusion Date 2 DONOR_EXCLUSION_DATE_2 | APAMAIL | APREXCL_DATE |
| A8.56 | Donor Exclusion Code 3 DONOR_EXCL_CODE_3 | APAMAIL | APREXCL_EXCL_CODE |
| A8.57 | Donor Exclusion Code Description 3 DONOR_EXCL_DESC_3 | APAMAIL | ATVEXCL_DESC |
| A8.58 | Donor Exclusion Date 3 DONOR_EXCLUSION_DATE_3 | APAMAIL | APREXCL_DATE |
| A8.59 | Additional Donor Exclusion Codes Flag DONOR_ADD_EXCLUSION_FLAG | Function | F_CHECK_FOR_MORE If there are more than three exclusion codes, put a <i>Y</i> in this field. |
| Select the spouse using the most recent From Date. | | | |
| <p>Note: The table source of some spouse attributes depends on if the spouse has a PIDM. Multi-source attributes are denoted using a slash (/). The table name to the left of the slash indicates the source if the spouse <i>does not have a PIDM</i> or it may indicate a <i>Null</i> value. The table name to the right of the slash indicates the source if the spouse <i>has a PIDM</i>. In most cases, the field name is the same except for the table prefix.</p> | | | |
| A8.60 | Spouse Personal ID Master SPOUSE_PIDM | APACONS | null/APRCSPS_SPS_PIDM |
| A8.61 | Spouse Surname Prefix SPOUSE_SURNAME_PREFIX | APAIDEN | APRCSPS/ SPRIDEN_SURNAME_PREFIX |
| A8.62 | Spouse Last Name SPOUSE_LAST_NAME | APACONS | APRCSPS/SPRIDEN_LAST_NAME |

Table 8: Designation Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------------------|---|
| A8.63 | Spouse First Name SPOUSE_FIRST_NAME | APACONS | APRCSPS/ SPRIDEN_FIRST_NAME |
| A8.64 | Spouse Birth/Maiden Name SPOUSE_BIRTH_MAIDEN_NAME | APACONS | APRCSPS_MAIDEN_NAME/ APBCONS_MAIDEN_LAST_NAME |
| A8.65 | Spouse Name Prefix SPOUSE_NAME_PREFIX | APACONS | APRCSPS/ SPBPERS_NAME_PREFIX |
| A8.66 | Spouse Name Suffix SPOUSE_NAME_SUFFIX | APACONS | APRCSPS/ SPBPERS_NAME_SUFFIX |
| A8.67 | Spouse Status SPOUSE_IND | APACONS | APRCSPS_MARS_IND |
| A8.68 | Spouse Deceased Indicator SPOUSE_DECEASED_IND | APACONS | APRCSPS/SPBPERS_DEAD_IND |
| A8.69 | Spouse Date of Death SPOUSE_DECEASED_DATE | APACONS | APRCSPS/SPBPERS_DEAD_DATE |
| A8.70 | Spouse Preferred College SPOUSE_PREF_COLL | APANAME | null/ APBCONS_COLL_CODE_PREF |
| A8.71 | Spouse Preferred Class Year SPOUSE_CLASS_YEAR | APANAME | null/APBCONS_PREF_CLAS |
| A8.72 | Spouse Lost Alumnus Indicator SPOUSE_LOST_ALUMNUS_IND | Function (APAIDEN) | null/F_LOST_AL_IND If spouse has no active addresses, that is, the TO_DATE passed on all addresses or all addresses on SPRADDR have an I (Inactive) status, put a Y in this field. |
| A8.73 | Spouse Primary Donor Category Code SPOUSE_PREF_DONR_CODE | APACONS | null/ATVDONR_CODE |
| A8.74 | Spouse Primary Donor Category Desc. SPOUSE_PREF_DONR_DESC | APACONS | null/ATVDONR_DESC |

Table 8: Designation Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|--|--|-----------|--|
| A8.75 | Spouse ID SPOUSE_ID | APACONS | null/SPRIDEN_ID |
| A8.76 | Spouse Designation Giving SPOUSE_DESG_GIVING | Function | F_DESIGNATION_GIVING Sum (APRDHIS_AMT_PLEDGED_PAID) + Sum (APRDHIS_AMT_GIFT) |
| A8.77 | Spouse Designation Pledged SPOUSE_DESG_PLEDGED | APADHIS | APRDHIS_AMT_PLEDGED |
| A8.78 | Spouse Designation Gifts SPOUSE_DESG_GIFT | APADHIS | APRDHIS_AMT_GIFT |
| A8.79 | Spouse Designation Payments SPOUSE_DESG_PAYMENT | APADHIS | APRDHIS_AMT_PLEDGED_PAID |
| A8.80 | Spouse Designation Matching Gifts SPOUSE_DESG_MATCHING_GIFT | Function | F_DESIGNATION_MATCHING_GIFT AGRMGIF_AMT_PAID for the designation |
| A8.81 | Spouse Designation Memo Credit (Non-matching) SPOUSE_DESG_MEMO_CREDIT | Function | F_DESIGNATION_MEMO_CREDIT APRDHIS_AMT_MEMO – (AGRMGIF_AMT_PAID for the designation) |
| <p>Select three Exclusions for the spouse using the logic defined for the Exclusion Code (Designation) concept on GTVSDAX.</p> <p>For more information about this concept, refer to the <i>GTVSDAX Handbook</i>. You can also go to GTVSDAX in Banner and query on Internal Code = <i>ALUMEXCL</i> and Internal Group = <i>DESG EXCLUSION</i>.</p> <p>Note: Be sure to refer to the correct Exclusion Code concept, because there is more than one.</p> | | | |
| A8.82 | Spouse Exclusion Code 1 SPOUSE_EXCL_CODE_1 | APAMAIL | APREXCL_EXCL_CODE |
| A8.83 | Spouse Exclusion Code Description 1 SPOUSE_EXCL_DESC_1 | APAMAIL | ATVEXCL_DESC |

Table 8: Designation Giving by ID View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A8.84 | Spouse Exclusion Date 1 SPOUSE_EXCLUSION_DATE_1 | APAMAIL | APREXCL_DATE |
| A8.85 | Spouse Exclusion Code 2 SPOUSE_EXCL_CODE_2 | APAMAIL | APREXCL_EXCL_CODE |
| A8.86 | Spouse Exclusion Code Description 2 SPOUSE_EXCL_DESC_2 | APAMAIL | ATVEXCL_DESC |
| A8.87 | Spouse Donor Exclusion Date 2 SPOUSE_EXCLUSION_DATE_2 | APAMAIL | APREXCL_DATE |
| A8.88 | Spouse Exclusion Code 3 SPOUSE_EXCL_CODE_3 | APAMAIL | APREXCL_EXCL_CODE |
| A8.89 | Spouse Exclusion Code Description 3 SPOUSE_EXCL_DESC_3 | APAMAIL | ATVEXCL_DESC |
| A8.90 | Spouse Exclusion Date 3 SPOUSE_EXCLUSION_DATE_3 | APAMAIL | APREXCL_DATE |
| A8.91 | Additional Donor Exclusion Codes Flag SPOUSE_ADD_EXCLUSION_FLAG | Function | F_CHECK_FOR_MORE If there are more than three exclusion codes, put a <i>Y</i> in this field. |

View 9: Gift Detail

AA_GIFT_DETAIL

If you are using FOCUS, the view name is AGVGFD0.

The Gift Detail view lets you report on an ID's gift credit. This view includes the donor's name, ID, and core personal data, and information about donor categories, gift campaign, gift designation, and gift solicitation.

This view accesses the following main database tables.

- ADBDESG Designation Base Table
- AFBCAMP Campaign Base Table
- AGBGIFT Gift/Pledge Payment Base Table
- AGRGDES Gift Designation Table
- AGRGMLT Gift Multiple ID Table
- AGRGSOL Gift Solicitor Repeating Table
- APBCONS Constituent Base Table
- SPBPERS Basic Person Base Table
- SPRIDEN Person Identification/Name Repeating Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) for a complete description of PIDM. ■

The key attributes of this view are:

- Donor Personal ID Master PIDM_KEY
- Gift Number GIFT_NO_KEY
- Pledge Number PLEDGE_NO_KEY
- Campaign CAMPAIGN_KEY
- Designation DESIGNATION_KEY

Because the PIDM is an internal ID unique to each ID, the view returns one row of information for each ID for every unique combination of Gift Number, Pledge Number, and Campaign/Designation. If a gift has multiple IDs, there is a row for each Campaign/Designation per multiple ID, and for the key ID.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view; however, you may find it useful to specify criteria for some or all of the following attributes. Specifying these criteria selects the population for a report and may reduce the time it takes to run the report.

- Campaign CAMPAIGN_KEY
- Designation DESIGNATION_KEY
- Fiscal Year FISC_CODE
- Gift Date GIFT_DATE
- Preferred Donor Category Code PREF_DONR_CODE

Attributes

The following list specifies the attributes included in the Gift Detail view. The list also indicates the primary Banner form and the database field or function that is the source for each attribute.

Table 9: Gift Detail View Attributes

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|--|-----------|-------------------------------|
| <p>Note: The table source of some attributes in this view depends on if the information is for a key ID or multiple IDs. Multi-source attributes are denoted using a slash (/). The table name to the left of the slash indicates the source if the <i>information relates to a key ID</i>. The table name to the right of the slash indicates the source if the <i>information relates to multiple ID</i>'.</p> | | | |
| A9.1 | Donor Personal ID Master Key PIDM_KEY | APAIDEN | AGRGDES / AGRGMLT_PIDM |
| A9.2 | Gift Number Key GIFT_NO_KEY | AGCGIFT | AGRGDES / AGRGMLT_GIFT_NO |
| A9.3 | Pledge Number Key PLEDGE_NO_KEY | AGCGIFT | AGRGDES / AGRGMLT_PLEDGE_NO |
| A9.4 | Campaign Key CAMPAIGN_KEY | AGCGIFT | AGRGDES / AGRGMLT_CAMPAIGN |
| A9.5 | Campaign Description CAMPAIGN_NAME | AFACAMP | AFBCAMP_NAME |

Table 9: Gift Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A9.6 | Designation DESIGNATION_KEY | AGCGIFT | AGRGDES / AGRGMLT_DESG |
| A9.7 | Designation Description DESIGNATION_NAME | ADADESG | ADBDESG_NAME |
| A9.8 | Donor Entity Indicator ENTITY_IND | N/A | SPRIDEN_ENTITY_IND |
| A9.9 | Donor Lost Alumnus Indicator LOST_ALUMNUS_IND | Function | F_LOST_AL_IND If alumnus has no active addresses, that is, the TO_DATE passed on all addresses or all addresses on SPRADDR have an I (Inactive) status, put a Y in this field. |
| A9.10 | Donor ID ID | APAIDEN | SPRIDEN_ID |
| A9.11 | Donor Social Security Number SSN | APAPERS | SPBPERS_SSN |
| A9.12 | Donor Surname Prefix | APAIDEN | SPRIDEN_SURNAME_PREFIX |
| A9.13 | Donor Last Name LAST_NAME | APAIDEN | SPRIDEN_LAST_NAME |
| A9.14 | Donor First Name FIRST_NAME | APAIDEN | SPRIDEN_FIRST_NAME |
| A9.15 | Donor Middle Name MIDDLE_NAME | APAIDEN | SPRIDEN_MI |
| A9.16 | Donor Middle Initial MIDDLE_INITIAL | APAIDEN | SUBSTR (SPRIDEN_MI , 1 , 1) Returns first letter of middle name |
| A9.17 | Donor Name Prefix NAME_PREFIX | APAIDEN | SPBPERS_NAME_PREFIX |

Table 9: Gift Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|---|---------------------|-------------------------------|
| A9.18 | Donor Name Suffix NAME_SUFFIX | APAIDEN | SPBPERS_NAME_SUFFIX |
| A9.19 | Donor Nickname NICKNAME | APANAME | APBCONS_NICKNAME |
| A9.20 | Donor Combined Mail Name COMBINED_MAIL_NAME | APANAME | APBCONS_CM_NAME |
| A9.21 | Donor Birth/Maiden Name BIRTH_MAIDEN_NAME | APANAME | APBCONS_MAIDEN_LAST_NAME |
| A9.22 | Donor Preferred Address Name PREF_ADDRESS_NAME | APANAME | APBCONS_ADDR_NAME |
| A9.23 | Donor Preferred Address Type PREF_ADDRESS_TYPE | APANAME | APBCONS_ATYP_CODE_PREF |
| A9.24 | Donor Deceased Indicator DECEASED_IND | APAPERS | SPBPERS_DEAD_IND |
| A9.25 | Donor Date of Death DECEASED_DATE | APAPERS | SPBPERS_DEAD_DATE |
| A9.26 | Donor Preferred College PREF_COLL | APACONS | APBCONS_COLL_CODE_PREF |
| A9.27 | Donor Preferred Class PREF_CLASS | APACONS | APBCONS_PREF_CLAS |
| <p>Get the four most preferred Donor Category Codes using the ATVDONR_RPT_SEQ_IND field which sorts Donor Categories by preference.</p> <p>Note: The source form of some donor category attributes depends on whether the donor is a person or a company. Multi-source attributes are denoted using a slash (/). The form name to the left of the slash indicates the source if the donor is a person. The form name to the right of the slash indicates the source if the donor is a company.</p> | | | |
| A9.28 | Preferred Donor Category Code PREF_DONR_CODE | APACONS/ AOAORGN | ATVDONR_CODE |

Table 9: Gift Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|---------------------|--|
| A9.29 | Preferred Donor Category Description PREF_DONR_DESC | APACONS/ AOAORGN | ATVDONR_DESC |
| A9.30 | Pref. Donor Category Alumni Indicator PREF_ALUM_IND | ATVDONR | ATVDONR_ALUM_IND |
| A9.31 | Other Donor Category Code 1 OTHER_DONR_CODE_1 | APACONS/ AOAORGN | ATVDONR_CODE |
| A9.32 | Other Donor Category 1 Description OTHER_DONR_DESC_1 | APACONS/ AOAORGN | ATVDONR_DESC |
| A9.33 | Other Donor Category Alumni Indicator 1 OTHER_ALUM_IND_1 | ATVDONR | ATVDONR_ALUM_IND |
| A9.34 | Other Donor Category Code 2 OTHER_DONR_CODE_2 | APACONS/ AOAORGN | ATVDONR_CODE |
| A9.35 | Other Donor Category 2 Description OTHER_DONR_DESC_2 | APACONS/ AOAORGN | ATVDONR_DESC |
| A9.36 | Other Donor Category Alumni Indicator 2 OTHER_ALUM_IND_2 | ATVDONR | ATVDONR_ALUM_IND |
| A9.37 | Other Donor Category Code 3 OTHER_DONR_CODE_3 | APACONS/ AOAORGN | ATVDONR_CODE |
| A9.38 | Other Donor Category 3 Description OTHER_DONR_DESC_3 | APACONS/ AOAORGN | ATVDONR_DESC |
| A9.39 | Other Donor Category Alumni Indicator 3 OTHER_ALUM_IND_3 | ATVDONR | ATVDONR_ALUM_IND |
| A9.40 | Additional Donor Categories Flag ADD_DONOR_CAT_FLAG | Function | F_CHECK_FOR_MORE If there are more than four donor categories, put a Y in this field. |

Table 9: Gift Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|--|
| A9.41 | Campaign Type Code CMTP_CODE | AFACAMP | AFBCAMP_CMTP_CODE |
| A9.42 | Campaign Type Description CMTP_DESC | AFACAMP | ATVCMTP_DESC |
| A9.43 | Gift Amount (0 if PIDM is a multiple ID) GIFT_AMT | Function | AGRGDES_AMT |
| A9.44 | Gift Credit Amount GIFT_CREDIT_AMT | Function | AGRGMLT_CREDIT F_GIFT_HARD_CREDIT |
| A9.45 | Gift Date GIFT_DATE | AGCGIFT | AGBGIFT_GIFT_DATE |
| A9.46 | Fiscal Year FISC_CODE | AGCGIFT | AGBGIFT_FISC_CODE |
| A9.47 | Gift Type Code GIFT_CODE | AGCGIFT | AGBGIFT_GIFT_CODE |
| A9.48 | Gift Type Description GIFT_DESC | AGCGIFT | AGBGIFT_GIFT_DESC |
| A9.49 | Gift Class Code GCLS_CODE | AGCGIFT | AGBGIFT_GCLS_CODE |
| A9.50 | Gift Class Description GCLS_DESC | AGCGIFT | ATVGCLS_DESC |
| A9.51 | Matching Gift? ('W', 'P', 'N') MATCHING_GIFT | Function | F_MATCHING_GIFT Existence of AGBMGID for AGVGCRD_GIFT_NO |
| A9.52 | Matching Gift Received GIFT_MATCH_RECEIVED | AGAGIFT | AGBGIFT_MATCH_RECEIVED |
| A9.53 | Gift Feed Date GIFT_FEED_DATE | AGAGIFT | AGBGIFT_FEED_DATE |

Table 9: Gift Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|-------------------------------|
| A9.54 | Gift Batch ID GIFT_BATCH_ID | AGAGIFT | AGBGIFT_FEED_DOC_CODE |
| A9.55 | Gift Entry User GIFT_ENTRY_USER | AGAGIFT | AGBGIFT_USER |
| A9.56 | Gift Entry Date GIFT_ENTRY_DATE | AGAGIFT | AGBGIFT_ENTRY_DATE |
| A9.57 | Non-Banner Finance Debit Account Number NON_FIN_DEBIT_ACCOUNT_NO | ATVGIFT | ATVGIFT_DB_GL_ACCT |
| A9.58 | Banner Finance Rule Class Code FIN_RULE_CLASS_CODE | ATVGIFT | ATVGIFT_RUCL_CODE |
| A9.59 | Gift VSE Category GIFT_CFAE_CATG | ATVGIFT | ATVGIFT_CFAE_GIFT_CATG |
| A9.60 | Designation Type Code DSTP_CODE | ADADESG | ADBDESG_DSTP_CODE |
| A9.61 | Designation Type Description DSTP_DESC | ADADESG | ATVDSTP_DESC |
| A9.62 | Designation College Code COLL_CODE | ADADESG | ADBDESG_COLL_CODE |
| A9.63 | College Description COLL_DESC | ADADESG | STV_COLL_DESC |
| A9.64 | Voluntary Support of Education Code CFAE_CODE | ADADESG | ADBDESG_CFAE_CODE |
| A9.65 | Voluntary Support of Education Description CFAE_DESC | ADADESG | ATVCFAE_DESC |

Table 9: Gift Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|-------------------------------|
| A9.66 | Non-Banner Finance General Ledger Number NON_FIN_GL_NO_CREDIT | ADADESG | ADBDESG_GL_NO_CREDIT |
| A9.67 | Chart of Accounts Code COAS_CODE | ADADESG | ADBDESG_COAS_CODE |
| A9.68 | Account Index Code ACCI_CODE | ADADESG | ADBDESG_ACCI_CODE |
| A9.69 | Fund Code FUND_CODE | ADADESG | ADBDESG_FUND_CODE |
| A9.70 | Organization Code ORGN_CODE | ADADESG | ADBDESG_ORGN_CODE |
| A9.71 | Account Code ACCT_CODE | ADADESG | ADBDESG_ACCT_CODE |
| A9.72 | Program Code PROG_CODE | ADADESG | ADBDESG_PROG_CODE |
| A9.73 | Activity Code ACTV_CODE | ADADESG | ADBDESG_ACTV_CODE |
| A9.74 | Location Code LOCN_CODE | ADADESG | ADBDESG_LOCN_CODE |
| A9.75 | Gift Solicitation Type Code SOLC_CODE | AGAGSOL | AGRGSQL_SOLC_CODE |
| A9.76 | Gift Solicitation Type Description SOLC_DESC | AGAGSOL | ATVSOLC_DESC |
| A9.77 | Gift Solicitor Organization GIFT_SOLICITOR_ORG | AGAGSOL | AGRGSQL_SOL_ORG |
| A9.78 | Gift Solicitor Personal ID Master GIFT_SOLICITOR_PIDM | AGAGSOL | AGRGSQL_SOL_PIDM |

Table 9: Gift Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|--|
| A9.79 | Gift Solicitor ID Number GIFT_SOLICITOR_ID | AGAGSOL | SPRIDEN_ID for AGRSOL_SOL_PIDM |
| A9.80 | Gift Solicitor Surname Prefix GIFT_SOLICITOR_SNAME_PRFX | APAIDEN | SPRIDEN_SURNAME_PREFIX for AGRSOL_SOL_PIDM |
| A9.81 | Gift Solicitor Last Name GIFT_SOLICITOR_LAST_NAME | Function | F_GIFT_SOLICITOR SPRIDEN_LAST_NAME for AGRSOL_SOL_PIDM |
| A9.82 | Gift Solicitor First Name GIFT_SOLICITOR_FIRST_NAME | AGAGSOL | SPRIDEN_FIRST_NAME for AGRSOL_SOL_PIDM |
| A9.83 | Gift Solicitation Amount GIFT_SOLICITOR_AMT | AGAGSOL | AGRSOL_AMT |
| A9.84 | Other Gift Solicitors Exist Flag GIFT_SOLICITOR_MORE | Function | F_GIFT_SOLICITOR_MORE |

View 10: Pledge Detail

AA_PLEDGE_DETAIL

If you are using FOCUS, the view name is AGVPLD0.

The Pledge Detail view lets you report on an ID's pledge credit. This view includes the donor's name, ID, and core personal data, and information about donor categories, pledge campaign, pledge designation, and pledge solicitation.

This view accesses the following main database tables.

- ADBDESG Designation Base Table
- AFBCAMP Campaign Base Table
- AGBPLDG Pledge Base Table
- AGRPDES Pledge Designation Table
- AGRPMLT Pledge Multiple ID Table
- AGRPSOL Pledge Solicitor Repeating Table
- APBCONS Constituent Base Table
- SPBPERS Basic Person Base Table
- SPRIDEN Person Identification/Name Repeating Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) for a complete description of PIDM. ■

The key attributes of this view are:

- Donor Personal ID Master PIDM_KEY
- Pledge Number PLEDGE_NO_KEY
- Campaign CAMPAIGN_KEY
- Designation DESIGNATION_KEY

Because the PIDM is an internal ID unique to each ID, the view returns one row of information for each ID for every Campaign/Designation combination of a pledge. If a pledge has multiple IDs, there is a row for each Campaign/Designation per multiple ID, and for the key ID.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view, but you may find it useful to specify criteria for some or all of the following attributes. Specifying these criteria selects the population for a report and may reduce the time it takes to run the report.

- Campaign CAMPAIGN_KEY
- Designation DESIGNATION_KEY
- Fiscal Year FISC_CODE
- Pledge Date PLEDGE_DATE
- Preferred Donor Category Code PREF_DONR_CODE

Attributes

The following list specifies the attributes included in the Pledge Detail view. The list also indicates the primary Banner form and the database field or function that is the source for each attribute.

Table 10: Pledge Detail View Attributes

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|--|-----------|-------------------------------|
| <p>Note: The table source of some attributes in this view depends on if the information is for a key ID or multiple IDs. Multi-source attributes are denoted using a slash (/). The table name to the left of the slash indicates the source if the <i>information relates to a key ID</i>. The table name to the right of the slash indicates the source if the <i>information relates to multiple IDs</i>.</p> | | | |
| A10.1 | Donor Personal ID Master Key PIDM_KEY | APAIDEN | AGRPDES / AGRPMLT_PIDM |
| A10.2 | Pledge Number Key PLEDGE_NO_KEY | AGCPLDG | AGRPDES / AGRPMLT_PLEDGE_NO |
| A10.3 | Campaign Key CAMPAIGN_KEY | AGCPLDG | AGRPDES / AGRPMLT_CAMPAIGN |
| A10.4 | Campaign Description CAMPAIGN_NAME | AFACAMP | AFBCAMP_NAME |
| A10.5 | Designation Key DESIGNATION_KEY | AGCPLDG | AGRPDES / AGRPMLT_DESG |

Table 10: Pledge Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A10.6 | Designation Description DESIGNATION_NAME | ADADESG | ADBDESG_NAME |
| A10.7 | Donor Entity Indicator ENTITY_IND | N/A | SPRIDEN_ENTITY_IND |
| A10.8 | Donor Lost Alumnus Indicator LOST_ALUMNUS_IND | Function | F_LOST_AL_IND If alumnus has no active addresses, that is, the TO_DATE passed on all addresses or all addresses on SPRADDR have an I (Inactive) status, put a Y in this field. |
| A10.9 | Donor ID ID | APAIDEN | SPRIDEN_ID |
| A10.10 | Donor Social Security Number SSN | APAPERS | SPBPERS_SSN |
| A10.11 | Donor Surname Prefix SURNAME_PREFIX | APAIDEN | SPRIDEN_SURNAME_PREFIX |
| A10.12 | Donor Last Name LAST_NAME | APAIDEN | SPRIDEN_LAST_NAME |
| A10.13 | Donor First Name FIRST_NAME | APAIDEN | SPRIDEN_FIRST_NAME |
| A10.14 | Donor Middle Name MIDDLE_NAME | APAIDEN | SPRIDEN_MI |
| A10.15 | Donor Middle Initial MIDDLE_INITIAL | APAIDEN | SUBSTR (SPRIDEN_MI , 1 , 1) Returns first letter of middle name |
| A10.16 | Donor Name Prefix NAME_PREFIX | APAIDEN | SPBPERS_NAME_PREFIX |
| A10.17 | Donor Name Suffix NAME_SUFFIX | APAIDEN | SPBPERS_NAME_SUFFIX |

Table 10: Pledge Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|--|---------------------|-------------------------------|
| A10.18 | Donor Nickname NICKNAME | APANAME | APBCONS_NICKNAME |
| A10.19 | Donor Combined Mail Name COMBINED_MAIL_NAME | APACONS/ APANAME | APBCONS_CM_NAME |
| A10.20 | Donor Birth/Maiden Name BIRTH_MAIDEN_NAME | APACONS/ APANAME | APBCONS_MAIDEN_LAST_NAME |
| A10.21 | Donor Preferred Address Name PREF_ADDRESS_NAME | APANAME | APBCONS_ADDR_NAME |
| A10.22 | Donor Preferred Address Type PREF_ADDRESS_TYPE | APANAME | APBCONS_ATYP_CODE_PREF |
| A10.23 | Donor Deceased Indicator DECEASED_IND | APAPERS | SPBPERS_DEAD_IND |
| A10.24 | Donor Date of Death DECEASED_DATE | APAPERS | SPBPERS_DEAD_DATE |
| A10.25 | Donor Preferred College PREF_COLL | APACONS | APBCONS_COLL_CODE_PREF |
| A10.26 | Donor Preferred Class PREF_CLASS | APACONS | APBCONS_PREF_CLAS |
| <p>Get the four most preferred Donor Category Codes using the ATVDONR_RPT_SEQ_IND field which sorts Donor Categories by preference.</p> <p>Note: The source form of some donor category attributes depends on whether the donor is a person or a company. Multi-source attributes are denoted using a slash (/). The form name to the left of the slash indicates the source if the donor is a person. The form name to the right of the slash indicates the source if the donor is a company.</p> | | | |
| A10.27 | Preferred Donor Category Code PREF_DONR_CODE | APACONS/ AOAORGN | ATVDONR_CODE |
| A10.28 | Preferred Donor Category Description PREF_DONR_DESC | APACONS/ AOAORGN | ATVDONR_DESC |

Table 10: Pledge Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|---------------------|--|
| A10.29 | Pref. Donor Category Alumni Indicator PREF_ALUM_IND | ATVDONR | ATVDONR_ALUM_IND |
| A10.30 | Other Donor Category Code 1 OTHER_DONR_CODE_1 | APACONS/ AOAORGN | ATVDONR_CODE |
| A10.31 | Other Donor Category 1 Description OTHER_DONR_DESC_1 | APACONS/ AOAORGN | ATVDONR_DESC |
| A10.32 | Other Donor Category Alumni Indicator 1 OTHER_ALUM_IND_1 | ATVDONR | ATVDONR_ALUM_IND |
| A10.33 | Other Donor Category Code 2 OTHER_DONR_CODE_2 | APACONS/ AOAORGN | ATVDONR_CODE |
| A10.34 | Other Donor Category 2 Description OTHER_DONR_DESC_2 | APACONS/ AOAORGN | ATVDONR_DESC |
| A10.35 | Other Donor Category Alumni Indicator 2 OTHER_ALUM_IND_2 | ATVDONR | ATVDONR_ALUM_IND |
| A10.36 | Other Donor Category Code 3 OTHER_DONR_CODE_3 | APACONS/ AOAORGN | ATVDONR_CODE |
| A10.37 | Other Donor Category 3 Description OTHER_DONR_DESC_3 | APACONS/ AOAORGN | ATVDONR_DESC |
| A10.38 | Other Donor Category Alumni Indicator 3 OTHER_ALUM_IND_3 | ATVDONR | ATVDONR_ALUM_IND |
| A10.39 | Additional Donor Categories Flag ADD_DONOR_CAT_FLAG | Function | F_CHECK_FOR_MORE If there are more than four donor categories, put a Y in this field. |

Table 10: Pledge Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|---|
| A10.40 | Campaign Type Code CMTP_CODE | AFACAMP | AFBCAMP_CMTP_CODE |
| A10.41 | Campaign Type Description CMTP_DESC | AFACAMP | ATVCMTP_DESC |
| A10.42 | Pledge Amount PLEDGE_AMT | Function | AGRPDES_AMT |
| A10.43 | Pledge Credit Amount PLEDGE_CREDIT_AMT | Function | AGRPMLT_CREDIT OR F_PLEDGE_HARD_CREDIT |
| A10.44 | Pledge Amount Paid PLEDGE_AMT_PAID | Function | AGRPDES_AMT_PAID |
| A10.45 | Pledge Date PLEDGE_DATE | AGCPLDG | AGBPLDG_PLEDGE_DATE |
| A10.46 | Fiscal Year FISC_CODE | AGCPLDG | AGBPLDG_FISC_CODE |
| A10.47 | Pledge Type Code PLDG_CODE | AGCPLDG | AGBPLDG_PLDG_CODE |
| A10.48 | Pledge Type Description PLDG_DESC | AGCPLDG | ATVPLDG_DESC |
| A10.49 | Pledge Class Code PCLS_CODE | AGCPLDG | AGBPLDG_PCLS_CODE |
| A10.50 | Pledge Class Description PCLS_DESC | AGCPLDG | ATVPCLS_DESC |
| A10.51 | Pledge Status Code PSTA_CODE | AGCPLDG | AGBPLDG_PSTA_CODE |
| A10.52 | Pledge Status Description PSTA_DESC | AGCPLDG | ATVPSTA_DESC |

Table 10: Pledge Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|-------------------------------|
| A10.53 | Non-Banner Finance Debit Account Number NON_FIN_DEBIT_ACCOUNT_NO | ATVPLDG | ATVPLDG_DB_GL_ACCT |
| A10.54 | Banner Finance Rule Class Code FIN_RULE_CLASS_CODE | ATVPLDG | ATVPLDG_RUCL_CODE |
| A10.55 | Gift VSE Category PLEDGE_CFAE_CATG | ATVPLDG | ATVPLDG_CFAE_GIFT_CATG |
| A10.56 | Designation Type Code DSTP_CODE | ADADESG | ADBDESG_DSTP_CODE |
| A10.57 | Designation Type Description DSTP_DESC | ADADESG | ATVDSTP_DESC |
| A10.58 | Designation College Code COLL_CODE | ADADESG | ADBDESG_COLL_CODE |
| A10.59 | College Description COLL_DESC | ADADESG | STV_COLL_DESC |
| A10.60 | Voluntary Support of Education Code CFAE_CODE | ADADESG | ADBDESG_CFAE_CODE |
| A10.61 | Voluntary Support of Education Description CFAE_DESC | ADADESG | ATVCFAE_DESC |
| A10.62 | Non-Banner Finance General Ledger Number NON_FIN_GL_NO_CREDIT | ADADESG | ADBDESG_GL_NO_CREDIT |
| A10.63 | Chart of Accounts Code COAS_CODE | ADADESG | ADBDESG_COAS_CODE |
| A10.64 | Account Index Code ACCI_CODE | ADADESG | ADBDESG_ACCI_CODE |

Table 10: Pledge Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|---|
| A10.65 | Fund Code FUND_CODE | ADADESG | ADBDESG_FUND_CODE |
| A10.66 | Organization Code ORGN_CODE | ADADESG | ADBDESG_ORGN_CODE |
| A10.67 | Account Code ACCT_CODE | ADADESG | ADBDESG_ACCT_CODE |
| A10.68 | Program Code PROG_CODE | ADADESG | ADBDESG_PROG_CODE |
| A10.69 | Activity Code ACTV_CODE | ADADESG | ADBDESG_ACTV_CODE |
| A10.70 | Location Code LOCN_CODE | ADADESG | ADBDESG_LOCN_CODE |
| A10.71 | Pledge Solicitation Type SOLC_CODE | AGAPSOL | AGRPSOL_SOLC_CODE |
| A10.72 | Pledge Solicitation Type Description SOLC_DESC | AGAPSOL | ATVSOLC_DESC |
| A10.73 | Pledge Solicitor Organization PLEDGE_SOLICITOR_ORG | AGAPSOL | AGRPSOL_SOL_ORG |
| A10.74 | Pledge Solicitor Personal ID Master PLEDGE_SOLICITOR_PIDM | AGAPSOL | AGRPSOL_SOL_pidm |
| A10.75 | Pledge Solicitor ID Number PLEDGE_SOLICITOR_ID | AGAPSOL | SPRIDEN_ID for AGRPSOL_SOL_PIDM |
| A10.76 | Pledge Solicitor Surname Prefix PLEDGE_SOLICITOR_SNAME_PRFX | APAIDEN | SPRIDEN_SURNAME_PREFIX for AGRSOL_SOL_PIDM |
| A10.77 | Pledge Solicitor Last Name PLEDGE_SOLICITOR_LAST_NAME | Function | F_PLEDGE_SOLICITOR SPRIDEN_LAST_NAME for AGRPSOL_SOL_PIDM |

Table 10: Pledge Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|--|
| A10.78 | Pledge Solicitor First Name PLEDGE_SOLICITOR_FIRST_NAME | AGAPSOL | SPRIDEN_FIRST_NAME for AGRGSOL_SOL_PIDM |
| A10.79 | Pledge Solicitation Amount PLEDGE_SOLICITOR_AMT | AGAPSOL | AGRPSOL_AMT |
| A10.80 | Additional Pledge Solicitation Flag PLEDGE_SOLICITOR_MORE | Function | F_PLEDGE_SOLICITOR_MORE |

View 11: Gift Memo Detail

AA_GIFT_MEMO_DETAIL

If you are using FOCUS, the view name is AGVGMD0.

The Gift Memo Detail view lets you report on gift memo credit. This view includes the donor's name, ID, and core personal data, and information about donor categories, the memo ID, campaign, gift, and designation.

This view accesses the following main database tables.

- ADBDESG Designation Base Table
- AFBCAMP Campaign Base Table
- APBCONS Constituent Base Table
- SPBPERS Basic Person Base Table
- SPRIDEN Person Identification/Name Repeating Table

Key Attributes



Tip

Refer to [“PIDM” on page 1-6](#) for a complete description of PIDM. ■

The key attributes of this view are:

- Key Personal ID Master PIDM_KEY
- Memo Personal ID Master MEMO_PIDM_KEY
- Gift Number GIFT_NO_KEY
- Pledge Number PLEDGE_NO_KEY
- Campaign CAMPAIGN_KEY
- Designation DESIGNATION_KEY

Because the PIDM is an internal ID unique to each ID, the view returns one row of information for each memo ID for every unique combination of Gift Number, Pledge Number, and Campaign/Designation.

Recommended/Mandatory Conditions

There are no mandatory conditions for this view, but you may find it useful to specify criteria for some or all of the following attributes. Specifying these criteria selects the population for a report and may reduce the time it takes to run the report.

- Campaign CAMPAIGN_KEY
- Designation DESIGNATION_KEY
- Fiscal Year FISC_CODE
- Gift Date GIFT_DATE
- Preferred Donor Category Code PREF_DONR_CODE

Attributes

The following list specifies the attributes included in the Gift Memo Detail view. The list also indicates the primary Banner form and the database field or function that is the source for each attribute.

Table 11: Gift Memo Detail View Attributes

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|-------------------------------|
| A11.1 | Key Personal ID Master Key PIDM_KEY | APAIDEN | AGVGMEM_PIDM |
| A11.2 | Memo Personal ID Master Key MEMO_PIDM_KEY | AGCGIFT | AGVGMEM_MEMO_PIDM |
| A11.3 | Gift Number Key GIFT_NO_KEY | AGCGIFT | AGVGMEM_GIFT_NO |
| A11.4 | Pledge Number Key PLEDGE_NO_KEY | AGCGIFT | AGVGMEM_PLEDGE_NO |
| A11.5 | Campaign Key CAMPAIGN_KEY | AGCGIFT | AGVGMEM_CAMPAIGN |
| A11.6 | Campaign Description CAMPAIGN_NAME | AFACAMP | AFBCAMP_NAME |
| A11.7 | Designation Key DESIGNATION_KEY | AGCGIFT | AGVGMEM_DESG |
| A11.8 | Designation Description DESIGNATION_NAME | ADADESG | ADBDESG_NAME |

Table 11: Gift Memo Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|--|
| A11.9 | Donor Entity Indicator ENTITY_IND | N/A | SPRIDEN_ENTITY_IND |
| A11.10 | Donor Lost Alumnus Indicator LOST_ALUMNUS_IND | Function | F_LOST_AL_IND If alumnus has no active addresses, that is, the TO_DATE passed on all addresses or all addresses on SPRADDR have an I (Inactive) status), put a Y in this field. |
| A11.11 | Donor ID ID | APAIDEN | SPRIDEN_ID |
| A11.12 | Donor Social Security Number SSN | APAPERS | SPBPERS_SSN |
| A11.13 | Donor Surname Prefix SURNAME_PREFIX | APAIDEN | SPRIDEN_SURNAME_PREFIX |
| A11.14 | Donor Last Name LAST_NAME | APAIDEN | SPRIDEN_LAST_NAME |
| A11.15 | Donor First Name FIRST_NAME | APAIDEN | SPRIDEN_FIRST_NAME |
| A11.16 | Donor Middle Name MIDDLE_NAME | APAIDEN | SPRIDEN_MI |
| A11.17 | Donor Middle Initial MIDDLE_INITIAL | APAIDEN | SUBSTR (SPRIDEN_MI , 1 , 1) Returns first letter of middle name |
| A11.18 | Donor Name Prefix NAME_PREFIX | APAIDEN | SPBPERS_NAME_PREFIX |
| A11.19 | Donor Name Suffix NAME_SUFFIX | APAIDEN | SPBPERS_NAME_SUFFIX |
| A11.20 | Donor Nickname NICKNAME | APAPERS | APBCONS_NICKNAME |

Table 11: Gift Memo Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|---|--|---------------------|-------------------------------|
| A11.21 | Donor Combined Mail Name COMBINED_MAIL_NAME | APANAME | APBCONS_CM_NAME |
| A11.22 | Donor Birth/Maiden Name BIRTH_MAIDEN_NAME | APANAME | APBCONS_MAIDEN_LAST_NAME |
| A11.23 | Donor Preferred Address Name PREF_ADDRESS_NAME | APANAME | APBCONS_ADDR_NAME |
| A11.24 | Donor Preferred Address Type PREF_ADDRESS_TYPE | APANAME | APBCONS_ATYP_CODE_PREF |
| A11.25 | Donor Deceased Indicator DECEASED_IND | APAPERS | SPBPERS_DEAD_IND |
| A11.26 | Donor Date of Death DECEASED_DATE | APAPERS | SPBPERS_DEAD_DATE |
| A11.27 | Donor Preferred College PREF_COLL | APACONS | APBCONS_COLL_CODE_PREF |
| A11.28 | Donor Preferred Class PREF_CLASS | APACONS | APBCONS_PREF_CLAS |
| <p>Get the four most preferred Donor Category Codes using the ATVDONR_RPT_SEQ_IND field which sorts Donor Categories by preference.</p> <p>Note: The source form of some donor category attributes depends on whether the donor is a person or a company. Multi-source attributes are denoted using a slash (/). The form name to the left of the slash indicates the source if the donor is a person. The form name to the right of the slash indicates the source if the donor is a company.</p> | | | |
| A11.29 | Preferred Donor Category Code PREF_DONR_CODE | APACONS/ AOAORGN | ATVDONR_CODE |
| A11.30 | Preferred Donor Category Description PREF_DONR_DESC | APACONS/ AOAORGN | ATVDONR_DESC |
| A11.31 | Pref. Donor Category Alumni Indicator PREF_ALUM_IND | ATVDONR | ATVDONR_ALUM_IND |

Table 11: Gift Memo Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|---------------------|--|
| A11.32 | Other Donor Category Code 1 OTHER_DONR_CODE_1 | APACONS/ AOAORGN | ATVDONR_CODE |
| A11.33 | Other Donor Category 1 Description OTHER_DONR_DESC_1 | APACONS/ AOAORGN | ATVDONR_DESC |
| A11.34 | Other Donor Category Alumni Indicator 1 ALUM_IND_1 | ATVDONR | ATVDONR_ALUM_IND |
| A11.35 | Other Donor Category Code 2 OTHER_DONR_CODE_2 | APACONS/ AOAORGN | ATVDONR_CODE |
| A11.36 | Other Donor Category 2 Description OTHER_DONR_DESC_2 | APACONS/ AOAORGN | ATVDONR_DESC |
| A11.37 | Other Donor Category Alumni Indicator 2 ALUM_IND_2 | ATVDONR | ATVDONR_ALUM_IND |
| A11.38 | Other Donor Category Code 3 OTHER_DONR_CODE_3 | APACONS/ AOAORGN | ATVDONR_CODE |
| A11.39 | Other Donor Category 3 Description OTHER_DONR_DESC_3 | APACONS/ AOAORGN | ATVDONR_DESC |
| A11.40 | Other Donor Category Alumni Indicator 3 ALUM_IND_3 | ATVDONR | ATVDONR_ALUM_IND |
| A11.41 | Additional Donor Categories Flag ADD_DONOR_CAT_FLAG | Function | F_CHECK_FOR_MORE If there are more than four donor categories, put a Y in this field. |

Table 11: Gift Memo Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|---|-----------|---|
| A11.42 | Memo ID Entity Indicator MEMO_ID_ENTITY_IND | N/A | SPRIDEN_ENTITY_IND |
| A11.43 | Memo ID Lost Alumnus Indicator MEMO_ID_LOST_ALUMNUS_IND | Function | F_LOST_AL_IND If alumnus has no active addresses, that is, the TO_DATE passed on all addresses or all addresses on SPRADDR have an I (Inactive) status, put a Y in this field. |
| A11.44 | ID for Memo ID MEMO_ID_ID | AGCGIFT | SPRIDEN_ID |
| A11.45 | Memo ID Surname Prefix MEMO_ID_SNAME_PRFX | APAIDEN | SPRIDEN_SURNAME_PREFIX |
| A11.46 | Memo ID Last Name MEMO_ID_LAST_NAME | AGCGIFT | SPRIDEN_LAST_NAME |
| A11.47 | Memo ID First Name MEMO_ID_FIRST_NAME | AGCGIFT | SPRIDEN_FIRST_NAME |
| A11.48 | Memo ID Middle Name MEMO_ID_MIDDLE_NAME | AGCGIFT | SPRIDEN_MIDDLE_NAME |
| A11.49 | Memo ID Deceased Indicator MEMO_ID_DECEASED_IND | APAPERS | SPBPERS_DEAD_IND |
| A11.50 | Memo ID Deceased Date MEMO_ID_DECEASED_DATE | APAPERS | SPBPERS_DEAD_DATE |
| A11.51 | Memo ID Preferred College MEMO_ID_PREF_COLL | APACONS | APBCONS_COLL_CODE_PREF |
| A11.52 | Memo ID Preferred Class Year MEMO_ID_PREF_CLASS | APACONS | APBCONS_PREF_CLAS |
| A11.53 | Memo ID Preferred Donor Category Code MEMO_ID_PREF_DONR_CODE | APACONS | ATVDONR_CODE |

Table 11: Gift Memo Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|--------------------------------|
| A11.54 | Memo ID Preferred Donor Category Desc. MEMO_ID_PREF_DONR_DESC | APACONS | ATVDONR_DESC |
| A11.55 | Memo ID Alumni Indicator MEMO_ID_ALUM_IND | Function | F_ALUM_IND ATVDONR_ALUM_IND |
| A11.56 | Campaign Type Code CMTP_CODE | AFACAMP | AFBCAMP_CMTP_CODE |
| A11.57 | Campaign Type Description CMTP_DESC | AFACAMP | ATVCMTP_DESC |
| A11.58 | Gift Designation Amount GIFT_DESG_AMT | AGCGIFT | AGVGMEM_DESG_AMT |
| A11.59 | Gift Designation Credit Amount GIFT_DESG_CREDIT_AMT | AGCGIFT | AGVGMEM_CREDIT |
| A11.60 | Gift Date GIFT_DATE | AGCGIFT | AGVGMEM_GIFT_DATE |
| A11.61 | Fiscal Year FISCAL_YEAR | AGCGIFT | AGVGMEM_FISC_CODE |
| A11.62 | Gift Type Code GIFT_CODE | AGCGIFT | AGVGMEM_GIFT_CODE |
| A11.63 | Gift Type Description GIFT_DESC | AGCGIFT | AGVGMEM_GIFT_DESC |
| A11.64 | Gift Class Code GCLS_CODE | AGCGIFT | AGVGMEM_GCLS_CODE |
| A11.65 | Gift Class Description GCLS_DESC | AGCGIFT | ATVGCLS_DESC |

Table 11: Gift Memo Detail View Attributes (cont)

| Ref. No. | Attribute | Form Name | Source Field or Function Name |
|----------|--|-----------|--|
| A11.66 | Matching Gift? ('Y'/'N') MATCHING_GIFT_IND | Function | F_MEMO_DETAIL_MATCHING_GIFT Existence of AGBMGID for AGVGMEM_GIFT_NO |
| A11.67 | Designation Type Code DSTP_CODE | ADADESG | ADBDESG_DSTP_CODE |
| A11.68 | Designation Type Description DSTP_DESC | ADADESG | ATVDSTP_DESC |
| A11.69 | Designation College Code COLL_CODE | ADADESG | ADBDESG_COLL_CODE |
| A11.70 | College Description COLL_DESC | ADADESG | STV_COLL_DESC |
| A11.71 | Voluntary Support of Education Code CFAE_CODE | ADADESG | ADBDESG_CFAE_CODE |
| A11.72 | Voluntary Support of Education Description CFAE_DESC | ADADESG | ATVCFAE_DESC |

